Series GAZELA

Flush mounting switches

screwless terminals
rated voltage 250V
rated current 16AX
maximum load 3520W
protection rating IP-20



ŁP-1J/00 347
Single pole switch



ŁP-2J/00 348
All-or-part switch, chandelier
ŁP-9J/00 353
Two-way + single pole switch
ŁP-10J/00 355
Double two-way switch



ŁP-3J/00 349
Two-way switch



ŁP-4J/00 350
Intermediate switch



ŁP-11J/00 357
Double pole switch

rated current 10AX
maximum load 2200W



ŁP-5J/00 351
Short-circuiting switch „light"



ŁP-6J/00 351
Short-circuiting switch „bell"



ŁP-7J/00 352
Venetian blind switch



ŁP-17J/00 1261
Double short-circuiting switch



ŁP-13J/00 356
Triple switch

Flush mounting switches with built-in light

screwless terminals
rated voltage 250V
rated current 16AX
maximum load 3520W
protection rating IP-20



ŁP-1JS/00 347
Single pole switch



ŁP-2JS/00 348
All-or-part switch, chandelier



ŁP-3JS/00 349
Two-way switch



ŁP-4JS/00 350
Intermediate switch



ŁP-11JS/00 357
Double pole switch



ŁP-12JS/00 358
Control switch



ŁP-15JS/00 512
Hotel switch

Hotel switch
rated voltage: 230V ~ 50Hz
protection rating: IP-20
rated current: 16A
time of delay: 3 sec.

Hotel switch co-operates with a standard card of size 86 x 54 x 0,8 mm

rated current 10AX
maximum load 2200W



ŁP-5JS/00 351
Short-circuiting switch „light"



ŁP-6JS/00 351
Short-circuiting switch „bell"



ŁP-7JS/00 352
Venetian blind switch

Accessories for switches with built-in light



KS-1 344
Capacitor for energy-saving fluorescent lamps



Accessories for switches IP-44



ZU-1J 359
Sealing set for switches IP-44



ROH-1J/00 359
Decorative, fixing surround for switches IP-44

There is a possibility to mount switches with protection rating IP-20 as switches with IP-44, to do that must be bought accessories above.

Electronic movement detector



ŁP-16J/00 510
Electronic movement detector

Screw terminals,
Rated voltage 230 V,
Load:
- incandescent 3200 W
- fluorescent 750 W
- inductive 750 W
Protection rating IP-20,
Way of adjustment of transmitter's switching on: 3 sec. – 5 min.
Angle of movement detection's field: 136°.
Field of activity: 7 m.

Temperature regulator



RTP-1J/00 509
Temperature regulator

Screw terminals,
Rated voltage 230 V,
Load:
- incandescent 3200 W
- inductive 750 W
Protection rating IP-20

Push-turn dimmers

screw terminals, current supply 230V~50Hz
load 60-400W, protection rating IP-20



ŁP-8JA/00 399
Push-turn dimmer, adapted to incandescent loading



ŁP-8JB/00 399
Push-turn dimmer, adapted to incandescent and halogen loading

Flush mounting socket outlets

screwless terminals, rated voltage 250V, rated current 16A, protection rating IP-20



GP-1J/00 375
Single socket



GP-1JP/00 375
Single socket with shutters



GP-1JZ/00 376
Single socket with ground



GP-1JZP/00 376
Single socket with ground, with shutters



GP-1JS/00 377
Single socket with ground schuko



GP-1JSP/00 377
Single socket with ground, schuko with shutters



GP-1JZD/00 381
Single socket with ground DATA



GP-1JZDP/00 381
Single socket with ground DATA, with shutters



GP-1JGZK/00 505
Single socket with ground DATA, with access key



GPH-1JZ/00/d 378
Splashproof socket with ground, IP-44



GPH-1JZP/00/d 378
Splashproof socket with ground, IP-44, with shutters



GPH-1JS/00/d 379
Splashproof single socket with ground schuko, IP-44

GPH-1JSP/00/d 379
Splashproof single socket with ground schuko, with shutters, IP-44

Flush mounting socket outlets

screw terminals, rated voltage 250V, rated current 16A, protection rating IP-20

GP-2J/00 382
Twin socket

GP-2JP/00 382
Twin socket with shutters

GP-2JZ/00 383
Twin socket with ground

GP-2JZP/00 383
Twin socket with ground, with shutters

GP-2JS/00 384
Twin socket with ground schuko

GP-2JSP/00 384
Twin socket with ground schuko, with shutters

GP-2JC/00 385
Twin socket without changing phase

GP-2JCP/00 385
Twin socket without changing phase, with shutters

Triple socket EURO



Screw terminals,
Rated voltage 230V,
Rated current 2,5A
Protection rating IP-20

GP-3J/00 577
Triple socket EURO

Flush mounting socket outlets

connection of lines ability: 0,75 mm²



GG-1J/00 395
Single loudspeaker socket



GG-2J/00 395
Twin loudspeaker socket



GPT-1J/00 389
Single telephone socket



GPT-2JN/00 390
Twin telephone socket, independent
GPT-2JR/00 390
Twin telephone socket, parallel

Flush mounting socket outlets

connection IDC



GPK-1J/K/00 391
Single computer socket, 5e class, KRONE
GPK-1J/F/00 391
Single computer socket, 5e class, FOREX
GPK-1J/K6/00 589
Single computer socket, 6 class, KRONE
GPK-1J/K6E/00 589
Single computer socket, 6 class, shielded, KRONE



GPK-2J/K/00 393
Twin computer socket, 5e class, KRONE
GPK-2J/F/00 393
Twin computer socket, 5e class, FOREX
GPK-2J/K6/00 590
Twin computer socket, 6 class, KRONE
GPK-2J/K6E/00 590
Twin computer socket, 6 class, shielded, KRONE



GPKT-J/K/00 394
Conjunct computer and telephone socket, KRONE
GPKT-J/F/00 394
Conjunct computer and telephone socket, FOREX
GPKT-J/K6/00 591
Conjunct computer (6 class) and telephone socket, KRONE
GPKT-J/K6E/00 591
Conjunct computer (6 class, shielded) and telephone socket, KRONE

Flush mounting socket outlets screw terminals



GPA-JK/00 388
Terminal antenna RTV subscriber



GPA-10JP/00 386
Through antenna RTV subscriber, attenuation coefficient 10dB
GPA-14JP/00 386
Through antenna RTV subscriber, attenuation coefficient 14dB
GPA-16JP/00 386
Through antenna RTV subscriber, attenuation coefficient 16dB



GPA-10JPZ/00 386
Through antenna RTV subscriber



GPA-JS/00 387
Terminal antenna RTV-SAT subscriber, attenuation coefficient 1,5-2dB
GPA-JSP/00 583
Through antenna RTV-SAT subscriber, attenuation coefficient 1,2 dB



GPA-J2S/00 605
Terminal antenna RTV-SAT subscriber with two outlets SAT

Surrounds

Surrounds are offered in following colours: 00 - white, 01 - beige, 11 - willow green, 16 - satin and 18 - silver.
After right code of surround please write the right number of wanted colour.



R-1J/00 404
Single surround



R-2JH/00 410
Twin horizontal surround
R-2JV/00 410
Twin vertical surround



R-3JH/00 411
Threefold horizontal surround
R-3JV/00 411
Threefold vertical surround



R-4JH/00 412
Fourfold horizontal surround
R-4JV/00 412
Fourfold vertical surround



R-5JH/00 491
Fivefold horizontal surround

Wall frames



PNP-1J/00 498
Single wall frame



PNP-2JH/00 518
Twin, horizontal wall frame
PNP-2JV/00 518
Twin, vertical wall frame



PNP-3JH/00 519
Threefold, horizontal wall frame
PNP-3JV/00 519
Threefold, vertical wall frame



PNP-4JH/00 520
Fourfold, horizontal wall frame
PNP-4JV/00 520
Fourfold, vertical wall frame



PNP-5JH/00 522
Fivefold, horizontal wall frame

Available colours

Products of GAZELA series are offered as a white product without external surround, available in colours: 01 - beige, 11 - willow green, 16 - satin and 18 - silver.



ŁP-1J/m + R-1J/01 = ŁP-1J

Designations:

ŁP-…..J/m/00 – switches - In the place marked by dots, write the right number of switch
ŁP-…..JS/m/00 – switches with built in light - In the place marked by dots, write the right number of switch
GP-1J/m/00 – single socket
GP-1JP/m/00 – single socket with shutters
GP-1JZ/m/00 – single socket with ground
GP-1JZP/m/00 – single socket with ground, with shutters
GP-1JS/m/00 – single socket with ground schuko
GP-1JSP/m/00 – single socket with ground schuko, with shutters
GP-1JZD/m/00 – single socket with ground DATA
GP-1JZDP/m/00 – single socket with ground DATA, with shutters
GP-1JGZK/m/00 – single socket with ground DATA, with key
GPH-1JZ/m/00/d – splashproof socket with ground IP-44
GPH-1JZP/m/00/d – splashproof socket with ground IP-44, with shutters
GPH-1JS/m/00/d – splashproof socket with ground schuko, IP-44
GPH-1JSP/m/00/d – splashproof socket with ground schuko, IP-44, with shutters
GP-2J/m/00 – twin socket
GP-2JP/m/00 – twin socket with shutters
GP-2JZ/m/00 – twin socket with ground
GP-2JZP/m/00 – twin socket with ground, with shutters
GP-2JS/m/00 – twin socket with ground schuko
GP-2JSP/m/00 – twin socket with ground schuko, with shutters
GP-2JC/m/00 – twin socket without changing phase
GP-2JCP/m/00 – twin socket without changing phase, with shutters
GP-3J/m/00 – triple socket EURO
GPT-1J/m/00 – single telephone socket
GPT-2JN/m/00 – twin telephone socket, independent
GPT-2JR/m/00 – twin telephone socket, parallel
GPA-JK/m/00 – terminal antenna RTV subscriber
GPA-10JPZ/m/00 – antenna RTV subscriber
GPA-10JP/m/00 – through antenna RTV subscriber
GPA-14JP/m/00 – through antenna RTV subscriber
GPA-16JP/m/00 – through antenna RTV subscriber
GPA-JS/m/00 – antenna RTV-SAT subscriber
GPA-JSP/m/00 – through antenna RTV-SAT subscriber
GPA-J2S/m/00 – terminal antenna RTV-SAT subscriber with two outlets SAT
GG-1J/m/00 – single loudspeaker socket
GG-2J/m/00 – twin loudspeaker socket
GPK-1J/K/m/00 – single computer socket, 5 class, KRONE
GPK-1J/F/m/00 – single computer socket, 5 class, FOREX
GPK-1J/K6/m/00 – single computer socket, 6 class,KRONE
GPK-1J/K6E/m/00 – single computer socket, 6 class, shielded, KRONE
GPK-2J/K/m/00 – twin computer socket, 5 class, KRONE
GPK-2J/F/m/00 – twin computer socket, 5 class, FOREX
GPK-2J/K6/m/00 – twin computer socket, 6 class, KRONE
GPK-2J/K6E/m/00 – twin computer socket, 6 class, shielded, KRONE
GPKT-J/K/m/00 – conjunct computer and telephone socket, KRONE
GPKT-J/F/m/00 – conjunct computer and telephone socket, FOREX
GPKT-J/K6/m/00 – conjunct computer (6 class) and telephone socket, KRONE
GPKT-J/K6E/m/00 – conjunct computer (6 class, shielded) and telephone socket, KRONE

Surrounds



R-1J/01 - surround for switches and single sockets

RG-1J/01 - surround for twin sockets

Surrounds are offered in following colours: 01 - beige, 11 - willow green, 16 - satin and 18 - silver. After right code of product please write the right number of colour.

Metallized colours



ŁP-1J/16/16 satin + satin
ŁP-1JS/16/16 satin + satin
GP-2J/16/16 satin + satin
ŁP-1J/18/23 silver + titanium
ŁP-1JS/18/23 silver + titanium
GP-2J/18/23 silver + titanium



Presented colours are offered for all products of GAZELA series. After right product code please use the right number of colour, according to the presentation. Products in metallized colours can be bought without external surround.

Series TON

Flush mounting switches

screwless terminals, rated voltage 250V
rated current 16AX , maximum load 3520W
protection rating IP-20



ŁP-1C/00 126
Single pole switch

ŁP-2C/00 127
All-or-part switch, chandelier
ŁP-9C/00 469
Two-way + single pole switch
ŁP-10C/00 458
Double two-way switch

ŁP-3C/00 128
Two-way switch

ŁP-4C/00 129
Intermediate switch

rated current 10AX
maximum load 2200W



ŁP-5C/00 130
Short-circuiting switch „light"

ŁP-6C/00 131
Short-circuiting switch „bell"

ŁP-7C/00 132
Venetian blind switch

Flush mounting switches with built-in light

screwless terminals, rated voltage 250V, rated current 16AX ,
maximum load 3520W, protection rating IP-20



ŁP-1CS/00 133
Single pole switch

ŁP-2CS/00 134
All-or-part switch, chandelier
ŁP-9CS/00 470
Two-way + single pole switch
ŁP-10CS/00 459
Double two-way switch

ŁP-3CS/00 135
Two-way switch

ŁP-4CS/00 136
Intermediate switch

rated current 10AX
maximum load 2200W



ŁP-5CS/00 137
Short-circuiting switch „light"

ŁP-6CS/00 138
Short-circuiting switch „bell"

ŁP-7CS/00 139
Venetian blind switch

Flush mounting splashproof switches

screwless terminals, rated voltage 250V, rated current 16AX ,
maximum load 3520W, protection rating IP-44



ŁPH-1C/00 173
Single pole switch

ŁPH-2C/00 174
All-or-part switch, chandelier

ŁPH-3C/00 175
Two-way switch

ŁPH-4C/00 176
Intermediate switch

rated current 10AX
maximum load 2200W



ŁPH-5C/00 177
Short-circuiting switch „light"

ŁPH-6C/00 178
Short-circuiting switch „bell"

ŁPH-7C/00 179
Venetian blind switch

Flush mounting, splashproof switches with built-in light

screwless terminals, rated voltage 250V, rated current 16AX ,
maximum load 3520W, protection rating IP-44

rated current 10AX
maximum load 2200W



ŁPH-1CS/00 180
Single pole switch

ŁPH-2CS/00 181
All-or-part switch, chandelier

ŁPH-3CS/00 182
Two-way switch

ŁPH-4CS/00 183
Intermediate switch

ŁPH-5CS/00 184
Short-circuiting switch „light"

ŁPH-6CS/00 185
Short-circuiting switch „bell"

ŁPH-7CS/00 186
Venetian blind switch

Flush mounting socket outlets

screw terminals, rated voltage 250V, rated current 16A,
maximum load 3520W, protection rating IP-20



GP-1C/00 156
Single socket

GP-1CP/00 156
Single socket with shutters

GP-1CZ/00 157
Single socket with ground

GP-1CZP/00 157
Single socket with ground, with shutters

GP-1CS/00 187
Single socket with ground schuko

GP-1CSP/00 187
Single socket with ground schuko, with shutters



GP-1CZD/00 172
Single socket with ground DATA

GP-1CZDP/00 172
Single socket with ground DATA, with shutters

GP-1CZK/00 429
Single socket with ground DATA, with access key

GPH-1CZ/00/d 160
Splashproof single socket with ground, IP-44

GPH-1CZP/00/d 160
Splashproof single socket with ground, with shutters, IP-44

GPH-1CS/00/d 189
Splashproof single socket with ground schuko, IP-44

GPH-1CSP/00/d 189
Splashproof single socket with ground schuko, with shutters, IP-44

Push-turn dimmers

60-400W
230V~50Hz
screw terminals



ŁP-8CA/00 192
Push-turn dimmer adapted to incandescent loading

ŁP-8CB/00 192
Push-turn dimmer adapted to incandescent and halogen loading



Flush mounting socket outlets

screw terminals, rated voltage 250V, rated current 16A,
maximum load 3520W, protection rating IP-20



GP-2C/00 158
Twin socket

GP-2CP/00 158
Twin socket with shutters

GP-2CZ/00 159
Twin socket with ground

GP-2CZP/00 159
Twin socket with ground, with shutters

GP-2CC/00 499
Twin socket with ground, without changing phase

GP-2CS/00 188
Twin socket with ground schuko

GP-2CSP/00 188
Twin socket with ground schuko, with shutters

Triple socket EURO

Screw terminals,
Rated voltage 230V,
Rated current 2,5A
Protection rating IP-20



GP-3C/00 608
Triple socket EURO

Flush mounting special sockets

screw terminals



GPA-1C/00 487
Single, terminal antenna RTV subscriber

GPA-CK/00 164
Terminal antenna RTV subscriber, attenuation coefficient: 2,5 - 3dB

GPA-10CP/00 166
Through antenna RTV subscriber, attenuation coefficient: 10dB

GPA-14CP/00 167
Through antenna RTV subscriber, attenuation coefficient: 14dB

GPA-16CP/00 168
Through antenna RTV subscriber, attenuation coefficient: 16dB

GPA-10CP2/00 165
Through antenna RTV subscriber

GPA-CS/00 169
Terminal antenna RTV - SAT subscriber, attenuation coefficient: 1,5-2 dB

GPA-CSP/00 582
Through antenna RTV - SAT subscriber, attenuation coefficient: 1,2 dB

GPA-C2S/00 606
Terminal antenna RTV-SAT subscriber with two outlets SAT

Flush mounting special sockets

screwless terminals



GPK-1C/R/00 170
Single computer socket, 5e class, R&M

GPK-1C/K/00 170
Single computer socket, 5e class, KRONE

GPK-1C/F/00 170
Single computer socket, 5e class, FOREX

GPK-1C/K6/00 586
Single computer socket, 6 class, KRONE

GPK-1C/K6E/00 586
Single computer socket, 6 class, shielded, KRONE

GPK-2C/R/00 171
Twin computer socket,5e class, R&M

GPK-2C/K/00 171
Twin computer socket, 5e class, KRONE

GPK-2C/F/00 171
Twin computer socket,,5e class, FOREX

GPK-2C/K6/00 587
Twin computer socket, 6 class, KRONE

GPK-2C/K6E/00 587
Twin computer socket, 6 class, shielded, KRONE

GPKT-C/K/00 428
Conjunct computer and telephone socket, KRONE

GPKT-C/F/00 428
Conjunct computer and telephone socket, FOREX

GPKT-C/K6/00 588
Conjunct computer (6 class) and telephone socket, KRONE

GPKT-C/K6E/00 588
Conjunct computer (6 class, shielded) and telephone socket, KRONE

Flush mounting special sockets

connection of lines ability: 0,75 mm²



GG-1C/00 413
Single loudspeaker socket

GG-2C/00 413
Twin loudspeaker socket



GPT-1C/00 161
Single telephone socket

GPT-2CN/00 162
Twin telephone socket, independent

GPT-2CR/00 163
Twin telephone socket, parallel

Surrounds



R-1C/00 194
Single surround

R-2CH/00 195
R-2CV/00 196
Twin horizontal surround/ Twin vertical surround

R-3CH/00 197
R-3CV/00 198
Threefold horizontal surround/ Threefold vertical surround



R-4CH/00 202
R-4CV/00 576
Fourfold horizontal surround/ Fourfold vertical surround

R-5CH/00 567
Fivefold horizontal surround

Wall frames for articles of Ton series



PNP-1C/00 476
Single wall frame



PNP-2CH/00 515
Twin wall frame, horizontal
PNP-2CV/00 515
Twin wall frame, vertical



PNP-3CH/00 516
Threefold wall frame, horizontal



PNP-4CH/00 517
Fourfold wall frame, horizontal

Available colours: pastel colours

Product is sold as a product with white, internal surround, pastel surround must be bought separately.



Beige



Blue



Willow green



Decorative, internal surrounds:



RO-1C/11 10-126-02
Surround for switches



RO-2C/11 10-156-01
Surround for single sockets



RO-3C/11 10-158-02
Surround for twin sockets
RO-4C/11 10-188-03
Surround for twin sockets schuko

Decorative surrounds are available in colours: beige - 01, blue - 09 and willow green - 11. After right code of surround please use the number of wanted colour.

Accessories for switches IP-44



ZU-1C 160
Sealing set for switches IP-44



ROH-1C/00 173
Decorative, fixing surround for switches IP-44

Accessories for switches with built-in light

KS-1 344
Capacitor for energy-saving fluorescent lamps

Metallized colours

Presented colours are offered for all products of Ton series. After right product code please use the right number of colour, according to the presentation below



ŁP-1C/18/16
Silver+satin



ŁP-1C/18/19
Silver+copper



ŁP-1C/21/18
Graphite+silver



ŁP-1C/16/19
Satin+copper



ŁP-1C/16/20
Satin+gold

Series TON COLOR SYSTEM

Products of Ton series are offered as a white product without external surround, available in 13 colours.



ŁP-1C/m

+



R-1C/11
willow green

=



ŁP-1C



Designations:

ŁP-.....C/m/00 – switches - In the place marked by dots, write the right number of switch
ŁP-.....CS/m/00 – switches with built in light - In the place marked by dots, write the right number of switch
ŁPH-.....C/m/00 – switches - In the place marked by dots, write the right number of switch
ŁPH-.....CS/m/00 – switches with built in light - In the place marked by dots, write the right number of switch
ŁP-8CA/m/00 – push-turn dimmer adapted to incandescent loading
ŁP-8CB/m/00 – push-turn dimmer adapted to incandescent and halogen loading
GP-1C/m/00 – single socket
GP-1CP/m/00 – single socket with shutters
GP-1CZ/m/00 – single socket with ground
GP-1CZP/m/00 – single socket with ground, with shutters
GP-1CZD/m/00 – single socket with ground DATA
GP-1CZDP/m/00 – single socket with ground DATA, with shutters
GP-1CZK/m/00 – single socket with ground DATA, with key
GP-1CS/m/00 – single socket with ground schuko
GP-1CSP/m/00 – single socket with ground schuko, with shutters
GPH-1CZ/m/00/d – splashproof socket with ground IP-44
GPH-1CZP/m/00/d – splashproof socket with ground IP-44, with shutters
GPH-1CS/m/00/d – splashproof socket with ground schuko, IP-44
GPH-1CSP/m/00/d – splashproof socket with ground schuko, IP-44, with shutters
GPT-1C/m/00 – single telephone socket
GPT-2CN/m/00 – twin telephone socket, independent
GPT-2CR/m/00 – twin telephone socket, parallel
GPA-1C/m/00 – terminal antenna RTV subscriber
GPA-CK/m/00 – terminal antenna RTV subscriber
GPA-10CPZ/m/00 – through antenna RTV subscriber
GPA-10CP/m/00 – through antenna RTV subscriber, 10 dB
GPA-14CP/m/00 – through antenna RTV subscriber, 14 dB
GPA-16CP/m/00 – through antenna RTV subscriber, 16 dB
GPA-CS/m/00 – terminal antenna RTV - SAT subscriber
GPA-CSP/m/00 – through antenna RTV - SAT subscriber
GPA-C2S/m/00 – terminal antenna RTV - SAT subscriber with two outlets SAT
GG-1C/m/00 – single loudspeaker socket
GG-2C/m/00 – twin loudspeaker socket
GPK-1C/R/m/00 – single computer socket, 5 class, R&M
GPK-1C/K/m/00 – single computer socket, 5 class, KRONE
GPK-1C/F/m/00 – single computer socket, 5 class, FOREX
GPK-1C/K6/m/00 – single computer socket, 6 class, KRONE
GPK-1C/K6E/m/00 – single computer socket, 6 class, shielded, KRONE
GPK-2C/R/m/00 – twin computer socket, 5 class, R&M
GPK-2C/K/m/00 – twin computer socket, 5 class, KRONE
GPK-2C/F/m/00 – twin computer socket, 5 class, FOREX
GPK-2C/K6/m/00 – twin computer socket, 6 class, KRONE
GPK-2C/K6E/m/00 – twin computer socket, 6 class, shielded, KRONE
GPKT-C/K/m/00 – conjunct computer and telephone socket, KRONE
GPKT-C/F/m/00 – conjunct computer and telephone socket, FOREX
GPKT-C/K6/m/00 – conjunct computer (6 class) and telephone socket, KRONE
GPKT-C/K6E/m/00 – conjunct computer (6 class, shielded) and telephone socket, KRONE

Surrounds

single and multiple, horizontal and vertical.
After right code of surround, please use the number of wanted colour, according to the presentation below



Presented colours can slightly differ from the original.



Series EFEKT

Flush mounting switches

screwless terminals, rated voltage 250V, rated current 10AX , maximum load 2200W, protection rating IP-20



ŁP-1FB/00 916
Single pole switch

ŁP-2FB/00 917
All-or-part switch, chandelier
ŁP-2FB-A/00 982
Two-way + single pole switch
ŁP-2FB-B/00 977
Double two-way switch

ŁP-3FB/00 918
Two-way switch

ŁP-4FB/00 919
Intermediate switch

ŁP-5FB/00 920
Short-circuiting switch „light"

ŁP-6FB/00 921
Short-circuiting switch „bell"

ŁP-7FB/00 940
Venetian blind switch

Flush mounting switches with built-in light



ŁP-1FBS/00 922
Single pole switch

ŁP-2FBS/00 923
All-or-part switch, chandelier
ŁP-2FBS-A/00 983
Two-way + single pole switch
ŁP-2FBS-B/00 978
Double two-way switch

ŁP-3FBS/00 924
Two-way switch

ŁP-4FBS/00 925
Intermediate switch

ŁP-5FBS/00 926
Short-circuiting switch „light"

ŁP-6FBS/00 927
Short-circuiting switch „bell"

ŁP-7FBS/00 941
Venetian blind switch

Electronic switch



ŁP-14F/00 321
Electronic switch

Electronic switches are sold with box ø 60, depth 60mm

ŁP-14FS/00 321
Electronic switch with built-in-light

rated voltage: 230V ~ 50Hz
way of adjustment: smooth
rated current: 10A
time delay of switching off: 10 sec. - 5min.
protection rating: IP-20

Flush mounting socket outlets

screw terminals, rated voltage 250V, rated current 16A, maximum load 3520W, protection rating IP-20



GP-1F/00 928
Single socket

GP-1FZ/00 929
Single socket with ground

GP-1FZD/00 149
Single socket with ground DATA

GP-1FZK/00 997
Single socket with ground DATA, with access key



GP-1FS/00 933
Single socket with ground schuko

GP-1FSP/00 933
Single socket with ground schuko, with shutters

GPH-1FZ/00/d 932
Splashproof socket with ground, IP-44

GPH-1FS/00/w 272
Splashproof socket with ground schuko, IP-44

GPH-1FSP/00/w 272
Splashproof socket with ground schuko, IP-44, with shutters

Push-turn dimmers

load: 60 – 400W, current supply: 230V~50Hz
protection rating: IP-20, screw terminals



ŁP-8FA/00 251
Push-turn dimmer adapted to incandescent loading



ŁP-8FB/00 251
Push-turn dimmer adapted to incandescent and halogen loading

Flush mounting socket outlets

screw terminals, rated voltage 250V, rated current 16A , maximum load 3520W, protection rating IP-20



GP-2F/00 930
Twin socket



GP-2FZ/00 931
Twin socket with ground



GP-2FC/00 953
Twin socket with ground, without changing phase



GP-2FS/00 271
Twin socket with ground schuko



GP-2FSP/00 271
Twin socket with ground schuko, with shutters

Flush mounting socket outlets

screw terminals



GPA-1F/00 504
Single terminal antenna RTV subscriber



GPA-FK/00 934
Terminal antenna RTV subscriber, attenuation coefficient 2,5-3dB



GPA-10FP/00 935
Through antenna RTV subscriber, attenuation coefficient 10dB
GPA-14FP/00 936
Through antenna RTV subscriber, attenuation coefficient 14dB
GPA-16FP/00 937
Through antenna RTV subscriber, attenuation coefficient 16dB



GPA-10FPZ/00 911
Through antenna RTV subscriber



GPA-FS/00 952
Terminal antenna RTV-SAT subscriber, attenuation coefficient 1,5-2dB
GPA-FSP/00 581
Through antenna RTV-SAT subscriber, attenuation coefficient 1,2 dB



GPA-F2S/00 607
Terminal antenna RTV-SAT subscriber with two outlets SAT

Flush mounting socket outlets

screwless terminals



GPK-1F/K/00 950
Single computer socket, 5e class, KRONE
GPK-1F/F/00 950
Single computer socket, 5e class, FOREX
GPK-1F/K6/00 592
Single computer socket, 6 class, KRONE
GPK-1F/K6E/00 592
Single computer socket, 6 class, shielded, KRONE



GPK-2F/K/00 944
Twin computer socket, 5e class, KRONE
GPK-2F/F/00 944
Twin computer socket, 5e class, FOREX
GPK - 2F/K6/00 593
Twin computer socket, 6 class, KRONE
GPK-2F/K6E/00 593
Twin computer socket, 6 class, shielded, KRONE



GPKT-F/K/00 980
Conjunct computer and telephone socket, KRONE
GPKT-F/F/00 980
Conjunct computer and telephone socket, FOREX
GPKT-F/K6/00 594
Conjunct computer (6 class) and telephone socket, KRONE
GPKT-F/K6E/00 594
Conjunct computer (6 class, shielded) and telephone socket, KRONE

Triple socket EURO

Screw terminals,
Rated voltage 230V,
Rated current 2,5A
Protection rating IP-20



GP-3F/00 609
Triple socket EURO

Flush mounting sockets outlets

Connection of lines ability: 0,75 mm²



GG-1F/00 263
Single loudspeaker socket



GG-2F/00 263
Twin loudspeaker socket

Flush mounting sockets outlets



GPT-1F/00 938
Single telephone socket



GPT-2FN/00 939
Twin telephone socket, independent
GPT-2FR/00 951
Twin telephone socket, parallel

Surrounds



R-1F/00 949
Single surround



R-2FH/00 945
Twin horizontal surround
R-2FV/00 946
Twin vertical surround



R-3FH/00 947
Threefold horizontal surround
R-3FV/00 948
Threefold vertical surround



R-4FH/00 955
Fourfold horizontal surround

Accessories for switches with built-in light



KS-1 344
Capacitor for energy-saving fluorescent lamps

Wall frames for articles of Efekt series



PN-1F/00 998
Single wall frame



PN-2F/00 199
Twin wall frame



PN-3F/00 200
Threefold wall frame



EFEKT METALIC

products of Efekt series in metallized colours



ŁP-1FB/18 SILVER



ŁP-1FB/16 SATIN



ŁP-1FB/17 SANDY



ŁP-1FB/21 GRAPHITE

After right code of product please use the right letters according to the presentation below.