
Control and signalling units Ø 22
Harmony® XB4, metal
Pilot lights with integral LED

Assembly of other products using:
body/light assemblies: see page 36068-EN/10
accessories: see pages 36069-EN/2 and 36070-EN/2



XB4 BVB5

Pilot lights with integral LED
Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Supply voltage V	Colour	Reference	Weight kg
Complete units				
■ With plain lens				
Protected LED	⎓ 24 (50/60 Hz)	White	**XB4 BVB1** (ZB4 BVB1 + ZB4 BV013)	0.080
		Green	**XB4 BVB3** (ZB4 BVB3 + ZB4 BV033)	0.080
		Red	**XB4 BVB4** (ZB4 BVB4 + ZB4 BV043)	0.080
		Orange	**XB4 BVB5** (ZB4 BVB5 + ZB4 BV053)	0.080
		Blue	**XB4 BVB6** (ZB4 BVB6 + ZB4 BV063)	0.080
	∼ 110...120 (50/60 Hz)	White	**XB4 BVG1** (ZB4 BVG1 + ZB4 BV013)	0.080
		Green	**XB4 BVG3** (ZB4 BVG3 + ZB4 BV033)	0.080
		Red	**XB4 BVG4** (ZB4 BVG4 + ZB4 BV043)	0.080
		Orange	**XB4 BVG5** (ZB4 BVG5 + ZB4 BV053)	0.080
		Blue	**XB4 BVG6** (ZB4 BVG6 + ZB4 BV063)	0.080
	∼ 230...240 (50/60 Hz)	White	**XB4 BVM1** (ZB4 BVM1 + ZB4 BV013)	0.080
		Green	**XB4 BVM3** (ZB4 BVM3 + ZB4 BV033)	0.080
		Red	**XB4 BVM4** (ZB4 BVM4 + ZB4 BV043)	0.080
		Orange	**XB4 BVM5** (ZB4 BVM5 + ZB4 BV053)	0.080
		Blue	**XB4 BVM6** (ZB4 BVM6 + ZB4 BV063)	0.080



ZB4 BV063

Shape of head	For use with body comprising light source type	Colour of lens	Reference	Weight kg
Heads only *(1)*				
■ With plain lens				
	Integral LED only Protected LED	White	**ZB4 BV013**	0.026
		Green	**ZB4 BV033**	0.026
		Red	**ZB4 BV043**	0.026
		Orange	**ZB4 BV053**	0.026
		Blue	**ZB4 BV063**	0.026
		5 colours *(2) (3)*	**ZB4 BV003**	0.026
■ With plain lens, for insertion of legend *(3)*				
	Integral LED only Protected LED	White	**ZB4 BV013E**	0.026
		Green	**ZB4 BV033E**	0.026
		Red	**ZB4 BV043E**	0.026
		Orange	**ZB4 BV053E**	0.026
		Blue	**ZB4 BV063E**	0.026
■ With grooved lens *(4)*				
	Integral LED only Protected LED	White	**ZB4 BV013S**	0.026
		Green	**ZB4 BV033S**	0.026
		Red	**ZB4 BV043S**	0.026
		Orange	**ZB4 BV053S**	0.026
		Blue	**ZB4 BV063S**	0.026



ZB4 BV043S

(1) Only for use with bodies comprising a light source with integral LED.
(2) Head supplied with 5 different coloured lenses (white, green, red, orange, blue) not fitted, for insertion of legend.
(3) For legend ordering information: see page 36070-EN/2.
(4) For use in bright ambient light conditions (outdoors in sunlight, for example).

General : page 36022-EN/2
Characteristics : page 36001-EN/2
Dimensions : page 36020-EN/2

Control and signalling units Ø 22
Harmony® XB4, metal
Pilot lights with integral LED and with BA 9s base fitting

Assembly of other products using:
body/light assemblies: see page 36068-EN/11
accessories: see pages 36069-EN/2 and 36070-EN/2

080702



XB4 BV5B●

Pilot lights with integral LED and transformer (1.2 VA, 24 V secondary)
Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Supply voltage V	Colour	Reference *(1)*	Weight kg
Complete units - With plain lens				
	∼ 400 - 50 Hz *(1)*	White	**XB4 BV5B1** (n)	0.172
		Green	**XB4 BV5B3** (n)	0.172
		Red	**XB4 BV5B4** (n)	0.172
		Orange	**XB4 BV5B5** (n)	0.172
		Blue	**XB4 BV5B6** (n)	0.172

Pilot lights with BA 9s base fitting, with plain or grooved lens
Screw clamp terminal connections (Schneider Electric anti-retightening system)


Shape of head	Supply voltage V	Colour	Reference	Weight kg
Complete units - With plain lens				
■ Direct supply, for BA 9s bulb, U ≤ 250 V, 2.4 W max (bulb not included)				
	≤ 250	White	**XB4 BV61** (ZB4 BV6 + ZB4 BV01)	0.075
		Green	**XB4 BV63** (ZB4 BV6 + ZB4 BV03)	0.075
		Red	**XB4 BV64** (ZB4 BV6 + ZB4 BV04)	0.075
		Orange	**XB4 BV65** (ZB4 BV6 + ZB4 BV05)	0.075
■ Via integral transformer, 1.2 VA, 6 V secondary, with BA 9s incandescent bulb (included)				
	∼ 110...120 - 50/60 Hz	White	**XB4 BV31** (ZB4 BV3 + ZB4 BV01)	0.152
		Green	**XB4 BV33** (ZB4 BV3 + ZB4 BV03)	0.152
		Red	**XB4 BV34** (ZB4 BV3 + ZB4 BV04)	0.152
		Orange	**XB4 BV35** (ZB4 BV3 + ZB4 BV05)	0.152
	∼ 230 - 50 Hz ∼ 220...240 - 60 Hz	White	**XB4 BV41** (ZB4 BV4 + ZB4 BV01)	0.152
		Green	**XB4 BV43** (ZB4 BV4 + ZB4 BV03)	0.152
		Red	**XB4 BV44** (ZB4 BV4 + ZB4 BV04)	0.152
		Orange	**XB4 BV45** (ZB4 BV4 + ZB4 BV05)	0.152

814114



XB4 BV64

814117



XB4 BV33

Heads only *(2)*

Shape of head	For use with body comprising light source type	Colour of lens	Reference	Weight kg
■ With plain lens				
	With BA 9s base fitting	White	**ZB4 BV01**	0.027
		Green	**ZB4 BV03**	0.027
		Red	**ZB4 BV04**	0.027
		Orange	**ZB4 BV05**	0.027
		Blue	**ZB4 BV06**	0.027
		Clear	**ZB4 BV07**	0.027
■ With grooved lens *(3)*				
	With BA 9s base fitting	White	**ZB4 BV01S**	0.027
		Green	**ZB4 BV03S**	0.027
		Red	**ZB4 BV04S**	0.027
		Orange	**ZB4 BV05S**	0.027
		Blue	**ZB4 BV06S**	0.027
		Clear	**ZB4 BV07S**	0.027

814213



ZB4 BV04

523768



ZB4 BV06S

(1) Tor order ∼ 440...460 V - 60 Hz tranformer blocks, please replace «5» in the reference by «8». Example: XB4 BV5B1 becomes XB4 BV8B1. To order ∼ 550...600 V - 60 Hz blocks, please replace «5» by «9». Example: XB4 BV5B1 becomes XB4 BV9B1.
(2) Only for use with bodies comprising a light source with BA 9s base fitting (incandescent, neon or LED).
(3) For use in bright ambient light conditions (outdoors in sunlight, for example).

(n) New

General : page 36022-EN/2
Characteristics : page 36001-EN/2
Dimensions : page 36020-EN/2