Harmony™ XB4 metal 22 mm push buttons

Illuminated selector switches with standard handle and integral LED

Assembly of other products using combined sub-assemblies, see page 48; accessories, see page 62

Illuminated selector switches with standard handle, with integral LED (continued) (1)

Shape of head	Type of operator	Positions		Color of handle	Reference	Weight kg
		Number	Type			
Heads only (2)						
Protected LED	**Standard handle**	2-position 90°	Stay put	White	**ZB4BK1213**	0.036
				Green	**ZB4BK1233**	0.036
				Red	**ZB4BK1243**	0.036
				Orange	**ZB4BK1253**	0.036
				Blue	**ZB4BK1263**	0.036
			Spring return from right to left	White	**ZB4BK1413**	0.037
				Green	**ZB4BK1433**	0.037
				Red	**ZB4BK1443**	0.037
				Orange	**ZB4BK1453**	0.037
				Blue	**ZB4BK1463**	0.037
		3-position ± 45°	Stay put	White	**ZB4BK1313**	0.036
				Green	**ZB4BK1333**	0.036
				Red	**ZB4BK1343**	0.036
				Orange	**ZB4BK1353**	0.036
				Blue	**ZB4BK1363**	0.036
			Spring return to center	White	**ZB4BK1513**	0.036
				Green	**ZB4BK1533**	0.036
				Red	**ZB4BK1543**	0.036
				Orange	**ZB4BK1553**	0.036
				Blue	**ZB4BK1563**	0.036
			Spring return from right to center	White	**ZB4BK1813**	0.036
				Green	**ZB4BK1833**	0.036
				Red	**ZB4BK1843**	0.036
				Orange	**ZB4BK1853**	0.036
				Blue	**ZB4BK1863**	0.036
			Spring return from left to center	White	**ZB4BK1713**	0.036
				Green	**ZB4BK1733**	0.036
				Red	**ZB4BK1743**	0.036
				Orange	**ZB4BK1753**	0.036
				Blue	**ZB4BK1763**	0.036



ZB4BK1343

Heads with black metal bezel

To order, add a figure **7** to the references selected from above.
Example: **ZB4BK1213** becomes **ZB4BK12137**.

(1) Recommended maximum number of contacts constituting the body (mounting collar + contact) associated with the head, see page 24.
(2) Only for use with bodies comprised of a light source with integral LED.
Note: For contact block and mounting collar ordering information, see pages 48, 50, 51 and 52.
For light module ordering information, see pages 49, 50 and 51.