Pendant control stations for control circuits

Ready to use



Type XACA "Pistol grip"

Degree of protection		IP 65 / Nema 4, 4X / Class II				
Rated operational characteristics		AC 15 (240 V 3 A), DC 13				
Conventional thermal current	Ithe	10 A				
Connection		Screw clamp terminals, 1 x 2.5 mm² or 2 x 1.5 mm²				
For control of		**single-speed motors**		**2-speed motors**		
Dimensions (mm)	W x H x D	52 x 295 x 71 (x 85 with ZA2BS834)		52 x 295 x 71 (x 85 with ZA2BS834)		
Number of operators	mechanically interlocked	**2**		**2**		
	Emergency stop	without	ZA2BS834	without	ZA2BS834	
References		**XACA201**	**XACA2014**	**XACA207**	**XACA2074**	



Type XACA

For control of single-speed motors					
Dimensions (mm)	W x H x D	80 x 314 x 70 (x 90 with ZA2BS834)		80 x 440 x 70 (x 90 with ZA2BS844)	
Number of operators	mechanically interlocked between pairs	**2**		**4**	
	Emergency stop	without	ZA2BS834	without	ZA2BS844
References		**XACA271**	**XACA2714**	**XACA471**	**XACA4714**



For control of single-speed motors				+ I / O	
Dimensions (mm)	W x H x D	80 x 500 x 70 (x 90 with ZA2BS844)		80 x 560 x 70	
Number of operators	mechanically interlocked between pairs	**6**		**8**	
	Emergency stop	without	ZA2BS844	without	
References		**XACA671**	**XACA6714**	**XACA871**	

Empty enclosures type XACA

Number of ways	2	3	4	5	6	8	12
References	XACA02	XACA03	XACA04	XACA05	XACA06	XACA08	XACA12