Harmony™ XB5 plastic 22 mm push buttons
Pilot lights with integral LED

Assembly of other products using light block sub-assemblies, see page 130; accessories, see pages 134 and 138


XB5AVB1


ZB5AV053


ZB5CV063

Pilot lights with integral LED
Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Supply voltage V	Color	Reference	Weight kg
Complete units				
■ With plain lens				
Protected LED	≂ 24 (50/60 Hz)	White	**XB5AVB1** (ZB5AVB1 + ZB5AV013)	0.038
		Green	**XB5AVB3** (ZB5AVB3 + ZB5AV033)	0.038
		Red	**XB5AVB4** (ZB5AVB4 + ZB5AV043)	0.038
		Orange	**XB5AVB5** (ZB5AVB5 + ZB5AV053)	0.038
		Blue	**XB5AVB6** (ZB5AVB6 + ZB5AV063)	0.038
	∿ 110 to 120 (50/60 Hz)	White	**XB5AVG1** (ZB5AVG1 + ZB5AV013)	0.038
		Green	**XB5AVG3** (ZB5AVG3 + ZB5AV033)	0.038
		Red	**XB5AVG4** (ZB5AVG4 + ZB5AV043)	0.038
		Orange	**XB5AVG5** (ZB5AVG5 + ZB5AV053)	0.038
		Blue	**XB5AVG6** (ZB5AVG6 + ZB5AV063)	0.038
	∿ 230 to 240 (50/60 Hz)	White	**XB5AVM1** (ZB5AVM1 + ZB5AV013)	0.038
		Green	**XB5AVM3** (ZB5AVM3 + ZB5AV033)	0.038
		Red	**XB5AVM4** (ZB5AVM4 + ZB5AV043)	0.038
		Orange	**XB5AVM5** (ZB5AVM5 + ZB5AV053)	0.038
		Blue	**XB5AVM6** (ZB5AVM6 + ZB5AV063)	0.038

Shape of head	For use with body comprised of light source type	Color of lens	Reference	Weight kg
Heads only, circular *(1)*				
■ With plain lens				
	Integral LED only Protected LED	White	**ZB5AV013**	0.017
		Green	**ZB5AV033**	0.017
		Red	**ZB5AV043**	0.017
		Orange	**ZB5AV053**	0.017
		Blue	**ZB5AV063**	0.017
		5 colors *(2) (3)*	**ZB5AV003**	0.017
■ With plain lens, for insertion of legend *(3)*				
	Integral LED only Protected LED	White	**ZB5AV013E**	0.017
		Green	**ZB5AV033E**	0.017
		Red	**ZB5AV043E**	0.017
		Orange	**ZB5AV053E**	0.017
		Blue	**ZB5AV063E**	0.017
■ With grooved lens *(4)*				
	Integral LED only Protected LED	White	**ZB5AV013S**	0.017
		Green	**ZB5AV033S**	0.017
		Red	**ZB5AV043S**	0.017
		Orange	**ZB5AV053S**	0.017
		Blue	**ZB5AV063S**	0.017
Heads only, square *(1)*				
■ With plain lens				
	Integral LED only Protected LED	White	**ZB5CV013**	0.020
		Green	**ZB5CV033**	0.020
		Red	**ZB5CV043**	0.020
		Orange	**ZB5CV053**	0.020
		Blue	**ZB5CV063**	0.020
		5 colors *(2)*	**ZB5CV003**	0.028

(1) Only for use with bodies comprised of a light source with integral LED.
(2) Head supplied with 5 different colored lenses (white, green, red, orange, blue) not fitted, for insertion of legend.
(3) For legend ordering information: see page 138.
(4) For use in bright ambient light conditions (outdoors in sunlight, for example).
Note: For contact block and mounting collar ordering information, see pages 122, 124, 125 and 126.
For light module ordering information, see pages 123, 124 and 125.

Introduction: page 86 | Specifications: page 92 | Dimensions: page 148