Harmony™ XB5 plastic 22 mm push buttons

Body/contact assemblies

Plug-in connector

To combine with heads, see pages 98 to 121



ZB5AZ009

Body/mounting collar

For use with	Sold in lots of	Unit reference	Weight kg
Electrical block (contact or light)	10	**ZB5AZ009**	0.006



ZBE1014



ZBE1024

Contact functions

Plug-in connector *(1)*

Contacts for standard applications

Description	Type of contact	N/O	N/C	Sold in lots of	Unit reference	Weight kg
Contact blocks	Single	1	–	5	**ZBE1014**	0.011
		–	1	5	**ZBE1024**	0.011
	Single with body/mounting collar	1	–	1	**ZB5AZ1014**	0.018
		–	1	1	**ZB5AZ1024**	0.018
		2	–	1	**ZB5AZ1034**	0.026
		–	2	1	**ZB5AZ1044**	0.026
		1	1	1	**ZB5AZ1054**	0.026
		1	2	1	**ZB5AZ1414**	0.036



ZB5AZ1014

Light blocks

Plug-in connector

Description	Supply voltage (V)	Color of light source	Sold in lots of	Unit reference	Weight kg
Integral LED (to combine with heads for integral LED) Protected LED	⎓ 24 (50/60 Hz)	White	5	**ZBVB14**	0.016
		Green	5	**ZBVB34**	0.016
		Red	5	**ZBVB44**	0.016
		Orange	5	**ZBVB54**	0.016
		Blue	5	**ZBVB64**	0.016
	~ 110 to 120 (50/60 Hz)	White	5	**ZBVG14**	0.016
		Green	5	**ZBVG34**	0.016
		Red	5	**ZBVG44**	0.016
		Orange	5	**ZBVG54**	0.016
		Blue	5	**ZBVG64**	0.016
	~ 230 to 240 (50/60 Hz)	White	5	**ZBVM14**	0.016
		Green	5	**ZBVM34**	0.016
		Red	5	**ZBVM44**	0.016
		Orange	5	**ZBVM54**	0.016
		Blue	5	**ZBVM64**	0.016




ZB5AZ1024



ZBVB●4

Connecting cables and connector

Description	Number of connectors	Wire c.s.a. mm²	Length mm	Sold in lots of	Unit reference	Weight kg
Cables with connectors 2-pin, 5.08 mm pitch	1	0.75	500	8	**APE1C2150**	0.120
	2	0.75	500	8	**APE1C2250**	0.180
Spring terminal connector 2-pin, 5.08 mm pitch	–	0.2 to 2.5	–	10	**APE1PRE21**	0.003



APE1C2250

(1) It is not possible to fit an additional contact block on the back of these contact blocks.