Harmony™ XB5 plastic 22 mm push buttons

Body/light assemblies for pilot lights with integral LED

To combine with heads, see page 118; contacts, see page 122



ZB5AV●●

Complete light bodies (mounting collar + light block with integral LED)
Screw clamp terminal connections (Schneider Electric anti-retightening system)

Light source	Supply voltage V	Color of light source	Reference	Weight kg
Integral LED Protected LED	≂ 12 (50/60 Hz)	White	**ZB5AVJ1**	0.022
		Green	**ZB5AVJ3**	0.022
		Red	**ZB5AVJ4**	0.022
		Orange	**ZB5AVJ5**	0.022
		Blue	**ZB5AVJ6**	0.022
	≂ 24 *(1)* (50/60 Hz)	White	**ZB5AVB1**	0.022
		Green	**ZB5AVB3**	0.022
		Red	**ZB5AVB4**	0.022
		Orange	**ZB5AVB5**	0.022
		Blue	**ZB5AVB6**	0.022
	≂24 to 120 (50/60 Hz)	White	**ZB5AVBG1**	0.022
		Green	**ZB5AVBG3**	0.022
		Red	**ZB5AVBG4**	0.022
		Orange	**ZB5AVBG5**	0.022
		Blue	**ZB5AVBG6**	0.022
	~ 110 to 120 *(1)* (50/60 Hz)	White	**ZB5AVG1**	0.022
		Green	**ZB5AVG3**	0.022
		Red	**ZB5AVG4**	0.022
		Orange	**ZB5AVG5**	0.022
		Blue	**ZB5AVG6**	0.022
	~ 230 to 240 *(1)* (50/60 Hz)	White	**ZB5AVM1**	0.022
		Green	**ZB5AVM3**	0.022
		Red	**ZB5AVM4**	0.022
		Orange	**ZB5AVM5**	0.022
		Blue	**ZB5AVM6**	0.022

(1) Complete bodies with Faston® connector terminals (6.35 or 2 x 2.8), see page 123.