Control and signalling units Ø 22
Harmony® XB5, plastic
Pilot lights with integral LED

Assembly of other products using:
light block sub-assemblies: see page 36068/10
accessories: see pages 36169/2 and 36170/2


814388

XB5 AVB1

Pilot lights with integral LED
Screw clamp terminal connections

Shape of head	Supply voltage V	Colour	Reference	Weight kg
Complete units				
■ With plain lens				
Protected LED	≂ 24	White	**XB5 AVB1** (ZB5 AVB1 + ZB5 AV013)	0.038
		Green	**XB5 AVB3** (ZB5 AVB3 + ZB5 AV033)	0.038
		Red	**XB5 AVB4** (ZB5 AVB4 + ZB5 AV043)	0.038
		Orange	**XB5 AVB5** (ZB5 AVB5 + ZB5 AV053)	0.038
		Blue	**XB5 AVB6** (ZB5 AVB6 + ZB5 AV063)	0.038
	∿ 48...120	White	**XB5 AVG1** (ZB5 AVG1 + ZB5 AV013)	0.038
		Green	**XB5 AVG3** (ZB5 AVG3 + ZB5 AV033)	0.038
		Red	**XB5 AVG4** (ZB5 AVG4 + ZB5 AV043)	0.038
		Orange	**XB5 AVG5** (ZB5 AVG5 + ZB5 AV053)	0.038
		Blue	**XB5 AVG6** (ZB5 AVG6 + ZB5 AV063)	0.038
	∿ 230...240	White	**XB5 AVM1** (ZB5 AVM1 + ZB5 AV013)	0.038
		Green	**XB5 AVM3** (ZB5 AVM3 + ZB5 AV033)	0.038
		Red	**XB5 AVM4** (ZB5 AVM4 + ZB5 AV043)	0.038
		Orange	**XB5 AVM5** (ZB5 AVM5 + ZB5 AV053)	0.038
		Blue	**XB5 AVM6** (ZB5 AVM6 + ZB5 AV063)	0.038

Heads only, circular *(1)*

Shape of head	For use with body comprising light source type	Colour of lens	Reference	Weight kg
■ With plain lens				
	Integral LED only Protected LED	White	**ZB5 AV013**	0.017
		Green	**ZB5 AV033**	0.017
		Red	**ZB5 AV043**	0.017
		Orange	**ZB5 AV053**	0.017
		Blue	**ZB5 AV063**	0.017
		5 colours *(2) (3)*	**ZB5 AV003**	0.017
■ With plain lens, for insertion of legend *(3)*				
	Integral LED only Protected LED	White	**ZB5 AV013E**	0.017
		Green	**ZB5 AV033E**	0.017
		Red	**ZB5 AV043E**	0.017
		Orange	**ZB5 AV053E**	0.017
		Blue	**ZB5 AV063E**	0.017
■ With grooved lens *(4)*				
	Integral LED only Protected LED	White	**ZB5 AV013S**	0.017
		Green	**ZB5 AV033S**	0.017
		Red	**ZB5 AV043S**	0.017
		Orange	**ZB5 AV053S**	0.017
		Blue	**ZB5 AV063S**	0.017


814529

ZB5 AV053

Heads only, square *(1)*

Shape of head	For use with body comprising light source type	Colour of lens	Reference	Weight kg
■ With plain lens				
	Integral LED only Protected LED	White	**ZB5 CV013**	0.020
		Green	**ZB5 CV033**	0.020
		Red	**ZB5 CV043**	0.020
		Orange	**ZB5 CV053**	0.020
		Blue	**ZB5 CV063**	0.020
		5 colours *(2)*	**ZB5 CV003**	0.028


814530

ZB5 CV063

(1) Only for use with bodies comprising a light source with integral LED.
(2) Head supplied with 5 different coloured lenses (white, green, red, orange, blue) not fitted, for insertion of legend.
(3) For legend ordering information: see page 36170/2.
(4) For use in bright ambient light conditions (outdoors in sunlight, for example).

General : pages 36025/2 to 36027/5
Characteristics : pages 36011/2 to 36011/5
Dimensions : pages 36021/2 to 36021/13

Control and signalling units Ø 22
Harmony® XB5, plastic
Pilot lights with BA 9s base fitting

Assembly of other products using:
light block sub-assemblies: see page 36168/10
accessories: see pages 36169/2 and 36170/2

814392



XB5 AV63

814391



XB5 AV34

Pilot lights with BA 9s base fitting, with plain lens
Screw clamp terminal connections

Shape of head	Supply voltage V	Colour	Reference	Weight kg
Complete units - With plain lens				
■ Direct supply, for BA 9s bulb, U ≤ 250 V, 2.4 W max (bulb not included)				
	≤ 250	White	**XB5 AV61** (ZB5 AV6 + ZB5 AV01)	0.037
		Green	**XB5 AV63** (ZB5 AV6 + ZB5 AV03)	0.037
		Red	**XB5 AV64** (ZB5 AV6 + ZB5 AV04)	0.037
		Orange	**XB5 AV65** (ZB5 AV6 + ZB5 AV05)	0.037
■ Via integral transformer, 1.2 VA, 6 V secondary, with BA 9s incandescent bulb (included)				
	∼ 110...120 - 50/60 Hz	White	**XB5 AV31** (ZB5 AV3 + ZB5 AV01)	0.109
		Green	**XB5 AV33** (ZB5 AV3 + ZB5 AV03)	0.109
		Red	**XB5 AV34** (ZB5 AV3 + ZB5 AV04)	0.109
		Orange	**XB5 AV35** (ZB5 AV3 + ZB5 AV05)	0.109
	∼ 230 - 50 Hz ∼ 220...240 - 60 Hz	White	**XB5 AV41** (ZB5 AV4 + ZB5 AV01)	0.110
		Green	**XB5 AV43** (ZB5 AV4 + ZB5 AV03)	0.110
		Red	**XB5 AV44** (ZB5 AV4 + ZB5 AV04)	0.110
		Orange	**XB5 AV45** (ZB5 AV4 + ZB5 AV05)	0.110

Heads only *(1)*

Shape of head	For use with body comprising light source type	Colour of lens	Reference	Weight kg
■ With plain lens				
	With BA 9s base fitting (incandescent, neon or LED)	White	**ZB5 AV01**	0.018
		Green	**ZB5 AV03**	0.018
		Red	**ZB5 AV04**	0.018
		Orange	**ZB5 AV05**	0.018
		Blue	**ZB5 AV06**	0.018
		Clear	**ZB5 AV07**	0.018
■ With grooved lens *(2)*				
	With BA 9s base fitting (neon or LED only)	White	**ZB5 AV01S**	0.017
		Green	**ZB5 AV03S**	0.017
		Red	**ZB5 AV04S**	0.017
		Orange	**ZB5 AV05S**	0.017
		Blue	**ZB5 AV06S**	0.017
		Clear	**ZB5 AV07S**	0.017

814528



ZB5 AV01

(1) Only for use with bodies comprising a light source with BA 9s base fitting (incandescent, neon or LED).
(2) For use in bright ambient light conditions (outdoors in sunlight, for example).

General : pages 36025/2 to 36027/5
Characteristics : pages 36011/2 to 36011/5
Dimensions : pages 36021/2 to 36021/13