HQI-TS 150/NDL EXCELLENCE



Opis produktu:	HQI-TS 150/NDL EXCELLENCE
Produkt:	4008321964366
Ilość:	Składane pudełko (FS) zawiera 1 Sztuka (ST)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=PL&~country=&it_p=4008321964366

Zastosowania	
Dozwolona pozycja pracy	p 45

Categorizations	
SEG nr	8333220
ILCOS	MD/UB-150/42/1B-H-RX7s=24-25/132/H

Opis ogólny	
Recykling	yes
Bezrtęciowy	No
Trzonek (standardowe rozwiązanie)	RX7s-24
Kształt / wersja	Clear
Nowy produkt	NEW

Techniczny - Dane elektryczne	
Pojemność kondensatora kompensacyjnego p	20 µF [1)]
Moc konstrukcji	150
Prąd konstrukcji	1.8 A
Moc znamionowa (opakowanie)	150 W

Techniczny - Dane geometryczne	
Średnica	23 mm
Długość	135.00 mm
Odległość a / LCL [mm]	66 mm

Techniczny - Trwałość	
Trwałość [h]	12000 h [2)]

Techniczny - Dane świetlne	
Strumień świetlny [lm]	12500 lm
Wskaźnik oddawania barw Ra	85
Temperatura barwowa [K]	4200 K
Stopień oddawania barw	1B
Skuteczność świetlna [lm/ W]	83 lm/W

Techniczny - Temperatury	
Maksymalna dozwolona temperatura bańki z	350 °C

Rodzaj opakowania

Product code	Rodzaj opakowania i zawartość	Wyniary: w x sz x dł	Waga brutto	Objętość:
4008321964366	Składane pudełko zawiera 1 Sztuka	35,000 mm x 35,000 mm x 141,000 mm	36,000 g (0,000 g)	0,173 dm3
4008321964373	Karton wysyłkowy zawiera 12 Sztuka	116,000 mm x 155,000 mm x 154,000 mm	498,000 g (0,000 g)	2,662 dm3

Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH



HQI-TS 150/NDL EXCELLENCE

Metal halide lamps POWERSTAR HQI with quartz technology

POWERSTAR HQI-TS EXCELLENCE is an innovative development of the successful HQI-TS lamps in a new design - can be used as direct replacements. UV-reduced, compact and double-ended. Approved for use only in enclosed luminaires.

Benefits of HQI-TS EXCELLENCE

- High efficiency
- Uniform distribution of light
- Excellent color rendering
- Long life
- In light color Warm White DE LUXE can be combined with POWERBALL HCI 830 and the light from HALOSTAR
- Hot restart

Benefits of OSRAM UV filter technology

- Reduced material load within the luminaire
- The UV filter on the lamp complies with the requirements of IEC 61167

Applications

- Shop interiors, shop windows
- Shopping arcades
- Foyers, reception areas
- Museums, exhibitions
- Exhibition halls and trade fairs
- Pedestrian zones, public squares
- Parks and gardens
- Buildings, monuments, bridges

System guarantee

For more and more lamps we are offering a system guarantee in conjunction with OSRAM POWERTRONIC control gear. For further information and the terms and conditions of the guarantee go to www.osram.com/system-guarantee.

[1] at rated voltage and cos φ $\geq$ 0.9

[2] Average lifespan

Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH