Mosaic™ programme audio/video sockets


0 787 77


0 787 74


0 787 72


0 787 73


0 787 70


0 787 99


Patch panels, cables and cords **p. 751**

Selection chart for boxes, supports and plates **p. 882-883**

Female HD15 sockets

Used to transmit analog video streams (VGA, XGA, UXGA depending on graphic card) between a source (computer) and a compatible receiver (plasma, LCD, video projector, etc...)

Pack	Cat.Nos	
		Preconnected sockets - 1 module Equipped with cord, length 15 cm
NEW		
1	0 787 77	○ White
1	0 793 77	● Alu
		Screw-type female HD15 sockets - 2 modules
1	0 787 57	○ White
1	0 792 57	● Alu
		Screw-type female HD15 sockets - 2 modules + 3.5 mm jack
1	0 787 74	○ White
		Solder-type female HD15 sockets - 1 module 15 pin
1	0 787 72	○ White

HDMI type A sockets

Used to transmit high-definition digital audio/video streams between a source (HD-DVD drive, computer, etc) and a compatible receiver (plasma, LCD, etc)
Can be associated with HDMI cord and cable (see p. 751)

Pack	Cat.Nos	
		Preconnected sockets - 1 module Equipped with cord, length 15 cm
NEW		
1	0 787 78	○ White
1	0 793 78	● Alu
		Screw-type sockets - 2 modules
1	0 787 68	○ White
1	0 792 75	● Alu

Jack sockets 3.5 mm

3.5 mm jack connectors can be used to create audio/video links from a portable source

Pack	Cat.Nos	
		Preconnected sockets - 1 module Equipped with cord, length 15 cm
NEW		
1	0 787 79	○ White
1	0 793 79	● Alu
		4 screw-type female 3.5 mm jack socket - 1 module
1	0 787 64	○ White
1	0 792 64	● Alu
		Solder-type female 3.5 mm jack socket - 1 module
1	0 787 73	○ White

HD15 + 3.5 mm Jack amplifier

Used to connect audio/video terminals more than 20 m apart up to 100 m
The video link is via an HD15 connector (resolution up to UXGA)
The stereo audio link is via a 3.5 mm jack
The kit includes:
- One 4-module Mosaic transmitter equipped with an HD15 connector and a 3.5 mm jack
- One 4-module Mosaic receiver equipped with an HD15 connector and a 3.5 mm jack
- One 4-module Mosaic power supply to be connected on the mains then linked to the receiver or transmitter

The link between the transmitter and receiver is via a network cable (Cat.No 0 327 56)
Transmitter and receiver are supplied with an RJ 45 LCS jack for tool-free connection

Pack	Cat.Nos	
1	0 787 70	○ White

Videoprojector switch

Universal remote switch allowing to turn ON or place in STANDBY mode a video projector
Works with all videoprojectors through IR learning process
Installed close to the room's lighting switches, it replaces the constructors remote and fosters the ignition and extinction of the video projector therefore reducing energy consumption and extending the bulb's lifetime

Pack	Cat.Nos	
NEW		
1	0 787 99	○ White

Display port sockets

Used to transmit high-definition digital audio/video streams between a source (laptop, computer, etc) and a compatible receiver (plasma, LCD, videoprojector)

Pack	Cat.Nos	
		Preconnected socket - 1 module Equipped with cord, length 15 cm
NEW		
1	0 787 91	○ White

Red catalogue numbers: New products