product details

QT-M 1X26-42/230-240 S UNV1



Product description: QT-M 1X26-42/230-240 S UNV1
EAN/ Product: 4050300609256
Quantity: Unpacked (UNV) contains 1 Piece (PCE)

Applications	
Dimmable	No
Type of protection	IP20

General Description	
Design / version	ECG multiwatt
SEG no.	7980081
Energy Label - EEI	A2
Sstl-Number	4030151

Technical - Electrical Data	
Operating frequency	≈ 40 kHz
Mains frequency	50-60 Hz
TH full width at half maximum	210 µs
Lamp wattage	42 W
Power factor c	0.97
Nominal voltage	230-240 V
DC voltage	176...254 V
IP inrush current	20 A
Max. no. of ECGs on circuit breaker 10A	17
Max. no. of ECGs on circuit breaker 16A	28

Technical - Geometries	
Mounting hole spacing, length	110 mm
Width	67 mm
Height	31 mm
Length	103 mm

Technical - Temperatures	
Max. casing temp. in case of fault	75 °C
Max. operating temp. at the Tc point	70 °C
Ambient temperature range	-10 ... +50 °C
Storage temperature	-40 ... 85 °C
Relative humidity	5 ... 85 % [1)]

Packaging units

EAN	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300609256	Unpacked contains 1 Piece	66,000 mm x 29,000 mm x 102,000 mm	156,700 g (0,000 g)	0,195 Cubic dec.
4050300609263	Shipping carton box contains 20 Piece	230,000 mm x 107,000 mm x 360,000 mm	3.420,000 g (0,000 g)	8,860 Cubic dec.

[1)] max. 56 d/y at 85%