# Accessories (cont.)
## Compact and Vigicompact NSX100/160/250 (cont.)

## Electrical auxiliaries

### Auxiliary contacts (changeover)




| | |
|---|---|
| OF or SD or SDE or SDV | **29450** |
| OF or SD or SDE or SDV low level | **29452** |
| SDE adapter, mandatory for trip unit TM, MA or Micrologic 2 | **LV429451** |

### SDx output module for Micrologic




| | |
|---|---|
| SDx module 24/415 V AC/DC | **LV429532** |

### SDTAM contactor tripping module (early-break thermal fault signal) for Micrologic 2.2-M/6.2 E-M




| | |
|---|---|
| SDTAM 24/415 V AC/DC overload fault indication | **LV429424** |

### Voltage releases




| | Voltage | MX | MN |
|---|---|---|---|
| AC | 24 V 50/60 Hz | **LV429384** | **LV429404** |
| | 48 V 50/60 Hz | **LV429385** | **LV429405** |
| | 110-130 V 50/60 Hz | **LV429386** | **LV429406** |
| | 220-240 V 50/60 Hz and 208-277 V 60 Hz | **LV429387** | **LV429407** |
| | 380-415 V 50 Hz and 440-480 V 60 Hz | **LV429388** | **LV429408** |
| | 525 V 50 Hz and 600 V 60 Hz | **LV429389** | **LV429409** |
| DC | 12 V | **LV429382** | **LV429402** |
| | 24 V | **LV429390** | **LV429410** |
| | 30 V | **LV429391** | **LV429411** |
| | 48 V | **LV429392** | **LV429412** |
| | 60 V | **LV429383** | **LV429403** |
| | 125 V | **LV429393** | **LV429413** |
| | 250 V | **LV429394** | **LV429414** |




| | | |
|---|---|---|
| **MN 48 V 50/60 Hz with fixed time delay** | | |
| Composed of: | MN 48 V DC | **LV429412** |
| | Delay unit 48 V 50/60 Hz | **LV429426** |
| **MN 220-240 V 50/60 Hz with fixed time delay** | | |
| Composed of: | MN 250 V DC | **LV429414** |
| | Delay unit 220-240 V 50/60 Hz | **LV429427** |
| **MN 48 V DC/AC 50/60 Hz with adjustable time delay** | | |
| Composed of: | MN 48 V DC | **LV429412** |
| | Delay unit 48 V 50/60 Hz | **33680** |
| **MN110-130 V DC/AC 50/60 Hz with adjustable time delay** | | |
| Composed of: | MN 125 V DC | **LV429413** |
| | Delay unit 110-130 V 50/60 Hz | **33681** |
| **MN 220-250 V 50/60 Hz with adjustable time delay** | | |
| Composed of: | MN 250 V DC | **LV429414** |
| | Delay unit 220-250 V 50/60 Hz | **33682** |