MOELLER

Type: **NZMB2–A125**
Article No.: **259087**



Ordering information			
Description			Terminal screws standard, terminals as accessories
Rated current = rated uninterrupted current	I_u	A	125
Setting range			
Short–circuit releases Short–circuit releases		A	750 – 1250
Switching capacity Switching capacity		kA	25
Release system			Thermomagnetic release
Pole			3

Notes concerning the product group

IEC/EN 61131–2

Adjustable overload release I_r

- 0.8 – 1 × I_n (ex–factory0.8 × I_n)

Adjustable short–circuit release I_i

- 6 – 10 × I_n
- (ex–factory6 × I_n

-)

– NZM...–A40: 8 – 10 × I_n (ex–factory 8 × I_n)

Fixed short–circuit release I_i

- 350 A With I_n = 20 – 32 A
- 1280 A with I_n = 160 A (NZM1)

Notes concerning the product group

Notes for terminals → 260042

General			
Standards			IEC/EN 60947
Protection against direct contact			Finger and back of hand proof to VDE 0106 Part 100
Climatic proofing			Damp heat, constant, according to IEC 60068–2–78 Damp heat, cyclical to IEC 60068–2–30
Mechanical shock resistance (IEC/EN 60068–2–27)			
Shock resistance		g	20 (half–sinusoidal shock 20 ms)
Safe isolation to VDE 0106 Part 101 and Part 101/A1			
Between auxiliary contacts and main contacts		V AC	500
between the auxiliary contacts		V AC	300
Dimensions			
Weight			
Weight		kg	2,345
Mounting position			
Direction of incoming supply			As required
Degree of protection			
Device			In the operating controls area: IP20 (basic degree of protection)
Enclosures			With insulating surround: IP40, with door coupling rotary handle: IP66
Terminations			Tunnel terminal: IP10 Phase isolator and strip terminal: IP00

Circuit–breakers			
Rated impulse withstand voltage U_{imp}			
Main contacts		V	8000
Auxiliary contacts		V	6000
Rated operational voltage	U_e	V AC	690
Overvoltage category/pollution degree			III/3
Rated insulation voltage	U_i	V	1000
Switching capacity			
Rated short–circuit making capacity			
240 V	I_{cm}	kA	63
400/415 V	I_{cm}	kA	53
440 V	I_{cm}	kA	53
525 V	I_{cm}	kA	30
Rated short–circuit breaking capacity I_{cn}			
I_{cu} to IEC/EN 60947 operating sequence O–t–CO			
240 V 50/60 Hz	I_{cu}	kA	30
400/415 V 50/60 Hz	I_{cu}	kA	25
440 V 50/60 Hz	I_{cu}	kA	25
525 V 50/60 Hz	I_{cu}	kA	15
I_{cu} to IEC/EN 60947 operating sequence O–t–CO–t–CO			
240 V 50/60 Hz	I_{cs}	kA	30
400/415 V 50/60 Hz	I_{cs}	kA	25
440 V 50/60 Hz	I_{cs}	kA	25
525 V 50/60 Hz	I_{cs}	kA	15
Technical data, divergent from the products for the IEC market switching capacity NA switches (UL489, CSA 22.2 No. 5.1)			
240 V 60 Hz		kA	35
480V 60Hz		kA	25
600 V 60 Hz		kA	18
Utilization category to IEC/EN 60947–2			A
Lifespan, mechanical	Operations		20000
Maximum operating frequency			
Max. operating frequency		Ops/h	120

Lifespan, electrical			
AC–1			
400/415 V 50/60 Hz	Operations		10000
690 V 50/60 Hz	Operations		7500
AC––3			
400/415 V 50/60 Hz	Operations		6500
690 V 50/60 Hz	Operations		5000
Current heat loss per pole at I_u		W	19
Overload releases			
Temperature compensation for NZM2 to IEC/EN 60947, residual error in the range –25 °C/+70 °C (reference temperature 40 °C)			
Electronic			0
Frequency range		ms	< 10
Terminal capacities			
Standard equipment			Screw terminal
Accessories			Box terminal Tunnel terminal Connection on rear
Cu conductors, Cu cable			
Box terminal			
Solid		mm^2	1 × (4 – 16) 2 × (4 – 16)
Stranded		mm^2	1 × (25 – 185) 2 × (25 – 70)
Tunnel terminal			
Solid		mm^2	1 × (16 – 185)
Stranded			
Single hole		mm^2	1 × (25 – 185)
Bolt terminal and rear–side connection			
Direct on the switch			
Solid		mm^2	1 × (4 – 16) 2 × (4 – 16)
Stranded		mm^2	1 × (25 – 185) 2 × (25 – 70)
Al conductors, Cu cable			
Tunnel terminal			
Solid		mm^2	1 × 16
Stranded			

Single hole		mm^2	1 × (25 – 185) je nach Kabelhersteller bis zu 240 mm^2 anschließbar
Bolt terminal and rear–side connection			
Direct on the switch			
Solid		mm^2	1 × (10 – 16) 2 × (10 – 16)
Stranded		mm^2	1 × (25 – 50) 2 × (25 – 50)
Cu strip (number of segments x width x segment thickness)			
Box terminal			
	min.	mm^2	2 × 9 × 0.8
	max.	mm^2	10 × 16 × 0.8
Bolt terminal and rear–side connection			
Flat copper strip, with holes	min.	mm	2 × 16 × 0.8
Flat copper strip, with holes	max.	mm	10 × 16 × 0.8
Copper busbar (width × thickness)			
Bolt terminal and rear–side connection			
Screw connection			M8
Direct on the switch			
	min.	mm^2	16 × 5
	max.	mm^2	20 × 5
Dimensions			
			Clearance from conductive parts 35 mm, laterally 5 mm
Explaination			Protection of systems and cables
Explaination			1 half–shaft

Mounting position

Vertical and 90° in all directions



With plug–in adapter NZM2: vertical, 90° right/left

Overview	With withdrawable unit NZM3: vertical, 90° left NZM4: verticalwith remote operator: NZM2, NZM3, NZM4: vertical and 90° in all directions
Basic equipment	
Box terminal	● – – –
Screw connection	– ● ● ●
Accessories	
Box terminal	– ● ● –
Screw connection	● – – ●
Tunnel terminal	● ● ● ●
Connection on rear	● ● ● ●
Flat conductor terminal	– – – ●

Dimensions



Characteristic curve



Characteristic curve



Characteristic curve



Moeller GmbH, Hein–Moeller–Str. 7–11, D–53115 Bonn
E–Mail: catalog@moeller.net, Internet: www.moeller.net, http://catalog.moeller.net
Copyright 2006 by Moeller GmbH. Subject to modifications. HPL–C2006GB–INT V2.3