




	Switching capacity 400/415 V 50/60 Hz	Rated current = Rated uninterrupted current	Setting range: Overload releases	Setting range: Short-circuit releases	Rated operational power AC-3 50/60 Hz		Rated operational current AC-3 50/60 Hz		**Fixed mounting** with screw terminals: **Part no.** Article no.	**Price** See price list		**Plug-in units**: **Part no.** Article no.	**Price** See price list	Std. pack	**Notes**
				Non-delayed	400 V	690 V	400 V	690 V	Order base separately			Order base separately			
	I_{cu}	$I_n = I_u$	I_r	$I_i = I_n$ x ...	P	P	I_e	I_e							
	kA	A	A		kW	kW	A	A							
			⊏	$I>$											**B = box terminals** **S = screw terminals** For further terminal types see accessories
Motor protection															
With phase-failure sensitivity															
Normal switching capacity															
	**50**	90	45-90	2-14	45	75	81	78	**NZMN2-ME90** 265778		S	**NZMN2-ME90-SVE** 113256		1 off	IEC/EN 60947-4-1, IEC/EN 60947-2 The circuit-breakers fulfill all requirements for utilization category AC-3.
		140	70-140	2-14	75	132	134	134	**NZMN2-ME140** 265779		S	**NZMN2-ME140-SVE** 113257			
		220	110-220	2-14	110	200	196	202	**NZMN2-ME220** 265780		S	**NZMN2-ME220-SVE** 113258			R.m.s. value measurement and "thermal memory"
		220	110-220	2-14	110	200	196	202	**NZMN3-ME220** 265781		S	**NZMN3-ME220-AVE** 110846			Adjustable delay setting t_r • 2 – 20 s at 6 x I_r, and infinite (without overload release)
		350	175-350	2-14	200	315	349	316	**NZMN3-ME350** 265782		S	**NZMN3-ME350-AVE** 110847			
		450	225-450	2-12	250	450	437	446	**NZMN3-ME450** 284468		S	**NZMN3-ME450-AVE** 110848			
		550	275-550	2-14	315	560	544	550	**NZMN4-ME550** 265783		S	Withdrawable units as accessories			
		875	438-875	2-14	500	600	820	588	**NZMN4-ME875** 265784		S				
		1400	700-1400	2-14	630	600	1066	588	**NZMN4-ME1400** 265785		S				
High switching capacity															
	**150**	90	45-90	2-14	45	45	81	78	**NZMH2-ME90** 265786		S	**NZMH2-ME90-SVE** 113348		1 off	
		140	70-140	2-14	75	132	134	134	**NZMH2-ME140** 265787		S	**NZMH2-ME140-SVE** 113349			
		220	110-220	2-14	110	200	196	202	**NZMH2-ME220** 265788		S	**NZMH2-ME220-SVE** 113350			
		220	110-220	2-14	110	200	196	202	**NZMH3-ME220** 265789		S	**NZMH3-ME220-AVE** 110855			
		350	175-350	2-14	200	315	349	316	**NZMH3-ME350** 265790		S	**NZMH3-ME350-AVE** 110856			
		450	225-450	2-12	250	450	437	446	**NZMH3-ME450** 284469		S	**NZMH3-ME450-AVE** 110857			
	**85**	550	275-550	2-14	315	560	544	550	**NZMH4-ME550** 265791		S	Withdrawable units as accessories			
		875	438-875	2-14	500	600	820	588	**NZMH4-ME875** 265792		S				
		1400	700-1400	2-14	630	600	1066	588	**NZMH4-ME1400** 265793		S				