Fixed/RC device = fixed/FC device + rear connection kit

Mixed RC kit



Kit 3P	Short RCs	2 x	**LV432475**
	Long RCs	1 x	**LV432476**
Kit 4P	Short RCs	2 x	**LV432475**
	Long RCs	2 x	**LV432476**

Fixed/FC device with 52.5 mm or 70 mm pitch = fixed/FC device with 45 mm pitch + spreaders

The pitch of all Compact and Vigicompact NSX400/630 devices is 45 mm. Spreaders are available for fixed front, plug-in or withdrawable connection with pitch of 52.5 mm or 70 mm.

Upstream or downstream spreaders



52.5 mm	3P	**LV432490**
	4P	**LV432491**
70 mm	3P	**LV432492**
	4P	**LV432493**

Plug-in version = fixed/FC device + plug-in kit

Kit for Compact



	3P	4P
Plug-in kit	**LV432538**	**LV432539**
Comprising:		
Base	= 1 x LV432516	= 1 x LV432517
Power connec ions	+ 3 x LV432518	+ 4 x LV432518
Short terminal shields	+ 2 x LV432591	+ 2 x LV432592
Safety trip interlock	+ 1 x LV432520	+ 1 x LV432520

Kit for Vigicompact



	3P	4P
Vigi plug-in kit	**LV432540**	**LV432541**
Comprising:		
Base	= 1 x LV432516	= 1 x LV432517
Power connections	+ 3 x LV432519	+ 4 x LV432519
Short terminal shields	+ 2 x LV432591	+ 2 x LV432592
Safety trip interlock	+ 1 x LV432520	+ 1 x LV432520