

T Cam switches
P Switch-disconnectors up to 315 A

The high performance and robust cam switch and switch-disconnector are used in industry, manual applications and building services management. Ten basic switch types in four different construction types can be selected in a multitude of standard contact sequences and a wide performance range.

ATEX

T/TM Cam switches
Performance up to 10/132 kW +++ Non-standard switches possible (see Online Catalog) +++ Several construction types

P switch-disconnectors
Performance up to 110 kW and 315 A +++ Switches up to 100 A (P1, P3) in housing IP65 +++ Four construction types

Switch for ATEX Zone 22
T Cam switches +++ Switch-disconnector up to 100 A (P1, P3) +++ IP65 Protection type

Cam switches, switch-disconnectors up to 315 A















Cam switches, switch-disconnectors

Technical overview

Cam switches, switch-disconnectors 4/2

System overview

Cam switches 4/4

Switch-disconnectors 4/6

Description

Key to part numbers, modular system 4/8

Ordering

Switch-disconnectors, main switches maintenance/manual override switches 4/10

Switch-disconnectors – On-Off switches 4/22

Switch-disconnectors – safety switches 4/30

Switch-disconnectors – changeover switches 4/32

Switch-disconnectors – reversing switches 4/38

Switch-disconnector - (reversing) star-delta switches, reversing multi-speed switch 4/38

Switch-disconnectors – multi-speed switches 4/40

Control switches - step switches 4/42

Control switches - On-Off switches 4/46

Control switches - changeover switches, manual/automatic switches 4/48

Control switches – On switches 4/50

Universal control switches 4/52

Control switches - instrument switches 4/54

Switch with locking mechanism 4/56

Main switch assembly kits, thumb-grips, maintenance key 4/58

Front plates 4/59

Add-on front plates 4/60

Key operation, locking interlock 4/62

Neutral conductor, auxiliary contact, centre mounting accessories, service distribution board mounting accessories 4/64

Coupling drive, interlock parts, shaft extension 4/65

Shrouds, keys 4/66

Accessories 4/67

Non-standard switches 4/79

Technical data

Switch-disconnectors 4/89

Switch-disconnectors, auxiliary contacts 4/92

Cam switch 4/94

Dimensions

Cam switches, switch-disconnectors 4/100









Mini rotary switches

Technical overview

Mini rotary switches 4/2

Description

Key to part numbers, modular system 4/9

System overview

Mini rotary switches 4/68

Ordering

Control circuit isolator, ON/OFF switches 4/60

Changeover switches 4/71

Hand/Auto switches 4/72

Control switch - step switch 4/72

Control switches - group switches, ON/ OFF switches, reversing switches, coding switches 4/75

Locks, front plates 4/77

Non-standard switches 4/83

Technical data

Mini rotary switches 4/99

Dimensions

Mini rotary switches 4/111

CI-K and CI basic enclosures and small enclosures 20/92

T, P, TM

	Switch, basic type Max. motor rating AC-23 A, 400/415 V, 50/60 Hz Max. rated operational current I_u	Part no.	TM 3.0 kW ≦ 10 A	T0 6.5 kW 20 A	T3 13 kW 32 A	T5B 22 kW 63 A	T5 30 kW 100 A	T6 55 kW 160 A	T8 132 kW 315 A	P1-25 13 kW 25 A	P1-32 15 kW 32 A	P3-63 37 kW 63 A	P3-100 50 kW 100 A	P5-125 45 kW 125 A	P5-160 55 kW 160 A	P5-250 90 kW 250 A	P5-315 110 kW 315 A
Switch-disconnectors																	
	Main switches, maintenance/manual override switches		–	→ 4/10	→ 4/10	→ 4/10	→ 4/12	→ 4/14	→ 4/14	→ 4/10	→ 4/10	→ 4/10	→ 4/10	→ 4/10	→ 4/10	→ 4/10	→ 4/10
	On-Off switches		→ 4/70	→ 4/22	→ 4/22	→ 4/22	→ 4/26	–	–	→ 4/28	→ 4/22	→ 4/22	→ 4/22	→ 4/22	→ 4/22	→ 4/22	→ 4/22
	Safety switches with warning label		–	–	–	→ 4/30	→ 4/30	–	–	→ 4/30	→ 4/30	→ 4/30	→ 4/30	–	–	–	–
	Changeover switches		–	→ 4/32	→ 4/32	→ 4/32	→ 4/32	→ 4/32	→ 4/32	–	–	–	–	–	–	–	–
	Reversing switch with 0 position		–	→ 4/38	→ 4/38	→ 4/38	–	–	–	–	–	–	–	–	–	–	–
	Star-delta switches		–	→ 4/38	→ 4/38	→ 4/38	–	–	–	–	–	–	–	–	–	–	–
	Reversing star-delta switches		–	→ 4/38	→ 4/38	→ 4/38	–	–	–	–	–	–	–	–	–	–	–
	Multi-speed switch		–	→ 4/40	→ 4/40	→ 4/40	–	–	–	–	–	–	–	–	–	–	–
	Reversing multi-speed switches		–	→ 4/40	→ 4/40	→ 4/40	–	–	–	–	–	–	–	–	–	–	–
Control switch																	
	Step switch		→ 4/72	→ 4/42		–	–	–	–	–	–	–	–	–	–	–	–
	On-Off switches		–	→ 4/46	–	–	–	–	–	–	–	–	–	–	–	–	–
	Changeover switches		→ 4/71	→ 4/48	–	–	–	–	–	–	–	–	–	–	–	–	–
	Manual/Auto switches		→ 4/72	→ 4/48	–	–	–	–	–	–	–	–	–	–	–	–	–
	Push button switch		–	→ 4/50	–	–	–	–	–	–	–	–	–	–	–	–	–
	Universal control switches		–	→ 4/52	–	–	–	–	–	–	–	–	–	–	–	–	–
	Coding switches		→ 4/76	→ 4/52	–	–	–	–	–	–	–	–	–	–	–	–	–
	Series switches		–	→ 4/52	–	–	–	–	–	–	–	–	–	–	–	–	–
	Instrument selector switches		–	→ 4/54	–	–	–	–	–	–	–	–	–	–	–	–	–
	Group switches		→ 4/75	–	–	–	–	–	–	–	–	–	–	–	–	–	–
	ON OFF button		→ 4/75	–	–	–	–	–	–	–	–	–	–	–	–	–	–
	Reversing switch		→ 4/76	–	–	–	–	–	–	–	–	–	–	–	–	–	–
Switches with interlocks																	
	Panic switches without emergency switching off function		–	→ 4/56	–	–	–	–	–	→ 4/56	→ 4/56	–	–	–	–	–	–
	On-Off switches without Emergency-Stop function		–	→ 4/56	–	–	–	–	–	→ 4/56	→ 4/56	–	–	–	–	–	–
Non-standard switches			→ 4/83	→ 4/79	→ 4/80	→ 4/81	→ 4/82	–	–	–	–	–	–	–	–	–	–
Mounting form																	
	Surface mounting	…/I…	–	✓	✓	✓	✓	–	–	✓	✓	✓	✓	–	–	–	–
		ATEX Ⓔx	–	✓	✓	✓	✓	–	–	✓	✓	✓	✓	–	–	–	–
	Surface mounting main switches	…/I…/SVB…	–	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	–	–	–	–
		ATEX Ⓔx	–	✓	✓	✓	✓	–	–	✓	✓	✓	✓	–	–	–	–
	Mounting	.../E…	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Flush mounting main switch	…/E(A)/SVB…	✓	✓	✓	✓	✓	–	–	✓	✓	✓	✓	✓	✓	✓	✓
	Center mounting	…/EZ…	✓	✓	✓	–	–	–	–	✓	✓	–	–	–	–	–	–
	Rear mounting	…/Z…	–	✓	✓	✓	✓	–	–	✓	✓	✓	✓	–	–	–	–
	Rear mounting main switches	…/V/SVB…	–	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Service distribution board mounting	…/IVS…	✓	✓	–	–	–	–	–	✓	✓	✓	✓	–	–	–	–

System overview

ON-OFF switches T0, T3, T5B, T5



Control switches T0, T3, T5B, T5



Service distribution board mounting (…/IVS) 1

Front IP30

Can be snapped onto top-hat rail as per IEC/EN 60715 (only T0 and T3)

Mounting

- In service distribution board up to 3 contact units (45 mm mounting depth)
- In control panel up to 11 contact units

→ Page 4/22

Rear mounting (.../Z) 2

Front IP65

Fixing: optionally with screw fixing or snap fitting, only T0 und T3

For snap fitting to IEC/EN 60715 top-hat rail

Drive coupling in door or cover

Connection from front

→ Page 4/22

Rear mounting main switch (...V/SVB) 2

Front IP65

To IEC/EN 60204, VDE 0113 and IEC/EN 60947-3

For T0…: up to 8 contacts; For T3…: up to 12 contacts

With door interlock in "I" position

→ Page 4/10

Flush mounting (.../E) 3

Front IP65

Flush mounting and connection from rear

Terminals:

Crosshead screwdriver Pozidrive

T8 always with extension terminals

→ Page 4/22

Flush mounting main switch (.../EA/SVB) 3

Front IP65

To IEC/EN 60204, VDE 0113 and IEC/EN 60947-3,

For T0…: up to 8 contacts; For T3…: up to 12 contacts

N and PE terminal

→ Page 4/10

Center mounting (.../EZ) 3

Front IP65

Mounted in ∅ 22.3 fixing hole to IEC/EN 60947-5-1

"One man mounting" by center fixing

→ Page 4/22

Surface mounting (.../I...) 4

IP65

totally insulated

With an additional terminal

Enclosures for metric cable glands to EN 50262

→ Page 4/22

Surface mounting main switch (.../I...) 4

IP65

totally insulated

To IEC/EN 60204, VDE 0113 and IEC/EN 60947-3,

For T0…: up to 8 contacts; For T3…: up to 10 contacts

Position 0 lockable with 3 padlocks

Enclosures for metric cable glands to EN 50262

With an additional terminal

→ Page 4/10

ATEX

→ Page 4/58

Safety switch (.../I...) 5

IP65

totally insulated

With an additional terminal

With cover fixing in 0 position

Position 0 lockable with 3 padlocks

Enclosures for metric cable glands to EN 50262

"Safety Switch" label; color: orange

→ Page 4/30

ATEX

→ Page 4/58

Main switch (kit) for use as emergency switching off device 6

To IEC/EN 60204-1,VDE 0113 part 1

With red rotary handle and yellow locking collar

Lockable in the 0 (Off) position

→ Page 4/58

Main switch (kit) 7

Black rotary handle and locking collar

Lockable in the 0 position

→ Page 4/58

Thumb-grip, for use as emergency switching off device 8

To IEC/EN 60204-1, VDE 0113 part 1

Red thumb-grip and yellow front plate

→ Page 4/58

Thumb-grip 9

Black thumb-grip with front plate

→ Page 4/58

Coupling drive 10

Including push-fit shaft

For the retrofitting of switch T0(T3)-.../XZ as rear mounting, spare part for T0(T3)/(P1)-.../Z

For the conversion of T5(B)-.../E flush mounting switch to rear mounting, spare part for T5(B)/(P3)-...Z

→ Page 4/65

Note:

Cam switches T5 and T5B are only available with screw connections for fixing on a mounting plate.

ON-OFF switches P1, P3



ON OFF switches P5



Service distribution board mounting (…/IVS) 1
Front IP30
Fitting dimensions according to DIN 43880
For snap fitting to top-hat rail according to IEC/EN 60715
Space requirement
P1, 3 pole: 3 space units
P3, 3 pole: 4 space units
P3-.../IVS lockable with padlock in "0" position
→ Page 4/22

Rear mounting (.../Z) 2
Front IP65
Fixing either by snap-on or screw fixing
For snap fitting to top-hat rail according to IEC/EN 60715
Drive coupling in door or cover
Connection from front
2 add-on modules can be retrofitted
→ Page 4/22

Rear mounting main switch (...V/SVB) 2
Front IP65
To IEC/ENEN 60204, VDE 0113 and IEC/EN 60947-3
With door interlock in "I" position
Maintenance key for commissioning or fault-finding
Position 0 lockable with 3 padlocks
2 add-on modules can be retrofitted
→ Page 4/10

Flush mounting (.../E) 3
Front IP65
Flush mounting and connection from rear
Terminals: Crosshead screwdriver Pozidrive
Back-of-hand proof
2 add-on modules can be retrofitted
→ Page 4/22

Flush mounting main switch (.../EA/SVB) 3
Front IP65
To IEC/ENEN 60204, VDE 0113 and IEC/EN 60947-3
N and PE terminal
Position 0 lockable with 3 padlocks
2 add-on modules can be retrofitted
→ Page 4/10

Center mounting (.../EZ) 3
Front IP65
Mounted in ∅ 22.3 fixing hole to IEC/EN 60947-5-1
"One man mounting" by center fixing
→ Page 4/22

Add-on modules 4
Switchable N conductor (early-make N/O contact)
Auxiliary contacts
Finger proof
Auxiliary N/O contact: Always connected as a load-shedding contact (late-make on, late-break off)
→ Page 4/64

Surface mounting (.../I...) 5
IP65
totally insulated
With an additional terminal
Installable add-on modules:
P1: HI 11-P1/P3 or N-P1..., P3: HI 11-P1/P3 and/or N-P5
Enclosures for metric cable glands to EN 50262
→ Page 4/22

Surface mounting main switch (…/I…) 5
IP65
totally insulated
With an additional terminal
To IEC/ENEN 60204, VDE 0113 and IEC/EN 60947-3
Position 0 lockable with 3 padlocks
Installable add-on modules:
P1: HI 11-P1/P3 or N-P1..., P3: HI 11-P1/P3 and/or N-P5
Enclosures for metric cable glands to EN 50262
→ Page 4/10

ATEX

→ Page 4/58

Safety switch (.../I...-SI) 6
IP65
totally insulated
With an additional terminal
With cover fixing in 0 position
Position 0 lockable with 3 padlocks
"Safety Switch" label; color: orange
Enclosures for metric cable glands to EN 50262
→ Page 4/30

ATEX

→ Page 4/58

Main switch (kit) for use as emergency switching off device 7
To IEC/EN 60204-1, VDE 0113 Part 1
With red rotary handle and yellow locking collar
Lockable in the 0 (Off) position
→ Page 4/58

Main switch (kit) 8
Black rotary handle and locking collar
Lockable in the 0 position
→ Page 4/58

Thumb-grip, for use as emergency switching off device 9
To IEC/EN 60204-1, VDE 0113 Part 1
Red thumb-grip and yellow front plate
→ Page 4/58

Thumb-grip 10
Black thumb-grip with front plate
→ Page 4/58

Coupling drive 11
Including push-fit shaft
For retrofitting mounting switches T0(T3)-…/XZ as rear mounting design spare part for T0(T3)/(P1)-…/Z
For converting flush mounting switches T5(B)-…/E into rear mounting switch spare part for T5(B)/(P3)-…Z
→ Page 4/65

Ground terminal 12
Front mounting, right
Service distribution board mounting, left

Neutral terminal 13
Front mounting, left
Service distribution board mounting, right
→ Page 4/64

T0, T3, T5, T5B

Description

Cam switches can be used for many switching and control applications. For example as ON-OFF switches, main switches, main/control switches, instrument switches.

The switches consist of a hand actuator, the switch unit and the mounting accessories.

The contact chamber (contact unit = BE) contains 1 or 2 contacts.

Our "T Cam Switches" catalog has over 800 popular standard contact sequences (please request under K115D/F/GB, article no. 077643).

The following pages feature a selection of our standard contact sequences.

T cam switches and P switch-disconnectors are manufactured without PCB, CFC, asbestos and silicon.The contacts are cadmium free.

The CI-K... insulated enclosures are silicon and halogen free.

Cam switches T0 and T3

Key to part numbers

T..... ... - .....- ..../ ....

↑	↑	↑	↑
Switch size T0 or T3	**Number of contact chambers** = contact units	**Contact sequence number**	**Mounting form** → Page 4/2

Using the modular system to convert the mounting form



Cam switch TB5

Key to part numbers

T..... ... - .....- ..../ ....

↑	↑	↑	↑
Switch size T5(B)	**Number of contact chambers** = contact units	**Contact sequence number**	**Mounting form** → Page 4/2

Using the modular system to convert the mounting form T5(B)



Note 1) Including shaft

P1, P3, TM

Switch-disconnectors P1 and P3

Key to part numbers

P. . . . . - . . . . . / . . . . . - . . . . . / . . . . . .

↑	↑	↑	↑	↑
Switch size P1 or P3	**Rated uninterrupted current**	**Mounting form** → Page 4/2	**Part no. suffix** (if required)	**Accessories** from → Page 7/47

Add-on functions due to modular system



3-pole basic unit
.../E or .../Z

Switched neutral
Can be fitted left
or right
(for P1.../I: left only)

Auxiliary contact
Can be fitted left
or right
(for P1.../I: left only)

Terminal shroud
can be fitted at
top or bottom

N + PE terminals,
also as cover interlock
on .../Z-switches.

TM mini cam switches

The TM mini cam switch is a particularly small switch with a small space requirement. It is ideally suited for small voltages and currents such as electronic controls. For greater safety the contacts are gold plated.

TM switches have consecutive terminal markings starting with 1.

Selection pages: Starting on → Page7/54

Key to part numbers

TM-. . . . . - . . . . . / . . . . . + ...

↑	↑	↑	↑
Number of contact chambers = contact units	**Contact sequence number**	**Mounting form** → Page 4/2	**Accessories** → Page 7/59

Circuit representation



(see also ordering example in the electronic catalogue)

Switch from 0 to 1

Contact 1 – 2 open,
Contact 3 – 4 open,
Contact 5 – 6 open,
Contact 7 – 8 closed

Switch from 1 to START
with automatic return to 1

Contact 1 – 2 open,
Contact 3 – 4 closed,
Contact 5 – 6 open,
Contact 7 – 8 remains closed

Switch from 1 to 0

Contact 1 – 2 open,
Contact 3 – 4 open,
Contact 5 – 6 open,
Contact 7 – 8 open

Switch from 0 to 2

Contact 1 – 2 closed,
Contact 3 – 4 open,
Contact 5 – 6 open,
Contact 7 – 8 closed

Switch from 2 to START
with automatic return to 2
Contact 1 – 2 open,
Contact 3 – 4 open,
Contact 5 – 6 closes with early make,
Contact 7 – 8 opens with late break

Switch from 2 to 0

Contact 1 – 2 open,
Contact 3 – 4 open,
Contact 5 – 6 open,
Contact 7 – 8 open

Ordering

Contact sequence	Front plate no.	Main contacts	Auxiliary contacts		Max. motor rating AC-23 A, 400/415 V, 50/60 Hz	Rated uninterrupted current	Flush mounting **Front IP65**		Std. pack
		Pole			400 V		**Part no.** Article no.	**Price** See price list	
	FS 908	N/O	N/O	N/C	P kW	I_u A			
Main switch as emergency switching off/emergency stop device									
With red rotary handle and yellow locking collar To IEC/EN 60204-1, VDE 0113 Part 1 Lockable in the 0 (Off) position									
Without auxiliary contacts									
		1	0	0	6.5	20	**T0-1-8200/EA/SVB** 053110		1 Off
					13	32	**T3-1-8200/EA/SVB**[1] 066576		
					22	63	**T5B-1-8200/EA/SVB**[3] 094279		
		2	0	0	6.5	20	**T0-1-102/EA/SVB**[1] 091078		
					13	32	**T3-1-102/EA/SVB**[1] 014374		
					22	63	**T5B-1-102/EA/SVB**[3] 094469		
					30	100	**T5-1-102/EA/SVB** 098808		1 Off
		3	0	0	6.5	20	**T0-2-1/EA/SVB**[1] 038873		1 Off
					13	25	**P1-25/EA/SVB**[1] 041097		
					13	25			
					15	32	**P1-32/EA/SVB**[1] 081438		
					37	63	**P3-63/EA/SVB**[1] 031607		
					45	125	**P5-125/EA/SVB**[4] 280898		
					50	100	**P3-100/EA/SVB**[1] 074320		
					55	160	**P5-160/EA/SVB**[4] 280922		
					90	250	**P5-250/EA/SVB**[4] 280936		
					110	315	**P5-315/EA/SVB**[4] 280950		
		3 + N	0	0	6.5	20	**T0-2-8900/EA/SVB**[1] 207400		1 Off
		3 + N	0	0	13	25	**P1-25/EA/SVB/N**[1] 081587		
					13	25			
					15	32	**P1-32/EA/SVB/N**[1] 091079		
					15	32			
					37	63	**P3-63/EA/SVB/N**[1] 010398		
					45	125	**P5-125/EA/SVB/N**[4] 280910		
					50	100	**P3-100/EA/SVB/N**[1] 019890		
					55	160	**P5-160/EA/SVB/N**[4] 280924		

Surface mounting **IP65** totally insulated			Rear mounting **Front IP65**			
Part no. Article no.	**Price** See price list	Std. pack	**Part no.** Article no.	**Price** See price list	Std. pack	**Information relevant for export to North America**
T0-1-8200/I1/SVB 207145		1 Off	**T0-1-8200/V/SVB** 057856		1 Off	1)
T3-1-8200/I2/SVB[2] 207200		1 Off	**T3-1-8200/V/SVB**[1] 007255			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
T5B-1-8200/I4/SVB[3] 207240		1 Off	**T5B-1-8200/V/SVB**[3] 094273			
T0-1-102/I1/SVB 207143		1 Off	**T0-1-102/V/SVB**[1] 095824			
T3-1-102/I2/SVB[2] 207198		1 Off	**T3-1-102/V/SVB**[1] 019120			
T5B-1-102/I4/SVB[3] 207238		1 Off	**T5B-1-102/V/SVB**[3] 094463			
T5-1-102/I5/SVB 207273		1 Off				
T0-2-1/I1/SVB 207147		1 Off	**T0-2-1/V/SVB**[1] 043619		1 Off	2)
P1-25/I2/SVB[2] 207293		1 Off	**P1-25/V/SVB**[2] 055335			Product Standards: UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
P1-25/I2H/SVB 226900		1 Off				
P1-32/I2/SVB[2] 207314		1 Off	**P1-32/V/SVB**[1] 095676			
P3-63/I4/SVB[1] 207343		1 Off	**P3-63/V/SVB**[1] 048218			
			P5-125/V/SVB[4] 280914			
P3-100/I5/SVB[1] 207373		1 Off	**P3-100/V/SVB**[1] 088558			
			P5-160/V/SVB[4] 280928			3)
			P5-250/V/SVB[4] 280942			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV7 CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 1, 3R, 12, 13
			P5-315/V/SVB[4] 280956			
T0-2-8900/I1/SVB 207151		1 Off	**T0-2-8900/V/SVB**[1] 207405		1 Off	
P1-25/I2/SVB/N[2] 207298		1 Off	**P1-25/V/SVB/N**[2] 086333			
P1-25/I2H/SVB/N 227860		1 Off				
P1-32/I2/SVB/N[2] 207319		1 Off	**P1-32/V/SVB/N**[1] 095825			
P1-32/I2H/SVB/N 227871		1 Off				4)
P3-63/I4/SVB/N[1] 207349		1 Off	**P3-63/V/SVB/N**[1] 015144			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV, NLRV7 CSA File No.: 223805 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
			P5-125/V/SVB/N[4] 280916			
P3-100/I5/SVB/N[1] 207379		1 Off	**P3-100/V/SVB/N**[1] 024636			
			P5-160/V/SVB/N[4] 280930			

Contact sequence	Front plate no.	Main contacts	Auxiliary contacts		Max. motor rating AC-23 A, 400/415 V, 50/60 Hz	Rated uninterrupted current	Flush mounting **Front IP65**		Std. pack	Surface mounting **IP65** totally insulated		Std. pack	Rear mounting **Front IP65**		Std. pack	**Information relevant for export to North America**
		Pole			400 V		**Part no.** Article no.	**Price** See price list		**Part no.** Article no.	**Price** See price list		**Part no.** Article no.	**Price** See price list		
	FS 908	N/O	N/O	N/C	P kW	I_u A										
Main switch as emergency switching off/emergency stop device																
With red rotary handle and yellow locking collar To IEC/EN 60204-1, VDE 0113 Part 1 Lockable in the 0 (Off) position																
Without auxiliary contacts																
		3 + N	0	0	90	250	**P5-250/EA/SVB/N**[4] 280938		1 Off				**P5-250/V/SVB/N**[4] 280944		1 Off	1)
		3 + N	0	0	110	315	**P5-315/EA/SVB/N**[4] 280952						**P5-315/V/SVB/N**[4] 280958			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
		6	0	0	6.5	20	**T0-3-8342/EA/SVB**[1] 029382			**T0-3-8342/I1/SVB** 207159		1 Off	**T0-3-8342/V/SVB**[1] 034128			
					13	32	**T3-3-8342/EA/SVB**[1] 071326			**T3-3-8342/I2/SVB**[2] 207208		1 Off	**T3-3-8342/V/SVB**[1] 076072			
					22	63	**T5B-3-8342/EA/SVB**[3] 092308			**T5B-3-8342/I4/SVB**[3] 207242		1 Off	**T5B-3-8342/V/SVB**[3] 092300			
					30	100	**T5-3-8342/EA/SVB** 096383		1 Off	**T5-3-8342/I5/SVB** 207279		1 Off	**T5-3-8342/V/SVB** 096381		1 Off	
		8	0	0	6.5	20	**T0-4-8344/EA/SVB**[1] 008267		1 Off	**T0-4-8344/I1/SVB** 207163		1 Off	**T0-4-8344/V/SVB**[1] 014007		1 Off	
					13	32	**T3-4-8344/EA/SVB**[1] 008964			**T3-4-8344/I2/SVB**[2] 207212		1 Off	**T3-4-8344/V/SVB**[1] 020598			2)
					22	63	**T5B-4-8344/EA/SVB**[3] 092062			**T5B-4-8344/I4/SVB**[3] 207248		1 Off	**T5B-4-8344/V/SVB**[3] 092056			Product Standards: UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
					30	95				**T5-4-8344/I5/SVB** 207283		1 Off				
					30	100	**T5-4-8344/EA/SVB** 095961		1 Off				**T5-4-8344/V/SVB** 095959		1 Off	
With auxiliary contacts																
		3	1	0	6.5	20	**T0-2-15679/EA/SVB**[1] 081588		1 Off	**T0-2-15679/I1/SVB** 207149		1 Off	**T0-2-15679/V/SVB**[1] 086334		1 Off	
		3	1	1	13	25	**P1-25/EA/SVB/HI11**[1] 091080			**P1-25/I2/SVB/HI11**[2] 207297		1 Off	**P1-25/V/SVB/HI11**[1] 095826			3)
					13	25				**P1-25/I2H/SVB/HI11** 226902		1 Off				Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV7 CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 1, 3R, 12, 13
					15	32	**P1-32/EA/SVB/HI11**[1] 072567			**P1-32/I2/SVB/HI11**[1] 207318		1 Off	**P1-32/V/SVB/HI11**[1] 015145			
					15	32				**P1-32/I2H/SVB/HI11** 227870		1 Off				
					37	63	**P3-63/EA/SVB/HI11**[1] 019891			**P3-63/I4/SVB/HI11**[1] 207348		1 Off	**P3-63/V/SVB/HI11**[1] 024637			
					50	100	**P3-100/EA/SVB/HI11**[1] 029383			**P3-100/I5/SVB/HI11**[1] 207378		1 Off	**P3-100/V/SVB/HI11**[1] 034129			
		3	1	0	45	125	**P5-125/EA/SVB/HI10**[4] 280899		1 Off				**P5-125/V/SVB/HI10**[4] 280915		1 Off	
					55	160	**P5-160/EA/SVB/HI10**[4] 280923						**P5-160/V/SVB/HI10**[4] 280929			4)
					90	250	**P5-250/EA/SVB/HI10**[4] 280937						**P5-250/V/SVB/HI10**[4] 280943			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV, NLRV7 CSA File No.: 223805 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
					110	315	**P5-315/EA/SVB/HI10**[4] 280951						**P5-315/V/SVB/HI10**[4] 280957			

Contact sequence	Front plate no.	Main contacts	Auxiliary contacts		Max. motor rating AC-23 A, 400/415 V, 50/60 Hz	Rated uninterrupted current	Flush mounting **Front IP65**		Surface mounting **IP65** totally insulated			Rear mounting **Front IP65**			
		Pole			400 V		**Part no.** Article no.	**Price** See price list	**Part no.** Article no.	**Price** See price list	Std. pack	**Part no.** Article no.	**Price** See price list	Std. pack	**Information relevant for export to North America**
	FS 908	N/O	N/O	N/C	P kW	I_u A									
Main switch as emergency switching off/emergency stop device															
With red rotary handle and yellow locking collar To IEC/EN 60204-1, VDE 0113 Part 1 Lockable in the 0 (Off) position															
With auxiliary contacts															
		3	2	1	6.5	20	**T0-3-15683/EA/SVB**[1] 015571		**T0-3-15683/I1/SVB** 207157		1 Off	**T0-3-15683/V/SVB**[1] 015634		1 Off	1)
		3	2	1	13	32	**T3-3-15683/EA/SVB**[1] 040478		**T3-3-15683/I2/SVB**[2] 207206		1 Off	**T3-3-15683/V/SVB**[1] 045224			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
		3 + N	1	1	6.5	20	**T0-3-15680/EA/SVB**[1] 038875		**T0-3-15680/I1/SVB** 207153		1 Off	**T0-3-15680/V/SVB**[1] 043621			UL File No.: E36332
					13	32	**P1-25/EA/SVB/N/HI11**[1] 048367					**P1-25/V/SVB/N/HI11**[1] 053113			UL CCN: NLRV
					13	32	**T3-3-15680/EA/SVB**[1] 012002		**T3-3-15680/I2/SVB**[2] 207202		1 Off	**T3-3-15680/V/SVB**[1] 016748			CSA File No.: 12528
		3 + N	1	1	15	32	**P1-32/EA/SVB/N/HI11**[1] 057859					**P1-32/V/SVB/N/HI11**[1] 062605			CSA Class No.: 3211-05
		3 + N	1	1	6.5	20	**T0-3-8901/EA/SVB**[1] 231932		**T0-3-8901/I1/SVB** 231934		1 Off				NA Certification: UL Listed, CSA certified
					13	32	**T3-3-8901/EA/SVB**[1] 231945		**T3-3-8901/I2/SVB**[2] 218987		1 Off				Suitable for: Branch circuits, suitable as motor disconnect
					22	63	**T5B-3-8901/EA/SVB**[3] 207420		**T5B-3-8901/I4/SVB**[3] 207244		1 Off	**T5B-3-8901/V/SVB**[3] 207422		1 Off	Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
					30	100	**T5-3-8901/EA/SVB** 207408		**T5-3-8901/I5/SVB** 207277		1 Off				
		3 + N	1	1	37	63	**P3-63/EA/SVB/N/HI11**[1] 067351		**P3-63/I4/SVB/N/HI11**[1] 207350		1 Off	**P3-63/V/SVB/N/HI11**[1] 072097		1 Off	2)
		3 + N	1	1	50	100	**P3-100/EA/SVB/N/HI11**[1] 076843		**P3-100/I5/SVB/N/HI11**[1] 207380		1 Off	**P3-100/V/SVB/N/HI11**[1] 081589			Product Standards: UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
		6	1	1	6.5	20	**T0-4-15682/EA/SVB**[1] 019892		**T0-4-15682/I1/SVB** 207161		1 Off	**T0-4-15682/V/SVB**[1] 024638			UL File No.: E36332
					13	32	**T3-4-15682/EA/SVB**[1] 054716		**T3-4-15682/I2/SVB**[2] 207210		1 Off	**T3-4-15682/V/SVB**[1] 059462			UL CCN: NLRV
					22	63	**T5B-4-15682/EA/SVB**[3] 207425		**T5B-4-15682/I4/SVB**[3] 207246		1 Off	**T5B-4-15682/V/SVB**[3] 207427			CSA File No.: 12528
					30	100	**T5-4-15682/EA/SVB** 207413		**T5-4-15682/I5/SVB** 207281		1 Off	**T5-4-15682/V/SVB** 207415		1 Off	CSA Class No.: 3211-05
		6	1	1	55	160			**T6-160-6/I45/SVB/HI11**[5] 201448			**T6-160-6/V/SVB/HI11** 200619			NA Certification: UL Listed, CSA certified
		6	1	1	132	275			**T8-3-8342/I48/SVB/HI11**[5] 201450			**T8-3-8342/V/SVB/HI11** 200620			Suitable for: Branch circuits, suitable as motor disconnect
															Degree of Protection: IEC: IP65; UL/CSA Type 1, 3R, 12, 13

3)

Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.: E36332
UL CCN: NLRV7
CSA File No.: 12528
CSA Class No.: 3211-05
NA Certification: UL Listed, CSA certified
Suitable for: Branch circuits, suitable as motor disconnect
Degree of Protection: IEC: IP65; UL/CSA Type 1, 3R, 12, 13

Notes
[5] Enclosure without flanges with K95/1N/BR
[6] With KS4-CI and K150/1/BR: Ingress protection IP64

Contact sequence	Front plate no.	Main contacts	Auxiliary contacts		Max. motor rating AC-23 A, 400/415 V, 50/60 Hz	Rated uninterrupted current	Flush mounting **Front IP65**		Std. pack	Surface mounting **IP65** totally insulated		Std. pack	Rear mounting **Front IP65**		Std. pack	**Information relevant for export to North America**
		Pole			400 V		**Part no.** Article no.	**Price** See price list		**Part no.** Article no.	**Price** See price list		**Part no.** Article no.	**Price** See price list		
	FS 908	N/O	N/O	N/C	P kW	I_u A										
Main switch without emergency switching off/emergency stop function																
With black rotary handle and locking collar Lockable in the 0 (Off) position																
Without auxiliary contacts																
	1	0	0		6.5	20	**T0-1-8200/EA/SVB-SW**[1] 055483		1 Off	**T0-1-8200/I1/SVB-SW** 207146		1 Off	**T0-1-8200/V/SVB-SW**[1] 060229		1 Off	1)
					13	32	**T3-1-8200/EA/SVB-SW**[1] 068949			**T3-1-8200/I2/SVB-SW**[2] 207201		1 Off	**T3-1-8200/V/SVB-SW**[1] 004882			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
					22	63	**T5B-1-8200/EA/SVB-SW**[3] 094278			**T5B-1-8200/I4/SVB-SW**[3] 207241		1 Off				
	2	0	0		6.5	20	**T0-1-102/EA/SVB-SW**[1] 093451			**T0-1-102/I1/SVB-SW** 207144		1 Off	**T0-1-102/V/SVB-SW**[1] 022330			
					13	32	**T3-1-102/EA/SVB-SW**[1] 016747			**T3-1-102/I2/SVB-SW**[2] 207199		1 Off	**T3-1-102/V/SVB-SW**[1] 021493			
					22	63	**T5B-1-102/EA/SVB-SW**[3] 094468			**T5B-1-102/I4/SVB-SW**[3] 207239		1 Off	**T5B-1-102/V/SVB-SW**[3] 094462			
					30	100	**T5-1-102/EA/SVB-SW** 098807		1 Off							2)
	3	0	0		6.5	20	**T0-2-1/EA/SVB-SW**[1] 041246		1 Off	**T0-2-1/I1/SVB-SW** 207148		1 Off	**T0-2-1/V/SVB-SW**[1] 045992		1 Off	Product Standards: UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
					13	25	**P1-25/EA/SVB-SW**[1] 048365			**P1-25/I2/SVB-SW**[2] 207294		1 Off	**P1-25/V/SVB-SW**[2] 050738			
					13	25				**P1-25/I2H/SVB-SW** 227861		1 Off				
					15	32	**P1-32/EA/SVB-SW**[1] 053111			**P1-32/I2/SVB-SW**[2] 207315		1 Off	**P1-32/V/SVB-SW**[1] 055484			
					15	32				**P1-32/I2H/SVB-SW** 227872		1 Off				
					37	63	**P3-63/EA/SVB-SW**[1] 057857			**P3-63/I4/SVB-SW**[1] 207344		1 Off	**P3-63/V/SVB-SW**[1] 060230			
					50	100	**P3-100/EA/SVB-SW**[1] 062603			**P3-100/I5/SVB-SW**[1] 207374		1 Off	**P3-100/V/SVB-SW**[1] 064976			3)
					45	125	**P5-125/EA/SVB-SW**[4] 280911						**P5-125/V/SVB-SW**[4] 280917			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV7 CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 1, 3R, 12, 13
					55	160	**P5-160/EA/SVB-SW**[4] 280925						**P5-160/V/SVB-SW**[4] 280931			
					90	250	**P5-250/EA/SVB-SW**[4] 280939						**P5-250/V/SVB-SW**[4] 280945			
					110	315	**P5-315/EA/SVB-SW**[4] 280953						**P5-315/V/SVB-SW**[4] 280959			
	3 + N	0	0		6.5	20	**T0-2-8900/EA/SVB-SW**[1] 207401		1 Off	**T0-2-8900/I1/SVB-SW** 207152		1 Off	**T0-2-8900/V/SVB-SW**[1] 207406		1 Off	
					13	25	**P1-25/EA/SVB-SW/N**[1] 083960			**P1-25/I2/SVB-SW/N**[2] 207296		1 Off	**P1-25/V/SVB-SW/N**[1] 088706			4)
					13	25				**P1-25/I2H/SVB-SW/N** 227863		1 Off				
					15	32	**P1-32/EA/SVB-SW/N**[1] 093452			**P1-32/I2/SVB-SW/N**[2] 207317		1 Off	**P1-32/V/SVB-SW/N**[1] 098198			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV, NLRV7 CSA File No.: 223805 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
					15	32				**P1-32/I2H/SVB-SW/N** 227874		1 Off				
					15	32				**P1-32/I2H/N** 227869		1 Off				
					37	63	**P3-63/EA/SVB-SW/N**[1] 012771			**P3-63/I4/SVB-SW/N**[1] 207346		1 Off	**P3-63/V/SVB-SW/N**[1] 017517			
					50	100	**P3-100/EA/SVB-SW/N**[1] 022263			**P3-100/I5/SVB-SW/N**[1] 207376		1 Off	**P3-100/V/SVB-SW/N**[1] 027009			

Contact sequence	Front plate no.	Main contacts	Auxiliary contacts		Max. motor rating AC-23 A, 400/415 V, 50/60 Hz	Rated uninterrupted current	Flush mounting **Front IP65**		Std. pack	Surface mounting **IP65**		Std. pack	Rear mounting **Front IP65**		Std. pack	**Information relevant for export to North America**
		Pole			400 V		**Part no.** Article no.	**Price** See price list		**Part no.** Article no.	**Price** See price list		**Part no.** Article no.	**Price** See price list		
	FS 908	N/O	N/O	N/C	P kW	I_u A										
Main switch without emergency switching off/emergency stop function																
With black rotary handle and locking collar Lockable in the 0 (Off) position																
Without auxiliary contacts																
		3 + N	0	0	45	125	**P5-125/EA/SVB-SW/N**[4] 280913		1 Off				**P5-125/V/SVB-SW/N**[4] 280919		1 Off	1)
					55	160	**P5-160/EA/SVB-SW/N**[4] 280927						**P5-160/V/SVB-SW/N**[4] 280933			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
					90	250	**P5-250/EA/SVB-SW/N**[4] 280941						**P5-250/V/SVB-SW/N**[4] 280947			UL File No.: E36332
					110	315	**P5-315/EA/SVB-SW/N**[4] 280955						**P5-315/V/SVB-SW/N**[4] 280961			UL CCN: NLRV
		6	0	0	6.5	20	**T0-3-8342/EA/SVB-SW**[1] 031755		1 Off	**T0-3-8342/I1/SVB-SW** 207160		1 Off	**T0-3-8342/V/SVB-SW**[1] 036501		1 Off	CSA File No.: 12528
					13	32	**T3-3-8342/EA/SVB-SW**[1] 073699			**T3-3-8342/I2/SVB-SW**[2] 207209		1 Off	**T3-3-8342/V/SVB-SW**[1] 078445			CSA Class No.: 3211-05
					22	63	**T5B-3-8342/EA/SVB-SW**[3] 092307			**T5B-3-8342/I4/SVB-SW**[3] 207243		1 Off	**T5B-3-8342/V/SVB-SW**[3] 092299			NA Certification: UL Listed, CSA certified
					30	100	**T5-3-8342/EA/SVB-SW** 096382		1 Off	**T5-3-8342/I5/SVB-SW** 207280		1 Off	**T5-3-8342/V/SVB-SW** 096380		1 Off	Suitable for: Branch circuits, suitable as motor disconnect
		8	0	0	6.5	20	**T0-4-8344/EA/SVB-SW**[1] 008268		1 Off	**T0-4-8344/I1/SVB-SW** 207164		1 Off	**T0-4-8344/V/SVB-SW**[1] 008272		1 Off	Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
					13	32	**T3-4-8344/EA/SVB-SW**[1] 008965			**T3-4-8344/I2/SVB-SW**[2] 207213		1 Off	**T3-4-8344/V/SVB-SW**[1] 008967			
					22	63	**T5B-4-8344/EA/SVB-SW**[3] 092061			**T5B-4-8344/I4/SVB-SW**[3] 207249		1 Off	**T5B-4-8344/V/SVB-SW**[3] 092055			2)
					30	95				**T5-4-8344/I5/SVB-SW** 207284		1 Off				Product Standards: UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
					30	100	**T5-4-8344/EA/SVB-SW** 095960		1 Off				**T5-4-8344/V/SVB-SW** 095958		1 Off	UL File No.: E36332
With auxiliary contacts																UL CCN: NLRV
		3	1	0	6.5	20	**T0-2-15679/EA/SVB-SW**[1] 083961		1 Off	**T0-2-15679/I1/SVB-SW** 207150		1 Off	**T0-2-15679/V/SVB-SW**[1] 088707		1 Off	CSA File No.: 12528
		3	1	1	13	25	**P1-25/EA/SVB-SW/HI11**[1] 070194			**P1-25/I2/SVB-SW/HI11**[2] 207295		1 Off	**P1-25/V/SVB-SW/HI11**[1] 098199			CSA Class No.: 3211-05
				1	13	25				**P1-25/I2H/SVB-SW/HI11** 227862		1 Off				NA Certification: UL Listed, CSA certified
				1	13	25				**P1-25/I2H/SVB/HI11** 226902		1 Off				Suitable for: Branch circuits, suitable as motor disconnect
				1	15	32	**P1-32/EA/SVB-SW/HI11**[1] 012772			**P1-32/I2/SVB-SW/HI11**[1] 207316		1 Off	**P1-32/V/SVB-SW/HI11**[1] 017518			Degree of Protection: IEC: IP65; UL/CSA Type 1, 3R, 12, 13
				1	15	32				**P1-32/I2H/SVB-SW/HI11** 227873		1 Off				
				1	37	63	**P3-63/EA/SVB-SW/HI11**[1] 022264			**P3-63/I4/SVB-SW/HI11**[1] 207345		1 Off	**P3-63/V/SVB-SW/HI11**[1] 027010			4)
				1	50	100	**P3-100/EA/SVB-SW/HI11**[1] 031756			**P3-100/I5/SVB-SW/HI11**[1] 207375		1 Off	**P3-100/V/SVB-SW/HI11**[1] 036502			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
		3	1	0	45	125	**P5-125/EA/SVB-SW/HI10**[4] 280912		1 Off				**P5-125/V/SVB-SW/HI10**[4] 280918		1 Off	UL File No.: E36332
				0	55	160	**P5-160/EA/SVB-SW/HI10**[4] 280926						**P5-160/V/SVB-SW/HI10**[4] 280932			UL CCN: NLRV, NLRV7
				0	90	250	**P5-250/EA/SVB-SW/HI10**[4] 280940						**P5-250/V/SVB-SW/HI10**[4] 280946			CSA File No.: 223805
				0	110	315	**P5-315/EA/SVB-SW/HI10**[4] 280954						**P5-315/V/SVB-SW/HI10**[4] 280960			CSA Class No.: 3211-05
		3	2	1	6.5	20	**T0-3-15683/EA/SVB-SW**[1] 015600		1 Off	**T0-3-15683/I1/SVB-SW** 207158		1 Off	**T0-3-15683/V/SVB-SW**[1] 015664		1 Off	NA Certification: UL Listed, CSA certified
		3	2	1	13	32	**T3-3-15683/EA/SVB-SW**[1] 042851		1 Off	**T3-3-15683/I2/SVB-SW**[2] 207207		1 Off				Suitable for: Branch circuits, suitable as motor disconnect
																Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12

Contact sequence	Front plate no.	Main contacts	Auxiliary contacts		Max. motor rating AC-23 A, 400/415 V, 50/60 Hz	Rated uninterrupted current	Flush mounting **Front IP65**		Std. pack	Surface mounting **IP65** totally insulated		Std. pack	Rear mounting **Front IP65**		Std. pack	**Information relevant for export to North America**
		Pole			400 V		**Part no.** Article no.	**Price** See price list		**Part no.** Article no.	**Price** See price list		**Part no.** Article no.	**Price** See price list		
	FS 908	N/O	N/O	N/C	P kW	I_u A										
Main switch without emergency switching off/emergency stop function																
With black rotary handle and locking collar Lockable in the 0 (Off) position																
With auxiliary contacts																
		3 + N	1	1	6.5	20	**T0-3-15680/EA/SVB-SW**[1] 041248		1 Off	**T0-3-15680/I1/SVB-SW** 207154		1 Off	**T0-3-15680/V/SVB-SW**[1] 045994		1 Off	1)
					13	32	**P1-25/EA/SVB-SW/N/HI11**[1] 050740			**T3-3-15680/I2/SVB-SW**[4] 207203		1 Off	**T3-3-15680/V/SVB-SW**[1] 019121			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
					13	32	**T3-3-8901/EA/SVB-SW**[1] 231946									
					15	32	**P1-32/EA/SVB-SW/N/HI11**[1] 060232						**P1-32/V/SVB-SW/N/HI11**[1] 064978			
		3 + N	1	1	6.5	20	**T0-3-8901/EA/SVB-SW**[1] 231933		1 Off	**T0-3-8901/I1/SVB-SW** 231935		1 Off			1 Off	
					13	32	**T3-3-15680/EA/SVB-SW**[1] 014375			**T3-3-8901/I2/SVB-SW**[2] 218988		1 Off	**P1-25/V/SVB-SW/N/HI11**[1] 055486			2)
					22	63	**T5B-3-8901/EA/SVB-SW**[3] 207421			**T5B-3-8901/I4/SVB-SW**[3] 207245		1 Off	**T5B-3-8901/V/SVB-SW**[3] 207423			Product Standards: UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
					30	100	**T5-3-8901/EA/SVB-SW** 207409		1 Off	**T5-3-8901/I5/SVB-SW** 207278		1 Off				
		3 + N	1	1	37	63	**P3-63/EA/SVB-SW/N/HI11**[1] 069724		1 Off	**P3-63/I4/SVB-SW/N/HI11**[1] 207347		1 Off	**P3-63/V/SVB-SW/N/HI11**[1] 074470			
		3 + N	1	1	50	100	**P3-100/EA/SVB-SW/N/HI11**[1] 079216		1 Off	**P3-100/I5/SVB-SW/N/HI11**[1] 207377		1 Off	**P3-100/V/SVB-SW/N/HI11**[1] 083962			
		6	1	1	6.5	20	**T0-4-15682/EA/SVB-SW**[1] 022265		1 Off	**T0-4-15682/I1/SVB-SW** 207162		1 Off	**T0-4-15682/V/SVB-SW**[1] 027011			
					13	32	**T3-4-15682/EA/SVB-SW**[1] 057089			**T3-4-15682/I2/SVB-SW**[2] 207211		1 Off	**T3-4-15682/V/SVB-SW**[1] 061835			
					22	63	**T5B-4-15682/EA/SVB-SW**[3] 207426			**T5B-4-15682/I4/SVB-SW**[3] 207247		1 Off	**T5B-4-15682/V/SVB-SW**[3] 207428			
					30	100	**T5-4-15682/EA/SVB-SW** 207414		1 Off	**T5-4-15682/I5/SVB-SW** 207282		1 Off	**T5-4-15682/V/SVB-SW** 207416		1 Off	
		6	1	1	55	160				**T6-160-6/I45/SVB-SW/HI11**[5] 201447		1 Off	**T6-160-6/V/SVB-SW/HI11** 200127			3)
					132	275				**T8-3-8342/I48/SVB-SW/HI11**[6] 201449		1 Off				Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV7 CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 1, 3R, 12, 13
					132	315							**T8-3-8342/V/SVB-SW/HI11** 200128			

Notes
[5] Enclosure without flanges with K95/1N/BR
[6] With KS4-CI and K150/1/BR: Ingress protection IP64

Contact sequence	Front plate no.	Main contacts Pole	Auxiliary contacts N/O	Auxiliary contacts N/O	Auxiliary contacts N/C	Max. motor rating: AC-23A 400/415 V 50/60 Hz P kW	Rated uninterrupted current I_u A	Flush mounting Front IP65 Part no. Article no.	Price See price list	Center mounting Front IP65 Part no. Article no.	Price See price list	Std. pack
	FS 908	N/O	N/O	N/C								
On-Off switches												
Without auxiliary contacts With black thumb-grip and front plate												
		1	0	0	6.5	20		**T0-1-8200/E**[1] 067352		**T0-1-8200/EZ**[2] 069725		1 Off
		1	0	0	6.5	20						
		1	0	0	13	32		**T3-1-8200/E**[4] 064208		**T3-1-8200/EZ**[4] 066581		
		1	0	0	22	63		**T5B-1-8200/E**[6] 094281				
		2	0	0	6.5	20		**T0-1-102/E**[1] 088709		**T0-1-102/EZ**[2] 091082		
		2	0	0	6.5	20						
		2	0	0	13	32		**T3-1-102/E**[1] 076073		**T3-1-102/EZ**[1] 078446		
		2	0	0	22	63		**T5B-1-102/E**[6] 094471				
		3	0	0	6.5	20		**T0-2-1/E**[1] 024639		**T0-2-1/EZ**[1] 027012		
		3	0	0	6.5	20						
		3	0	0	13	25		**P1-25/E**[1] 038724		**P1-25/EZ**[1] 041250		
		3	0	0	13	25						
		3	0	0	15	32		**P1-32/E**[1] 079065		**P1-32/EZ**[1] 048369		
		3	0	0	15	32						
		3	0	0	37	63		**P3-63/E**[8] 026861				
		3	0	0	45	125		**P5-125/E**[9] 280897				
		3	0	0	50	100		**P3-100/E**[8] 067201				
		3	0	0	55	160		**P5-160/E**[9] 280921				
		3	0	0	90	250		**P5-250/E**[9] 280935				
		3	0	0	110	315		**P5-315/E**[9] 280949				
		3 + N	0	0	6.5	20		**T0-2-8900/E**[1] 207398		**T0-2-8900/EZ**[1] 207402		
		3 + N	0	0	13	25		**P1-25/E/N**[1] 076845		**P1-25/EZ/N**[1] 079218		
		3 + N	0	0	13	25						
		3 + N	0	0	15	32		**P1-32/E/N**[1] 093456		**P1-32/EZ/N**[1] 095829		
		3 + N	0	0	15	32						
		3 + N	0	0	37	63		**P3-63/E/N**[8] 019894				
		3 + N	0	0	50	100		**P3-100/E/N**[8] 031759				
		4	0	0	6.5	20						

Surface mounting IP65 totally insulated Part no. Article no.	Price See price list	Std. pack	Distribution board - mounting Front IP30 Part no. Article no.	Price See price list	Rear mounting Front IP65 Part no. Article no.	Price See price list	Std. pack	Information relevant for export to North America
T0-1-8200/I1 207074		1 Off	**T0-1-8200/IVS**[3] 074471		**T0-1-8200/Z**[1] 076844		1 Off	1) → Page 4/24
					T0-1-15401/Z[1] 048346			2) → Page 4/24
T3-1-8200/I2[4] 207167		1 Off			**T3-1-8200/Z**[4] 071327			3) → Page 4/24
T5B-1-8200/I4[5] 207218		1 Off			**T5B-1-8200/Z**[6] 094270			4) → Page 4/24
T0-1-102/I1 207061		1 Off	**T0-1-102/IVS**[3] 015147		**T0-1-102/Z**[1] 095828			5) → Page 4/24
					T0-1-15402/Z[1] 062584			6) → Page 4/24
T3-1-102/I2[4] 207165		1 Off			**T3-1-102/Z**[4] 083192			7) → Page 4/24
T5B-1-102/I4[5] 207215		1 Off			**T5B-1-102/Z**[6] 094460			8) → Page 4/24
T0-2-1/I1 207081		1 Off	**T0-2-1/IVS**[3] 031758		**T0-2-1/Z**[1] 036504			9) → Page 4/24
T0-2-15403/I1 207088		1 Off			**T0-2-15403/Z**[1] 076822			
P1-25/I2[8] 207299		1 Off	**P1-25/IVS**[7] 052962		**P1-25/Z**[8] 057708			
P1-25/I2H 226898		1 Off						
P1-32/I2[8] 207320		1 Off	**P1-32/IVS**[7] 093303		**P1-32/Z**[8] 098049			
P1-32/I2H 227866		1 Off						
P3-63/I4[8] 207356		1 Off	**P3-63/IVS**[7] 041099		**P3-63/Z**[8] 050591			
					P5-125/Z[9] 280920			
P3-100/I5[8] 207381		1 Off	**P3-100/IVS**[7] 081439		**P3-100/Z**[8] 090931			
					P5-160/Z[9] 280934			
					P5-250/Z[9] 280948			
					P5-315/Z[9] 280962			
T0-2-8900/I1 207109		1 Off	**T0-2-8900/IVS**[3] 207403		**T0-2-8900/Z**[1] 207407			
P1-25/I2/N[8] 207303		1 Off	**P1-25/IVS/N**[7] 083964		**P1-25/Z/N**[8] 088710			
P1-25/I2H/N 226901		1 Off						
P1-32/I2/N[8] 207324		1 Off	**P1-32/IVS/N**[7] 010402		**P1-32/Z/N**[8] 015148			
P1-32/I2H/N 227869		1 Off						
P3-63/I4/N[8] 207360		1 Off	**P3-63/IVS/N**[7] 022267		**P3-63/Z/N**[8] 027013			
P3-100/I5/N[8] 207385		1 Off	**P3-100/IVS/N**[7] 034132		**P3-100/Z/N**[8] 038878			
T0-2-15404/I1 207089		1 Off	**T0-2-15404/IVS**[3] 088687		**T0-2-15404/Z**[1] 091060			

HPL04024EN

Contact sequence	Front plate no.	Main contacts Pole	Auxiliary contacts		Max. motor rating: AC-23A 400/415 V 50/60 Hz	Rated uninterrupted current	Flush mounting Front IP65		Center mounting Front IP65		Std. pack
							Part no. Article no.	**Price** See price list	**Part no.** Article no.	**Price** See price list	
		N/O	N/O	N/C	P	I_u					
					kW	A					
On-Off switches											
Without auxiliary contacts With black thumb-grip and front plate	FS 908	6	0	0	6.5	20	**T0-3-8342/E**[1] 043624		**T0-3-8342/EZ**[1] 045997		1 Off
		6	0	0	13	32	**T3-3-8342/E**[4] 045225				
		6	0	0	22	63	**T5B-3-8342/E**[6] 092310				
		8	0	0	6.5	20	**T0-4-8344/E**[1] 014000		**T0-4-8344/EZ**[1] 014002		
		8	0	0	13	32	**T3-4-8344/E**[4] 020593		**T3-4-8344/EZ**[4] 020595		
		8	0	0	22	63	**T5B-4-8344/E**[6] 092064				

Information relevant for export to North America

1)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

2)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type: –

3)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP30; UL/CSA Type: –

6)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-07
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 1

7)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type: –

8)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

HPL04025EN

Surface mounting IP65 totally insulated		Std. pack	Distribution board - mounting Front IP30		Rear mounting Front IP65		Std. pack	Information relevant for export to North America
Part no. Article no.	**Price** See price list		**Part no.** Article no.	**Price** See price list	**Part no.** Article no.	**Price** See price list		
T0-3-8342/I1 207131		1 Off	**T0-3-8342/IVS**[3] 050743		**T0-3-8342/Z**[1] 055489		1 Off	
T3-3-8342/I2[4] 207187		1 Off			**T3-3-8342/Z**[4] 052344			
T5B-3-8342/I4[5] 207226		1 Off			**T5B-3-8342/Z**[6] 092297			
T0-4-8344/I1 207139		1 Off	**T0-4-8344/IVS**[3] 014006		**T0-4-8344/Z**[1] 014009			
T3-4-8344/I2[4] 207194		1 Off			**T3-4-8344/Z**[4] 020600			
T5B-4-8344/I4[5] 207233		1 Off						

4)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-07
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

5)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-07
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type: –

9)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	223805
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

Contact sequence	Front plate no.	Main contacts Pole	Auxiliary contacts N/O	Auxiliary contacts N/O	Auxiliary contacts N/C	Max. motor rating: AC-23A 400/415 V 50/60 Hz 400 V P kW	Rated uninterrupted current I_u A	Flush mounting Front IP65 Part no. Article no.	Price See price list	Std. pack	Center mounting Front IP65 Part no. Article no.	Price See price list	Std. pack	Surface mounting IP65 totally insulated Part no. Article no.	Price See price list	Std. pack	Distribution board - mounting Front IP30 Part no. Article no.	Price See price list	Std. pack	Rear mounting Front IP65 Part no. Article no.	Price See price list	Std. pack
On-Off switches without emergency switching off/emergency stop function																						
With auxiliary contacts With black thumb-grip and front plate																						
	FS 908	3	1	0	6.5	20		**T0-2-15679/E**[1] 029387		1 Off	**T0-2-15679/EZ**[1] 031760		1 Off	**T0-2-15679/I1** 207094		1 Off	**T0-2-15679/IVS**[2] 036506		1 Off	**T0-2-15679/Z**[1] 041252		1 Off
														P1-25/I2H/HI11 226899								
		3	1	1	13	25																
		3	1	1	15	32								**P1-32/I2H/HI11** 227867								
		3	2	1	6.5	20		**T0-3-15683/E**[1] 016619			**T0-3-15683/EZ**[1] 016658			**T0-3-15683/I1** 207118			**T0-3-15683/IVS**[2] 016722					
		3	2	1	13	32		**T3-3-15683/E**[3] 014377						**T3-3-15683/I2**[3] 207182		1 Off						
		3 + N	1	1	6.5	20		**T0-3-8901/E**[1] 231938			**T0-3-8901/EZ**[1] 231939			**T0-3-8901/I1** 231941		1 Off	**T0-3-8901/IVS**[2] 231940					
		3 + N	1	1	13	32		**T3-3-8901/E**[3] 231949			**T3-3-8901/EZ**[3] 231950			**T3-3-8901/I2**[3] 231951		1 Off				**T3-3-8901/Z**[3] 231952		
		6	1	1	6.5	20		**T0-4-15682/E**[1] 010405			**T0-4-15682/EZ**[1] 012778			**T0-4-15682/I1** 207135		1 Off	**T0-4-15682/IVS**[2] 017524			**T0-4-15682/Z**[1] 022270		
					13	32		**T3-4-15682/E**[3] 023869						**T3-4-15682/I2**[3] 207190		1 Off				**T3-4-15682/Z**[3] 030988		
					22	63		**T5B-4-15682/E**[4] 207424						**T5B-4-15682/I4**[5] 207229		1 Off				**T5B-4-15682/Z**[4] 207429		
					30	100		**T5-4-15682/E** 207412						**T5-4-15682/I5** 207269		1 Off				**T5-4-15682/Z** 207417		

Information relevant for export to North America

1)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

2)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP30; UL/CSA Type: –

3)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-07
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

4)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-07
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 1

5)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-07
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type: –

6)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type: –

7)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

HPL04028EN

Contact sequence	Front plate no.	Main contacts Pole	Auxiliary contacts		Max. motor rating: AC-23A 400/415 V 50/60 Hz	Rated uninterrupted current	Flush mounting Front IP65		Std. pack
	FS 908	N/O I	N/O I	N/C L	400 V P kW	I_u A	**Part no.** Article no.	**Price** See price list	
On-Off switches as an emergency switching off/emergency stop device									
With red thumb-grip and yellow front plate To IEC/EN 60204-1, VDE 113 Part 1									
		1	0	0	6.5	20	**T0-1-8200/E-RT**[1] 009474		1 Off
					13	32	**T3-1-8200/E-RT**[3] 017025		
					22	63	**T5B-1-8200/E-RT**[4] 094280		
					30	100	**T5-1-8200/E-RT** 097225		1 Off
		2	0	0	6.5	20	**T0-1-102/E-RT**[1] 009046		1 Off
					13	32	**T3-1-102/E-RT**[1] 016318		
					22	63	**T5B-1-102/E-RT**[4] 094470		
		3	0	0	6.5	20	**T0-2-1/E-RT**[1] 011082		
					13	25	**P1-25/E-RT**[1] 002388		
					15	32	**P1-32/E-RT**[1] 003197		
					37	63	**P3-63/E-RT**[7] 005743		
					50	100	**P3-100/E-RT**[7] 007189		
		3 + N	0	0	6.5	20	**T0-2-8900/E-RT**[1] 207399		

Information relevant for export to North America

1)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

2)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP30; UL/CSA Type: –

6)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type: –

7)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

HPL04029EN

Center mounting Front IP65			Surface mounting IP65 totally insulated			Distribution board - mounting Front IP30			Rear mounting Front IP65		
Part no. Article no.	**Price** See price list	Std. pack	**Part no.** Article no.	**Price** See price list	Std. pack	**Part no.** Article no.	**Price** See price list	Std. pack	**Part no.** Article no.	**Price** See price list	Std. pack
			T0-1-8200/I1-RT 207075		1 Off	**T0-1-8200/IVS-RT**[2] 081956		1 Off			
			T0-1-102/I1-RT 207062		1 Off	**T0-1-102/IVS-RT**[2] 079583					
			T3-1-102/I2-RT[3] 207166		1 Off						
			T0-2-1/I1-RT 207082		1 Off	**T0-2-1/IVS-RT**[2] 084329					
			P1-25/I2-RT[7] 207300		1 Off	**P1-25/IVS-RT**[6] 013140					
			P1-32/I2-RT[7] 207321		1 Off	**P1-32/IVS-RT**[6] 022632					
			P3-63/I4-RT[7] 207357		1 Off	**P3-63/IVS-RT**[6] 045845					
			P3-100/I5-RT[7] 207382		1 Off	**P3-100/IVS-RT**[6] 086185					
			T0-2-8900/I1-RT 207110		1 Off	**T0-2-8900/IVS-RT**[2] 207404					

3)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-07
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

4)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-07
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 1

5)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-07
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type: –

Contact sequence	Front plate no.	Main contacts Pole	Auxiliary contacts N/O	Auxiliary contacts N/O	Auxiliary contacts N/C	Max. motor rating AC-23 A, 400/415 V, 50/60 Hz 400 V P kW	Rated uninterrupted current I_u A	As an emergency switching off/ emergency stop device[1] Surface mounting IP65 totally insulated Part no. Article no.	Price See price list	Std. pack	Without emergency switching off/ emergency stop function[2] Surface mounting IP65 totally insulated Part no. Article no.	Price See price list	Std. pack	Notes
	FS 908													
Safety switches with warning label														
		3	0	0	13	25		**P1-25/I2-SI**[3] 207308		1 Off	**P1-25/I2-SI-SW**[3] 207309		1 Off	
					15	32		**P1-32/I2-SI**[3] 207329			**P1-32/I2-SI-SW**[3] 207330			
					37	63		**P3-63/I4-SI**[3] 207361			**P3-63/I4-SI-SW**[3] 207362			
					50	100		**P3-100/I5-SI**[3] 207386			**P3-100/I5-SI-SW**[3] 207387			
		3	1	1	13	25		**P1-25/I2-SI/HI11**[3] 207310			**P1-25/I2-SI/HI11-SW**[3] 207311			
					15	32		**P1-32/I2-SI/HI11**[3] 207331			**P1-32/I2-SI/HI11-SW**[3] 207332			
					37	63		**P3-63/I4-SI/HI11**[3] 207363			**P3-63/I4-SI/HI11-SW**[3] 207364			
					50	100		**P3-100/I5-SI/HI11**[3] 207388			**P3-100/I5-SI/HI11-SW**[3] 207389			
		3 + N	0	0	13	25		**P1-25/I2-SI/N**[3] 207312			**P1-25/I2-SI/N-SW**[3] 207313			
					15	32		**P1-32/I2-SI/N**[3] 207333			**P1-32/I2-SI/N-SW**[3] 207334			
					37	63		**P3-63/I4-SI/N**[3] 207365			**P3-63/I4-SI/N-SW**[3] 207366			
					50	100		**P3-100/I5-SI/N**[3] 207390			**P3-100/I5-SI/N-SW**[3] 207391			
		6	0	0	22	63		**T5B-3-8342/I4-SI**[4] 207250			**T5B-3-8342/I4-SI-SW**[4] 207251			
		6	0	0	30	100		**T5-3-8342/I5-SI**[4] 207447			**T5-3-8342/I5-SI-SW**[4] 207448			
		6	1	1	22	63		**T5B-4-15682/I4-SI**[4] 207254			**T5B-4-15682/I4-SI-SW**[4] 207255			
		6	1	1	30	100		**T5-4-15682/I5-SI**[4] 207285			**T5-4-15682/I5-SI-SW**[4] 207286			
		6	2	0	22	63		**T5B-4-8903/I4-SI**[4] 207258			**T5B-4-8903/I4-SI-SW**[4] 207259			
		6	2	0	30	100		**T5-4-8903/I5-SI**[4] 207289			**T5-4-8903/I5-SI-SW**[4] 207290			

Notes

[1] Surface mounting IP65 : With red rotary handle and yellow locking collar with auxiliary contacts , lockable in position 0 with cover interlock, according to IEC/EN 60204-1, VDE 0113 Part 1

[2] Surface mounting IP65 : With black rotary handle and locking collar with auxiliary contacts Lockable in position 0 with cover interlock

Engineering

Maintenance, repair and safety switches all have the same electrical function. They are designed to safely isolate electrical installations (loads) from mains power during maintenance and repair work and to ensure that a hazard does not arise which endangers personnel, machinery and production materials.

A safety switch is an additional enclosed main switch = isolator dedicated to an individual electrical load and mounted in the immediate vicinity of the motor or the electrical load.

This is particularly important if there is any danger of the main switch being inadvertently operated.

Application

By using his padlock (up to 3), each fitter/electrician involved can protect themselves by preventing unauthorized personnel from switching the unit on. Maintenance/manual override switches are simply additional enclosed main switches with a padlocking feature.

Enclosed main switch with padlocking facility

Features

- Safety switches are always housed in insulated enclosures and have an inscription saying "Safety Switch" on a bright orange label.
- Switches to be used for emergency stop switching have a red handle and yellow locking collar in accordance with STOP category 0 (as per IEC/EN 60204/VDE 0113).
- If the switch is not approved for emergency stop switching, both parts will be black ("SW" part no. suffix).
- The cover and handle are interlocked by fitting a padlock.

Selection

The switches must be selected according to the following performance specifications:

1) According to motor switching capacity, when the switch is fitted in such a way that the operator may use it for operational ON and OFF switching.

2) The rating data always applies to 3 poles. When the motor rating is divided between 6 poles, such as for star-delta switching, a 6 pole switch can be used to control 1.73 times the rated power.

3) If the switch has a load-shedding Contact (LA), you can select the appropriate switch according to the uninterrupted current. The load-shedding contact is an auxiliary contact, which is closed in the ON position and opens early when switching off, so that a contactor located in the circuit takes over the switching duty and the maintenance/safety switch operates at zero load. When switching on, the load-shedding contact closes later than or at the same time as the main contacts. With P and T switches this is the N/O auxiliary contact.

4)The "ON" position can be locked with a padlock (by altering the handle).

This is not permissible for switches with a red/yellow handle.

Safety switch with load shedding and signaling



Contact sequence	Front plate no.	Main contacts Pole	Max. operating power AC-23A 400/415 V 50/60 Hz	Rated uninterrupted current	Flush mounting Front IP65			Center mounting Front IP65			Surface mounting IP65 totally insulated			Distribution board mounting Front IP30			Rear mounting Front IP65		
		N/O I	400 V P kW	I_u A	**Part no.** Article no.	**Price** See price list	Std. pack	**Part no.** Article no.	**Price** See price list	Std. pack	**Part no.** Article no.	**Price** See price list	Std. pack	**Part no.** Article no.	**Price** See price list	Std. pack	**Part no.** Article no.	**Price** See price list	Std. pack
Changeover switches																			
With black thumb-grip and front plate without emergency switching off/emergency stop function																			
	FS 684	1	6.5	20	**T0-1-8210/E**[1] 012742		1 Off	**T0-1-8210/EZ**[1] 048337		1 Off	**T0-1-8210/I1** 207076		1 Off	**T0-1-8210/IVS**[2] 074440		1 Off	**T0-1-8210/Z**[1] 019862		1 Off
			13	32	**T3-1-8210/E**[1] 054718			**T3-1-8210/EZ**[1] 003072			**T3-1-8210/I2**[3] 207169						**T3-1-8210/Z**[1] 057091		
			22	63	**T5B-1-8210/E**[5] 094261						**T5B-1-8210/I4**[4] 207432						**T5B-1-8210/Z**[5] 094258		
	FS 4011	1	6.5	20				**T0-1-8214/EZ**[1] 076815									**T0-1-8214/Z**[1] 050720		
	FS 684	2	6.5	20	**T0-2-8211/E**[1] 022234			**T0-2-8211/EZ**[1] 053083			**T0-2-8211/I1** 207102		1 Off	**T0-2-8211/IVS**[2] 076813			**T0-2-8211/Z**[1] 029354		
			13	32	**T3-2-8211/E**[1] 061837			**T3-2-8211/EZ**[1] 003075			**T3-2-8211/I2**[3] 207178						**T3-2-8211/Z**[1] 064210		
			22	63	**T5B-2-8211/E**[5] 093094						**T5B-2-8211/I4**[4] 207220						**T5B-2-8211/Z**[5] 093082		
		3	6.5	20	**T0-3-8212/E**[1] 029353			**T0-3-8212/EZ**[1] 057829			**T0-3-8212/I1** 207123		1 Off	**T0-3-8212/IVS**[2] 079186			**T0-3-8212/Z**[1] 036473		
			13	32	**T3-3-8212/E**[1] 068956			**T3-3-8212/EZ**[1] 003080			**T3-3-8212/I2**[3] 207183						**T3-3-8212/Z**[1] 071329		
			22	63	**T5B-3-8212/E**[5] 092386						**T5B-3-8212/I4**[4] 207223						**T5B-3-8212/Z**[5] 092383		
			30	100	**T5-3-8212/E** 096466		1 Off				**T5-3-8212/I5** 207266		1 Off				**T5-3-8212/Z** 096464		1 Off
		3	55	160	**T6-3-8212/E/HI12** 214781		1 Off												
		3	132	315	**T8-3-8212/E/HI12** 214782		1 Off												

Information relevant for export to North America

1)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

2)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits
Degree of Protection	IEC: IP30; UL/CSA Type: –

3)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

4)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV7
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits
Degree of Protection	IEC: IP65; UL/CSA Type: –

5)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV7
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits
Degree of Protection	IEC: IP65; UL/CSA Type 1

HPL04034EN

Contact sequence	Front plate no.	Main contacts Pole N/O	Max. operating power AC-23A 400/415 V 50/60 Hz 400 V P kW	Rated uninterrupted current I_u A	Flush mounting Front IP65 **Part no.** Article no.	**Price** See price list	Std. pack
Changeover switches							
With black thumb-grip and front plate Without emergency switching off/emergency stop function							
	FS 161629	4	13	32	**T3-4-8902/E**[1] 215222		1 Off
			22	63	**T5B-4-8902/E**[5] 207430		
			30	100	**T5-4-8902/E** 207418		
	FS 684	4	6.5	20	**T0-4-8213/E**[1] 031726		
			13	32	**T3-4-8213/E**[1] 076075		
			22	63	**T5B-4-8213/E**[5] 092112		
			30	100	**T5-4-8213/E** 096014		
	FS 953	4	6.5	20	**T0-4-8294/E**[1] 010371		
			13	32	**T3-4-8294/E**[1] 002513		
			22	63	**T5B-4-8294/E**[5] 092084		
			30	100	**T5-4-8294/E** 095986		1 Off

Information relevant for export to North America

1)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

2)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits
Degree of Protection	IEC: IP30; UL/CSA Type: –

HPL04035EN

Center mounting Front IP65 **Part no.** Article no.	**Price** See price list	Std. pack	Surface mounting IP65 totally insulated **Part no.** Article no.	**Price** See price list	Std. pack	Distribution board mounting Front IP30 **Part no.** Article no.	**Price** See price list	Std. pack	Rear mounting Front IP65 **Part no.** Article no.	**Price** See price list	Std. pack
T3-4-8902/EZ[1] 215223		1 Off	**T3-4-8902/I2**[3] 215224		1 Off				**T3-4-8902/Z**[1] 215225		1 Off
			T5B-4-8902/I4[4] 207237		1 Off				**T5B-4-8902/Z**[5] 207431		1 Off
			T5-4-8902/I5 207214		1 Off				**T5-4-8902/Z** 207419		1 Off
T0-4-8213/EZ[1] 062575		1 Off	**T0-4-8213/I1** 207136		1 Off	**T0-4-8213/IVS**[2] 081559		1 Off	**T0-4-8213/Z**[1] 043592		1 Off
T3-4-8213/EZ[1] 003079		1 Off	**T3-4-8213/I2**[3] 207191		1 Off				**T3-4-8213/Z**[1] 078448		
			T5B-4-8213/I4[4] 207230		1 Off				**T5B-4-8213/Z**[5] 092109		
			T5-4-8213/I5 207270		1 Off				**T5-4-8213/Z** 096012		1 Off
T0-4-8294/EZ[1] 072069		1 Off	**T0-4-8294/I1** 207138		1 Off	**T0-4-8294/IVS**[2] 043594		1 Off			
			T3-4-8294/I2[3] 207193		1 Off				**T3-4-8294/Z**[1] 004886		1 Off
			T5B-4-8294/I4[4] 207232		1 Off				**T5B-4-8294/Z**[5] 092081		1 Off
			T5-4-8294/I5 207433		1 Off				**T5-4-8294/Z** 095984		1 Off

3)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

4)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV7
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits
Degree of Protection	IEC: IP65; UL/CSA Type: –

5)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV7
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits
Degree of Protection	IEC: IP65; UL/CSA Type 1