







SET60-K



SET80LT



SET105-K



SET150-N



SET210-N

- obudowa: tworzywo sztuczne
- casing: plastic

| Kanlux | Kanlux | | PRI | SEC | [W] | [°C] | | [g] |
|---|---|---|---|---|---|---|---|---|
| SET60-K | 01425 | biały / white | 220-240V~; 50/60Hz; 0,26A | 11,5V~; 4,9A; 60VA | 60 | max 50 | 1/-/100 | 72 |
| SET80LT | 01421 | biały / white | 220-240V~; 50/60Hz; 0,35A | 11,5V~; 6,9A; 80VA | 80 | max 50 | 1/-/100 | 100 |
| SET105-K | 01426 | biały / white | 220-240V~; 50/60Hz; 0,45A | 11,5V~; 8,8A; 105VA | 105 | max 40 | 1/-/100 | 98 |
| SET150-N | 01432 | biały / white | 220-240V~; 50/60Hz; 0,68A | 11,5V~; 150VA | 150 | max 45 | 1/-/50 | 200 |
| SET210-N | 01433 | biały / white | 220-240V~; 50/60Hz; 0,95A | 11,5V~; 210VA | 210 | max 45 | 1/-/50 | 225 |




**współczynnik mocy biernej cosØ dla SET60-K i SET105-K wynoszący 0,99, dla SET80LT, SET150-N i SET210-N wynoszący 0,97 / maksymalna dopuszczalna temperatura obudowy dla SET60-K wynosząca 80°C, dla pozostałych modeli wynosząca 85°C / zabezpieczenie termiczne wyłączające model SET80LT po przekroczeniu temperatury 100°C, modele SET150-N i SET210-N po przekroczeniu temperatury 110°C, modele SET60-K i SET105-K po przekroczeniu temperatury 120°C / wbudowane zabezpieczenie przeciwzwarciowe i przeciwprzeciążeniowe**
reactive power coefficient cosØ for SET60-K and SET105-K is 0,99, for SET80LT, SET150-N and SET210-N is 0,97 / max allowable temperature of a casing for SET60-K is 80°C, for the other models is 85°C / thermal protection switching SET80LT model off after thermperature 100°C is exceeded, for SET150-N and SET210-N models after 110°C is exceeded, for SET60-K and SET105-K models after 120°C is exceeded / inbuilt short circuit and overload protection