SIEMENS

# Data sheet for SINAMICS G120 Power Module PM230



## Ordering data

**6SL3223-0DE21-5AA0**

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

## Rated data

### Input

| | |
|---|---|
| **Number of phases** | 3 AC |
| **Line voltage** | 380 ... 480 V ±10 % |
| **Line frequency** | 47 ... 63 Hz |
| **Rated current (LO)** | 4.20 A |
| **Rated current (HO)** | 3.20 A |

### Output

| | |
|---|---|
| **Number of phases** | 3 AC |
| **Rated voltage** | 400 V |
| **Rated power (LO)** | 1.50 kW |
| **Rated power (HO)** | 1.10 kW |
| **Rated current (LO)** | 4.10 A |
| **Rated current (HO)** | 3.10 A |
| **Max. output current** | 6.20 A |
| **Pulse frequency** | 4 kHz |
| **Output frequency for vector control** | 0 ... 200 Hz |
| **Output frequency for V/f control** | 0 ... 550 Hz |

## General tech. specifications

| | |
|---|---|
| **Power factor λ** | 0.90 |
| **Offset factor cos φ** | 0.95 |
| **Efficiency η** | 0.95 |
| **Sound pressure level (1m)** | 62 dB |
| **Power loss** | 0.08 kW |

## Ambient conditions

| | |
|---|---|
| **Cooling** | Internal air cooling |
| **Cooling air requirement** | 0.007 m³/s |
| **Installation altitude** | 1000 m |

### Ambient temperature

| | |
|---|---|
| **Operation LO** | 0 ... 40 °C (32 ... 104 °F) |
| **Operation HO** | 0 ... 50 °C (32 ... 122 °F) |
| **Transport** | -40 ... 70 °C (-40 ... 158 °F) |
| **Storage** | -25 ... 55 °C (-13 ... 131 °F) |

### Relative humidity

| | |
|---|---|
| **Max. operation** | 95 % RH, condensation not permitted |

## Overload capability

**Low Overload (LO)**

1.1 × output current rating (i.e., 110 % overload) for 57 s with a cycle time of 300 s 1.5 × output current rating (i.e., 150 % overload) for 3 s with a cycle time of 300 s

**High Overload (HO)**

1.5 × output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 × output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

SIEMENS

# Data sheet for SINAMICS G120 Power Module PM230

**Ordering data** **6SL3223-0DE21-5AA0**



## Mechanical data

| | |
|---|---|
| **Degree of protection** | IP55/UL Type 12 |
| **Size** | FSA |
| **Net weight** | 4.30 kg |
| **Width** | 154.0 mm |
| **Height** | 460.0 mm |
| **Depth** | 249.0 mm |

## Connections

### Line side

| | |
|---|---|
| **Version** | Plug-in screw-type terminals |
| **Conductor cross-section** | 1.00 ... 2.50 mm² |

### Motor end

| | |
|---|---|
| **Version** | Plug-in screw-type terminals |
| **Conductor cross-section** | 1.00 ... 2.50 mm² |

### Max. motor cable length

| | |
|---|---|
| **Shielded** | 25 m |
| **Unshielded** | 100 m |

## Standards

| | |
|---|---|
| **Compliance with standards** | UL, CE, C-Tick |
| **CE marking** | According to low-voltage directive 2006/95/EC |