
High-Current Carrying Capacity


The **short-time withstand capacity** is defined in standards such as IEC/EN 60947-7-1 for through rail-mounted terminal blocks. It is a **current-carrying capacity of 120A per mm² nominal diameter** for the duration of 1 second. **In the case of a 4/0 AWG (95 mm²)** WAGO 285 Series **High-Current Terminal Block, this translates to 11,400A!**

Ground conductor terminal blocks are submitted to the "120A per mm²" test for 3x one second.

The pass criterion for the test is the voltage drop (limit value and constancy). CAGE CLAMP® and CAGE CLAMP®S connections passed this test without damage or reduced functionality.




Test arrangement: "Short-Time Current Withstand Test"




Unrealistic test of a CAGE CLAMP®-equipped,12 AWG (4mm²) rail-mounted terminal block: **Increase of current without time limit.** In such an extreme test – normally, fuse devices would have interrupted the current – **the electrical connection is undamaged.**

TOPJOB®S Rail-Mounted Terminal Blocks 2000, 2001, 2002, 2004, 2006, 2010 and 2016 Series

Conductor termination/removal




Push-in termination: Solid conductors with cross sections from either one size above, or up to two sizes below, the rated cross section can be pushed in directly – without tools.



With screwdriver: The operation of the clamp remains the same for unprepared fine-stranded conductors or small cross sections that don't allow push-in termination.


Like the original CAGE CLAMP®, a screwdriver is used for conductor removal with CAGE CLAMP®S.

Testing




Testing of TOPJOB®S rail-mounted terminal blocks using test plug adapter or testing tap

Commoning




Twin integrated, spring-loaded jumper system allows use of comb-style jumper bars, test plugs and connectors.

Jumper bars rated at 800V (ex works).



Commoning




Jumper contacts that are not required can be broken off and removed, the upper-side of the jumper can then be marked accordingly. Applies to 2001, 2002 and 2004 Series.

Marking




A thermal transfer printer and WAGO "smartDESIGNER" software generate the marking.



TOPJOB®S offers three marking positions for WMB markers, miniature WSB markers or a full-length marking strip.

Pre-assembled connectors



Pre-assembled connectors with CAGE CLAMP®S connection provide an additional connection option.

CAGE CLAMP®S clamps the following copper conductors:



solid | stranded | fine-stranded | tip bonded | with ferrule | with pin terminal

Strip length, see packaging or instructions.

TOPJOB®S
Rail-Mounted Terminal Blocks 1.0 (1.5) mm²
2000 Series


CAGE CLAMP®S


0.14 - 1.0 (1.5) mm² ❶	AWG 24 - 16
800 V/6 kV/3	600 V, 10 A
I_N 13.5 A (18 A)	600 V, 10 A


Terminal block width 3.5 mm / 0.138 in
9 - 11 mm / 0.39 in
❷ Approvals


❶ Conductor sizes: 0.14 – 1.5 mm² "s + f-st";
Push-in conductor sizes: 0.5 – 1.5 mm² "s" and 0.5 – 1 mm² "insulated ferrule, 12 mm"











Color	Item No.	Pack. Unit
2-conductor through terminal block		
gray	**2000-1201**	100
blue	**2000-1204**	100
orange	**2000-1202**	100
red	**2000-1203**	100
black	**2000-1205**	100
yellow	**2000-1206**	100
2-conductor ground terminal block		
green-yellow	**2000-1207**	100

Color	Item No.	Pack. Unit
3-conductor through terminal block		
gray	**2000-1301**	100
blue	**2000-1304**	100
orange	**2000-1302**	100
red	**2000-1303**	100
black	**2000-1305**	100
yellow	**2000-1306**	100
3-conductor ground terminal block		
green-yellow	**2000-1307**	100

Color	Item No.	Pack. Unit
4-conductor through terminal block		
gray	**2000-1401**	100
blue	**2000-1404**	100
orange	**2000-1402**	100
red	**2000-1403**	100
black	**2000-1405**	100
yellow	**2000-1406**	100
4-conductor ground terminal block		
green-yellow	**2000-1407**	100

Item-Specific Accessories

End and intermediate plate, 0.7 mm thick



orange **2000-1292** 100 (4x25)
gray **2000-1291** 100 (4x25)

End and intermediate plate, 0.7 mm thick



orange **2000-1392** 100 (4x25)
gray **2000-1391** 100 (4x25)

End and intermediate plate, 0.7 mm thick



orange **2000-1492** 100 (4x25)
gray **2000-1491** 100 (4x25)

2000 Series Accessories

Appropriate marking systems: **WMB/Marking Strips**

Push-in type jumper bar, insulated, I_N 14 A, light gray



2-way **2000-402** 200 (8x25)
3-way **2000-403** 200 (8x25)
4-way **2000-404** 200 (8x25)
5-way **2000-405** 100 (4x25)
: :
10-way **2000-410** 100 (4x25)

Push-in type jumper bar, insulated, I_N 14 A, light gray



1 - 3 **2000-433** 200 (8x25)
1 - 4 **2000-434** 200 (8x25)
1 - 5 **2000-435** 100 (4x25)
: :
1 - 10 **2000-440** 100 (4x25)

Star point jumper, insulated,



I_N = I_N terminal block, light gray
1–3–5 **2000-405/011-000**
100 (4x25)

Protective warning marker, with high-voltage symbol,
for 5 terminal blocks



yellow **2000-115** 100 (4x25)

WMB Multi marking system,

10 strips with 10 markers per card
for 3.5 mm terminal block width,
plain **793-3501** 50 (10x5)

Marking strips, plain



11 mm wide,
50m roll
white **2009-110** 1

Operating tool with partially insulated shaft,



type 1, (2.5 x 0.4) mm blade
210-719 1

Suitable for Ex i applications

Test plug adapter, for test plug 4 mm Ø



gray **2009-174** 100 (4x25)

Insulated ferrules, extra long,
for TOPJOB®S terminal blocks
see page 195



Testing tap, for max. 2.5 mm²/AWG 14



gray **2009-182** 100 (4x25)

❷ Approvals are available online at: www.wago.com.

For technical explanations and abbreviations, see technical section.

WAGO®