Item no.: 780-601

Product description: 2-CONDUCTOR THROUGH TERMINAL BLOCK



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Product group	17 (TOP JOB INSTALLATION TERMINAL BLOCKS)
Cross section [mm²]	0.08 - 2.5 mm²
Cross section [AWG]	28 - 12 AWG
Connection method	CAGE CLAMP® CONNECTION
Measured voltage EN	1000 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	7.808 g
Color	gray
Wiring type	Front-entry
No. of connection Points	2
No. of potentials	1
Height	43.5 mm
Height	1.71 in
Width	5 mm
Width	0.197 in
Depth	77 mm
Depth	3.03 in

Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
Mounting	TS 35

Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
780-601	ABS	05-HG476175/3-PDA	1000	24	2,5
780-601	BV	07436/Co	1000	24	2,5
780-601	CCA	NL5855	800	24	2,5
780-601	DNV	E-10423	1000	24	2,5
780-601	GL	17295-00HH	800	24	2,5
780-601	KEMA	2082859.08	800	24	2,5
780-601	LR	91/20112(E6)	1000	24	2,5
780-601	NEMKO	P94100800	800		2,5
780-601	RMR	11130002	1000	24	2,5
780-601	UR	E45172	600	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected