SIEMENS

Data sheet 8WD4420-0FA



Figure similar

SIGNALLING COLUMN BUZZER ELEMENT
CONTINUOUS SOUND OR PULSED ADJUSTABLE,
24V AC/DC

General technical data:		
product brand name		SIRIUS
Type of voltage of the operating voltage		AC/DC
Operating voltage		
• 1 for DC Rated value	V	24
• 1 with AC at 50 Hz Rated value	V	24
• 1 with AC at 60 Hz Rated value	V	24
Type of acoustic signal		continuous tone / pulse tone
Loudness level	dB	85
Equipment marking acc. to DIN EN 61346-2		P

Mechanical data:		
Outer diameter of the signal column element	mm	70

Ambient conditions:		
Ambient temperature during operation	°C	-20 ... +50
Protection class IP		IP65
Product function adjustable acoustic signal		Yes
Height	mm	72
Width	mm	70

Certificates/ approvals:

Changes preserved
© Copyright Siemens AG

General Product Approval		EMC	Declaration of Conformity	Shipping Approval	other
UL	EAC	C-TICK	EG-Konf.	DNV	Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)
http://www.siemens.com/industrymall

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD44200FA

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/8WD44200FA

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD44200FA&lang=en





\W8 4444:
\W8 8333: 8WD44..-..._ALL

last modified: 01.04.2015

Changes preserved
© Copyright Siemens AG