SIEMENS

Data sheet 8WD4400-1AD



SIGNALLING COLUMN STEADY LIGHT YELLOW, 12...240V AC/DC

General technical data:		
product brand name		SIRIUS
Product component Light source		No
Design of the optical signal		continous light
Type of voltage of the operating voltage		AC/DC
Operating voltage		
• for DC Rated value	V	230 ... 12
• with AC at 50 Hz Rated value	V	12 ... 230
• with AC at 60 Hz Rated value	V	12 ... 230
Equipment marking acc. to DIN EN 61346-2		P
Mechanical data:		
Outer diameter of the signal column element	mm	70
Lamp:		
Type of light source		filament lamp / LED
Ambient conditions:		
Ambient temperature during operation	°C	-20 ... +60
Protection class IP		IP65
Height	mm	65.5
Width	mm	70
Certificates/ approvals:		

Changes preserved
© Copyright Siemens AG

General Product Approval	EMC	Declaration of Conformity	Shipping Approval
UL EAC	C-TICK	EG-Konf.	DNV

Further information


Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/industrial-controls/catalogs


Industry Mall (Online ordering system)
http://www.siemens.com/industrymall

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD44001AD

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/8WD44001AD

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD44001AD&lang=en





\W8 4444:
\W8 8333: 8WD44..-..._ALL

last modified: 05.05.2015

Changes preserved
© Copyright Siemens AG