SIEMENS

## Data sheet 3TH42 44-0BB4




CONTACTOR RELAY 44E EN 50 011 4NO+4NC, SCREW TERMINALS DC OPERATION DC SOLENOID SYSTEM DC 24V

| General technical data: | |
|---|---|
| **Size of contactor** | 0 |
| **Ambient temperature during operation** | -25 ... +55 °C |
| **Protection class IP on the front** | IP20 |
| **Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750** | K |
| **Equipment marking acc. to DIN EN 61346-2** | K |
| **Equipment marking acc. to DIN EN 81346-2** | K |

| Control circuit/ Control: | |
|---|---|
| **Type of voltage of the control supply voltage** | DC |
| **Control supply voltage** | |
| • for DC | |
| — Rated value | 24 V |

| Auxiliary circuit: | |
|---|---|
| **Operating current at AC-15** | |
| • at 230 V Rated value | 10 A |
| • at 400 V Rated value | 6 A |
| **Identification number and letter for switching elements** | 44 E |
| **Number of NC contacts for auxiliary contacts** | 4 |
| • lagging switching | 0 |
| • delayed switching | 0 |
| • make-before-break switching | 0 |
| **Number of NO contacts for auxiliary contacts** | |


Changes preserved
© Copyright Siemens AG

| | |
|---|---|
| • delayed switching | 0 |
| • leading contact | 0 |
| • make-before-break switching | 0 |
| **Number of CO contacts for auxiliary contacts** | 0 |

## Connections/ Terminals:

| | |
|---|---|
| **Type of electrical connection for auxiliary and control current circuit** | screw-type terminals |

## Mechanical data:

| | |
|---|---|
| **Mounting type** | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022 |
| **Width** | 45 mm |
| **Height** | 78 mm |
| **Depth** | 135 mm |

## Certificates/ approvals:

| General Product Approval | | | | Test Certificates | |
|---|---|---|---|---|---|
| CCC | CSA | UL | EAC | Type Test Certificates/Test Report | Special Test Certificate |

| Test Certificates | Shipping Approval | | | | other |
|---|---|---|---|---|---|
| other | DNV | GL | LRS | RMRS | Declaration of Conformity |

| other | |
|---|---|
| other | Environmental Confirmations |

## Safety related data:

| | |
|---|---|
| **Protection against electrical shock** | finger-safe |
| B10 value with high demand rate acc. to SN 31920 | 1 000 000 |
| • Note | With 0.3 x Ie |
| **T1 value for proof test interval or service life acc. to IEC 61508** | 20 y |

## Further information


Changes preserved
© Copyright Siemens AG

**Information- and Downloadcenter (Catalogs, Brochures,…)**
http://www.siemens.com/industrial-controls/catalogs

**Industry Mall (Online ordering system)**
http://www.siemens.com/industrymall

**Cax online generator**
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TH42440BB4

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/3TH42440BB4

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TH42440BB4&lang=en




**last modified:** 23.04.2015


Changes preserved
© Copyright Siemens AG