	Number of poles	For use with	Terminal capacity Connection	Terminal capacity[1] mm²	AWG/kcmil	**Part no. suffix** Article no. for ordering with basic device	**Price** See price list
Control cable terminals							
	3 and 4 pole	NZM2(-4), PN2(-4), N(S)2(-4)	Screw terminals	1 x 0.75 - 2.5 2 x 0.75 - 1.5	1 x 18 - 14 2 x 18 - 16	–	
	3 and 4 pole	NZM2(-4), PN2(-4), N(S)2(-4)	Box terminal			–	
Cable lug cover							
	3 pole	NZM2, PN2, NS2	Copper cable lugs Aluminium cable lugs	1 x 10-185 2 x 4-70 1 x 10-50 2 x 10-50	–	–	
	4 pole	NZM2-4, PN2-4, N2-4			–	–	
Cover							
	3 pole	NZM2, PN2, NS2	–	–	–	–	
	4 pole	NZM2-4, PN2-4, N2-4	–	–	–	–	
Phase isolators							
	3 pole	NZM2, PN2, N(S)2	–	–	–	–	
	4 pole	NZM2-4, PN2-4, N2-4	–	–	–	–	
Terminal covers, knockout							
	3 pole	NZM2, PN2, N(S)2	–	–	–	**+NZM2-XKSFA0** 108269	
			–	–	–	**+NZM2-XKSFAU** 108270	
	4 pole	NZM2-4, PN2-4, N2-4	–	–	–	**+NZM2-4-XKSFA0** 108271	
			–	–	–	**+NZM2-4-XKSFAU** 108272	
IP2X protection against contact with finger							
For box terminal							
	3 pole	NZM2, PN2, N(S)2	–	–	–	–	
	4 pole	NZM2-4, PN2-4, N2-4	–	–	–	–	
For covers NZM2(-4)-XKSA or NZM2(-4) or NZM2…(C)NA and N(S)2…NA							
	3 pole	NZM2, PN2, N(S)2	–	–	–	–	
	4 pole	NZM2-4, PN2-4, N2-4	–	–	–	–	
Copper cable lug							
Not UL/CSA approved When using cable lugs without NZM3(-4)-XKSA cover, they must be insulated.							
	3 and 4 pole	NZM2(-4), PN2(-4), N2(-4)	–	150 mm²	–	–	
			–	120 mm²	–	–	
			–	95 mm²	–	–	
			–	185 mm²	–	–	

Part no. Article no. when ordered separately	**Price** See price list	Std. pack	**Notes**	**Information relevant for export to North America**
NZM2-XSTS 260156		1 set	Contains parts for two terminal locations located at top or bottom for 3 or 4 pole switches. Included as standard with tunnel terminal. Degree of protection IP1X NZM-XSTK cannot be combined with NZM1(-4)-XIPK IP2X protection against contact with a finger. Height or thickness of connections: 2 mm	Product Standards UL489; CSA-C22.2 No. 5-09; IEC60947, CE marking UL File No. E140305 UL CCN DIHS CSA File No. 022086 CSA Class No. 1437-01 NA Certification UL Listed, CSA certified Suitable for Refer to main component information
NZM-XSTK 266739		1 set		
NZM2-XKSAE 119868		1 set	Contains parts for a terminal located at top or bottom for 3 or 4 pole switches. Contact protection where cable lugs are used on screw terminals. When using insulated conductor material, degree of protection IP2X	UL/CSA certification not required
NZM2-4-XKSAE 119870		1 set		–
NZM2-XKSA 260038		1 off	Contains parts for a terminal located at top or bottom for 3 or 4 pole switches. Contact protection where cable lugs, bars or tunnel terminals are used. When using insulated conductor material, degree of protection IP1X	Product Standards UL489; CSA-C22.2 No. 5-09; IEC60947, CE marking UL File No. E31593 UL CCN DIHS CSA File No. 22086 CSA Class No. 1432-01 NA Certification UL Listed, CSA certified Suitable for Refer to main component information
NZM2-4-XKSA 266770		1 off		–
NZM2-XKP 119864		1 set	Contains parts, including insulating plate for mounting plate, for a terminal located at top or bottom for 3 or 4 pole circuit-breakers. Can not be combined with connection on rear NZM2(-4)-XKR. Insulation protection up to a rated operating voltage U_e of 415 V AC when minimum distances are not maintained.	UL/CSA certification not required
NZM2-4-XKP 119865		1 set		–
NZM2-XKSFA 104640		1 off	Contains parts for a terminal located at top or bottom for 3 or 4 pole switches. Enhanced contact protection (simplified finger protection). O = for fitting at the top U = for fitting at the bottom	UL/CSA certification not required
		1 off		
NZM2-4-XKSFA 104641				
NZM2-XIPK 266773		1 set	Contains parts for a terminal located at top or bottom for 3 or 4 pole switches. Enhanced contact protection to IP2X. Protection on grasping terminal chamber when connecting cables in box terminals. With two conductors maximum cross-section 25 mm² or AWG4. Can not be combined with control cable terminal NZM-XSTK.	UL/CSA certification not required
NZM2-4-XIPK 266774		1 set		–
NZM2-XIPA 266777		1 set	Contains parts for a terminal located at top or bottom for 3 or 4 pole switches. Enhanced contact protection to IP2X. When fitting to NZM2-..-(C)NA or NZM...-NA: With 2 conductors maximum cross-section 25 mm² or AWG4.	UL/CSA certification not required
NZM2-4-XIPA 266778		1 set		–
KS150-NZM7 059777		3 off	Contains a cable lug for 3 or 4 pole switch. Special cable lug, narrow style	–
KS120-NZM7 059776				
KS95-NZM7 059775				
NZM2-XKS185 260032				