❶ Conductor sizes: 0.25 mm² – 4 mm² "s + f-st"; Push-in conductor sizes: 0.75 mm² – 4 mm² "s" and 0.75 mm² – 2.5 mm² "insulated ferrule, 12 mm"

❷ 800 V = rated voltage
8 kV = rated surge voltage
3 = pollution degree
(also see Section 14)

❸ Strip length, see packaging or instructions.

❹ Suitable for Ex i applications

❺ See application notes for:
Colored push-in type jumper bars, page 139
Vertical jumper, page 142



Double-deck terminal block assembly

2002 Series Accessories

Appropriate marking systems: WMB/Marking strips/WMB Inline (see Section 13)

End and intermediate plate, 0.8 mm thick



orange	**2002-2492**	100	(4x25)
gray	**2002-2491**	100	(4x25)

Double-deck marker carrier,



pivoting			
gray	**2002-121**	50	(2x25)

Insulation stop,



5 pcs/strip,			
0.25 - 0.5 mm²			
light gray	**2002-171**	200	(8x25)

Insulation stop,



5 pcs/strip,			
0.75 - 1 mm²			
dark gray	**2002-172**	200	(8x25)

Push-in type jumper bar, insulated, ❺



I_N 25 A,			
light gray			
2-way	**2002-402**	200	(8x25)
3-way	**2002-403**	200	(8x25)
4-way	**2002-404**	200	(8x25)
5-way	**2002-405**	100	(4x25)
6-way	**2002-406**	100	(4x25)
7-way	**2002-407**	100	(4x25)
8-way	**2002-408**	100	(4x25)
9-way	**2002-409**	100	(4x25)
10-way	**2002-410**	100	(4x25)

Push-in type jumper bar, insulated,



I_N 25 A,			
light gray			
from 1 to 3	**2002-433**	200	(8x25)
from 1 to 4	**2002-434**	200	(8x25)
from 1 to 5	**2002-435**	100	(4x25)
from 1 to 6	**2002-436**	100	(4x25)
from 1 to 7	**2002-437**	100	(4x25)
from 1 to 8	**2002-438**	100	(4x25)
from 1 to 9	**2002-439**	100	(4x25)
from 1 to 10	**2002-440**	100	(4x25)

Double-deck vertical jumper, insulated, ❺

I_N 24 A			
light gray	**2002-492**	100	(4x25)

Protective warning marker,



with high-voltage symbol, black,			
for 5 terminal blocks			
yellow	**2002-115**	100	(4x25)

Test plug adapter,



for test plug 4 mm Ø			
gray	**2009-174**	100	(4x25)

Banana plug,



for socket 4 mm Ø,			
color mixed			
	215-111		50

Testing tap,



for max. 2.5 mm²			
gray	**2009-182**	100	(4x25)

Test plug,



with 500 mm cable,			
2 mm Ø			
red	**210-136**		50

Test plug,



with 500 mm cable,			
2.3 mm Ø			
yellow	**210-137**		50

WMB Multi marking system,

10 strips with 10 markers per card,			
stretchable 5 - 5.2 mm			
plain	**793-5501**		5

WMB Multi marking system, plain,



10 strips with 10 markers per card,			
stretchable 5 - 5.2 mm			
yellow	**793-5501/000-002**		
red	**793-5501/000-005**		
blue	**793-5501/000-006**		
gray	**793-5501/000-007**		
orange	**793-5501/000-012**		
light green	**793-5501/000-017**		
green	**793-5501/000-023**		
violet	**793-5501/000-024**		
			5

WMB Inline, plain,



stretchable 5 - 5.2 mm,			
1,500 WMB markers, 5 mm, on roll			
white	**2009-115**		1

Marking strip, plain,



11 mm wide,			
50 m roll			
white	**2009-110**		1

TOPJOB®S group marker carrier,



snap-on type for jumper slot,			
5 mm wide			
gray	**2009-191**	50	(2x25)

TOPJOB®S
Triple-Deck Terminal Blocks 2.5 (4) mm²
2002 Series

0.25 - 2.5 (4) mm² ❶ | AWG 22 - 12 500 V/6 kV/3 ❷ | 300 V, 20 A I_N 24 A (28 A) | 600 V, 20 A Terminal block width 5.2 mm / 0.205 in 10 - 12 mm / 0.43 in ❸	0.25 - 2.5 (4) mm² ❶ | AWG 22 - 12 500 V/6 kV/3 ❷ I_N 24 A (28 A) | 600 V, 20 A Terminal block width 5.2 mm / 0.205 in 10 - 12 mm / 0.43 in ❸	0.25 - 2.5 (4) mm² ❶ | AWG 22 - 12 500 V/6 kV/3 ❷ I_N 24 A (28 A) Terminal block width 5.2 mm / 0.205 in 10 - 12 mm / 0.43 in ❸







	Item No.	Pack. Unit
Through/through/through terminal block,		
with marker carrier,		
gray housing		
L/L/L	**2002-3231** ❺	50
L/L/N	**2002-3233** ❺	50
Through/through/through terminal block,		
without marker carrier,		
gray housing		
L/L/L	**2002-3201** ❺	50
L/L/N	**2002-3203** ❺	50
Other terminal blocks with the same profile:		
Diode	**2002-3211/1000-410** Page 126	
LED	**2002-3221/1000-434** Page 126	

	Item No.	Pack. Unit
Through/through/through terminal block,		
with marker carrier,		
blue housing		
N/N/N	**2002-3234** ❹ ❺	50
Through/through/through terminal block,		
without marker carrier,		
blue housing		
N/N/N	**2002-3204** ❹ ❺	50

	Item No.	Pack. Unit
Ground conductor/through/through terminal block,		
with marker carrier,		
gray housing		
PE/N/L	**2002-3247** ❺	50
PE/L/L	**2002-3257** ❺	50
Ground conductor/through/through terminal block,		
without marker carrier,		
gray housing		
PE/N/L	**2002-3217** ❺	50
PE/L/L	**2002-3227** ❺	50







	Item No.	Pack. Unit
6-conductor through terminal block,		
with marker carrier, internal commoning, conductor entry position colored in violet,		
gray housing		
L	**2002-3238** ❺	50
6-conductor through terminal block,		
without marker carrier, internal commoning, conductor entry position colored in violet,		
gray housing		
L	**2002-3208** ❺	50

	Item No.	Pack. Unit
6-conductor through terminal block,		
with marker carrier, internal commoning, conductor entry position colored in violet,		
blue housing		
N	**2002-3239** ❹ ❺	50
6-conductor through terminal block,		
without marker carrier, internal commoning, conductor entry position colored in violet,		
blue housing		
N	**2002-3209** ❹ ❺	50

	Item No.	Pack. Unit
6-conductor ground terminal block,		
with marker carrier, internal commoning,		
green-yellow housing		
PE	**2002-3237** ❺	50
6-conductor ground terminal block,		
without marker carrier, internal commoning,		
green-yellow housing		
PE	**2002-3207** ❺	50

For list of approvals and user guide, see pages 634 to 637.

0.25 - 2.5 (4) mm² ❶	AWG 22 - 12
500 V/6 kV/3 ❷	300 V, 20 A
I_N 24 A (28 A)	600 V, 20 A

Terminal block width 5.2 mm / 0.205 in
10 - 12 mm / 0.43 in ❸



❶ Conductor sizes: 0.25 mm² – 4 mm² "s + f-st"; Push-in conductor sizes: 0.75 mm² – 4 mm² "s" and 0.75 mm² – 2.5 mm² "insulated ferrules, 12 mm"

❷ 500 V = rated voltage
6 kV = rated surge voltage
3 = pollution degree
(also see Section 14)

❸ Strip length, see packaging or instructions.

❹ Suitable for Ex i applications

❺ Suitable for Ex e II applications
440 V, 19 A
Jumper 17 A
(also see Section 14)

❻ See application notes for:
Colored push-in type jumper bars, page 139
Vertical jumper, page 142

	Item No.	Pack. Unit
Shield/through/through terminal block,		
with marker carrier,		
gray housing		
Shield/N/L	**2002-3248**	50
Shield/L/L	**2002-3258**	50
Shield/through/through terminal block,		
without marker carrier,		
gray housing		
Shield/N/L	**2002-3218**	50
Shield/L/L	**2002-3228**	50



Triple-deck terminal block assembly



Combination of multilevel terminal blocks

2002 Series Accessories

Appropriate marking systems: WMB/Marking strips/WMB Inline (see Section 13)

End and intermediate plate, 0.8 mm thick			
	orange	**2002-3292**	100 (4x25)
	gray	**2002-3291**	100 (4x25)
Triple-deck marker carrier,			
	pivoting		
	gray	**2002-131**	50 (2x25)
Insulation stop,			
	5 pcs/strip,		
	0.25 - 0.5 mm²		
	light gray	**2002-171**	200 (8x25)
Insulation stop,			
	5 pcs/strip,		
	0.75 - 1 mm²		
	dark gray	**2002-172**	200 (8x25)
Push-in type jumper bar, insulated,			
❻ 	I_N 25 A,		
	light gray		
	2-way	**2002-402**	200 (8x25)
	3-way	**2002-403**	200 (8x25)
	4-way	**2002-404**	200 (8x25)
	5-way	**2002-405**	100 (4x25)
	6-way	**2002-406**	100 (4x25)
	7-way	**2002-407**	100 (4x25)
	8-way	**2002-408**	100 (4x25)
	9-way	**2002-409**	100 (4x25)
	10-way	**2002-410**	100 (4x25)
Push-in type jumper bar, insulated,			
	I_N 25 A,		
	light gray		
	from 1 to 3	**2002-433**	200 (8x25)
	from 1 to 4	**2002-434**	200 (8x25)
	from 1 to 5	**2002-435**	100 (4x25)
	from 1 to 6	**2002-436**	100 (4x25)
	from 1 to 7	**2002-437**	100 (4x25)
	from 1 to 8	**2002-438**	100 (4x25)
	from 1 to 9	**2002-439**	100 (4x25)
	from 1 to 10	**2002-440**	100 (4x25)
Triple-deck vertical jumper, insulated,			
❻	I_N 24 A		
	light gray	**2002-493**	100 (4x25)
Double-deck vertical jumper, insulated,			
❻	I_N 24 A		
	light gray	**2002-492**	100 (4x25)

TOPJOB®S
Quadruple-Deck, Rail-Mounted Terminal Blocks or Rail-Mounted Terminal Blocks for Wiring of Electric Motors, 2002 Series

0.25 - 2.5 (4) mm² ❶ | AWG 22 - 12 800 V/8 kV/3 ❷ I_N 20 A (25 A) Terminal block width 5.2 mm / 0.205 in 10 - 12 mm / 0.43 in ❸	0.25 - 2.5 (4) mm² ❶ | AWG 22 - 12 800 V/8 kV/3 ❷ I_N 20 A (25 A) Terminal block width 5.2 mm / 0.205 in 10 - 12 mm / 0.43 in ❸	0.25 - 2.5 (4) mm² ❶ | AWG 22 - 12 800 V/8 kV/3 ❷ I_N 20 A (25 A) Terminal block width 5.2 mm / 0.205 in 10 - 12 mm / 0.43 in ❸







Item No.	Pack. Unit
Quadruple-deck, rail-mounted terminal block or Rail-mounted terminal block for wiring of electric motors, without marker carrier, gray	
◯ L1 - L2 - L3 - PE **2002-4127**	25
Quadruple-deck, rail-mounted terminal block or Rail-mounted terminal block for wiring of electric motors, with marker carrier, gray	
◯ L1 - L2 - L3 - PE **2002-4157**	25

Item No.	Pack. Unit
Quadruple-deck, rail-mounted terminal block or Rail-mounted terminal block for wiring of electric motors, without marker carrier, gray	
◯ L1 - L2 **2002-4111**	25
Quadruple-deck, rail-mounted terminal block or Rail-mounted terminal block for wiring of electric motors, with marker carrier, gray	
◯ L1 - L2 **2002-4141**	25

Item No.	Pack. Unit
Quadruple-deck, rail-mounted terminal block or Rail-mounted terminal block for wiring of electric motors, without marker carrier, gray	
◯ L1 - L2 - L3 **2002-4101**	25
Quadruple-deck, rail-mounted terminal block or Rail-mounted terminal block for wiring of electric motors, with marker carrier, gray	
◯ L1 - L2 - L3 **2002-4131**	25

2002 Series Accessories

Appropriate marking systems: WMB/Marking strips/WMB Inline
(see Section 13)

End and intermediate plate, 1 mm thick			
orange	**2002-4192**	100 (4x25)	
gray	**2002-4191**	100 (4x25)	
Insulation stop,			
5 pcs/strip, 0.25 - 0.5 mm²			
light gray	**2002-171**	200 (8x25)	
Insulation stop,			
5 pcs/strip, 0.75 - 1 mm²			
dark gray	**2002-172**	200 (8x25)	
Push-in type jumper bar, insulated, ❹			
I_N 25 A, light gray			
2-way	**2002-402**	200 (8x25)	
3-way	**2002-403**	200 (8x25)	
4-way	**2002-404**	200 (8x25)	
5-way	**2002-405**	100 (4x25)	
6-way	**2002-406**	100 (4x25)	
7-way	**2002-407**	100 (4x25)	
8-way	**2002-408**	100 (4x25)	
9-way	**2002-409**	100 (4x25)	
10-way	**2002-410**	100 (4x25)	
Star point jumper, insulated, ❹			
I_N = I_N terminal block, light gray			
1-3-5	**2002-405/011-000**		
		100 (4x25)	
Delta jumper, insulated, ❹			
I_N = I_N terminal block, light gray			
1-2 3-4 5-6	**2002-406/020-000**		
		100 (4x25)	

Protective warning marker,			
with high-voltage symbol, black, for 5 terminal blocks			
yellow	**2002-115**	100 (4x25)	
Lockout cap,			
for conductor entry hole and operating slot			
orange	**2002-192**	25	
gray	**2002-191**	25	
blue	**2002-194**	25	
Push-in type jumper bar, insulated,			
I_N 25 A, light gray			
from 1 to 3	**2002-433**	200 (8x25)	
from 1 to 4	**2002-434**	200 (8x25)	
from 1 to 5	**2002-435**	100 (4x25)	
from 1 to 6	**2002-436**	100 (4x25)	
from 1 to 7	**2002-437**	100 (4x25)	
from 1 to 8	**2002-438**	100 (4x25)	
from 1 to 9	**2002-439**	100 (4x25)	
from 1 to 10	**2002-440**	100 (4x25)	
Adjacent jumper for continuous commoning, ❹			
insulated, I_N 25 A, light gray			
2-way	**2002-400**	100 (4x25)	
Triple-deck marker carrier,			
pivoting			
gray	**2002-131**	50 (2x25)	

Staggered jumper, ❹			
insulated, I_N 25 A, light gray			
2-way	**2002-472**	100 (4x25)	
3-way	**2002-473**	100 (4x25)	
4-way	**2002-474**	100 (4x25)	
5-way	**2002-475**	50 (2x25)	
6-way	**2002-476**	50 (2x25)	
7-way	**2002-477**	50 (2x25)	
8-way	**2002-478**	50 (2x25)	
9-way	**2002-479**	50 (2x25)	
10-way	**2002-480**	50 (2x25)	
11-way	**2002-481**	50 (2x25)	
12-way	**2002-482**	50 (2x25)	
Push-in type wire jumper, ❹			
insulated, I_N 16 A, wire size 1.5 mm²			
L = 60 mm	**2009-412**	100 (10x10)	
L = 110 mm	**2009-414**	100 (10x10)	
L = 250 mm	**2009-416**	100 (10x10)	
WMB Inline, plain,			
stretchable 5 - 5.2 mm, 1,500 WMB markers, 5 mm, on roll			
white	**2009-115**	1	
Marking strip, plain,			
11 mm wide, 50 m roll			
white	**2009-110**	1	

For list of approvals and user guide, see pages 634 to 637.



In addition to rail-mounted terminal blocks for electric motor wiring, new versions are now available.

- Terminal block **without** ground contact and only 2 potentials.

Especially for additional functions such as engine brakes or temperature probes. Having the same shape, this type can be put next to the appropriate terminal block for electric motor wiring without using intermediate plates.
That makes the rail assembly clearer and wiring is easier. This also prevents wiring errors as no conductor entry is unused.

- Terminal block **without** ground contact and with only 3 potentials.

Clearly designated clamping units is the primary advantage to this terminal block design. When using devices with protective insulation for example, there are no open ground clamping units that could create confusion.

❶ Conductor sizes: 0.25 mm² – 4 mm² "s + f-st";
Push-in conductor sizes: 0.75 mm² – 4 mm² "s" and 0.75 mm² – 2.5 mm² "insulated ferrule, 12 mm"

❷ 800 V = rated voltage
8 kV = rated surge voltage
3 = pollution degree
(see Section 14)

❸ Strip length, see packaging or instructions.

❹ See application notes for:
Colored push-in type jumper bars, page 139
Staggered jumper, page 141
Delta jumper, page 140
Star point jumper, page 140
Adjacent jumper for continuous commoning, page 139
Push-in type wire jumper, page 140
TOPJOB®S connector, page 134
TOPJOB®S L-type test plug module, page 136
Marker carrier, page 145



Testing with test plug 2 mm Ø.



Lockout cap for conductor entry hole and operating slot
Locking out conductor entry holes and operating slots to create spacer housings for rail-mounted terminal blocks for electric motor wiring.



Compact design:
3 phases and ground conductor in one terminal block.



Marking clamping units with WMB Multi marking system (see Section 13).
Group marking with marking strips.

– Handling –
Multilevel Installation Terminal Blocks, N-Disconnect Slide Link and Busbar Carrier



TOPJOB®S: Terminal blocks for every application.

- Push-in connection of solid conductors in small distribution boxes saves time and money.
- Operating errors can be prevented as all TOPJOB®S terminal blocks for building installation are equipped with push-in connection technology.
- Terminal blocks for building installation expand circuit design possibilities.
- The use of standard accessories reduces order-processing and stock-holding costs.
- Accessories, shared with all terminal blocks, enhance safety by reducing the amount of components and install techniques required.
- The position of the busbars is the same, making the new installation terminal blocks compatible with standard TOPJOB® installation terminal blocks.



Conductor termination
Fine-stranded conductors are inserted using an operating tool.



Conductor termination
Solid conductors are simply pushed in.



Environmentally friendly – TOPJOB®S rail-mounted terminal blocks are 100% lead-free.



Testing with test plug 2 mm Ø



Tool-operated N-disconnect slide link



Each connection point features an individual marker slot for WMB markers. Additionally, the upper marker slot is suitable for marker strips that can be marked manually using a felt-tip pen or automatically via thermal transfer printer.



The busbar carrier integrated into the N-disconnect terminal block of the supply terminal blocks for distribution boxes makes any separate busbar carrier unnecessary, saving space and costs.



Removing the separator plate from the busbar carrier.



Inserting the separator plate to protect the N-busbar against accidental contact.



The optional busbar transparent cover (777-303) protects the busbar against accidental contact and makes it easy to see which terminal blocks are connected to the busbar.



The compact busbar carrier, which is placed every 200 mm/7.87 in, provides additional busbar support for longer assemblies.



Perforations make it possible to fit the carrier to all TOPJOB®S installation terminal blocks using a single part.



Conductor entries on multilevel installation terminal blocks are color marked, providing a clear arrangement of the terminals.

TOPJOB®S
Multilevel Installation Terminal Blocks 2.5 (4) mm²
2003 Series

0.25 - 2.5 (4) mm² ❶ | **AWG 22 - 12** **250 V/4 kV/3; 32 A (32 A) ❷ ❸** **400 V/6 kV/3; 32 A (32 A) ❷ ❹** **Terminal block width 5.2 mm / 0.205 in** **10 - 12 mm / 0.43 in ❺**	**0.25 - 2.5 (4) mm² ❶** | **AWG 22 - 12** **400 V/6 kV/3 ❷** **I_N 32 A** **Terminal block width 5.2 mm / 0.205 in** **10 - 12 mm / 0.43 in ❺**





	Item No.	Pack. Unit
Multilevel installation terminal block,		
with N-disconnect slide link, gray		
◯ NT/L/PE	**2003-7641**	50

	Item No.	Pack. Unit
Multilevel installation terminal block,		
gray		
◯ L/L	**2003-7642**	50
◯ N/L	**2003-7649**	50





	Item No.	Pack. Unit
Multilevel installation terminal block,		
with N-disconnect slide link, gray		
◯ NT/L	**2003-7640**	50
◯ LT/L	**2003-7659**	50
Multilevel installation terminal block,		
gray		
◯ N/L/PE	**2003-7646**	50
◯ L/L/PE	**2003-7645**	50

	Item No.	Pack. Unit
Multilevel installation terminal block,		
gray		
◯ L	**2003-7650**	50
◯ N	**2003-7651**	50

2003 Series Accessories

Appropriate marking systems: WMB/Marking strips
(see Section 13)

Busbar carrier,
not suitable as end stop,
for DIN 35 rail,
1.5 mm thick
blue **2009-304** 100 (4x25)

Busbar carrier,
can replace end bracket, with detachable
separator plate,
for DIN 35 rail,
7.5 mm thick
blue **2009-305** 25

End and intermediate plate, 0.8 mm thick
orange **2003-7692** 100 (4x25)

Cover for N-busbar,
transparent,
1000 mm long
777-303 1

Accessories

Straight busbar, Cu with tin plating,
10 x 3 mm,
1000 mm long
I_N 140 A **210-133** 1

N-supply terminal block, I_N 76 A,
16 mm²,
12 mm wide
blue **2016-7714** 20

green-yellow **2016-7607** 20

Connector,
for N-busbar,
with blue cover,
2.5 - 16 mm²
blue **210-281** 100 (2x50)

Connector,
for N-busbar,
2.5 - 35 mm²
unplated **209-105** 50

Lock-out, snap-on type,
prevents reclosing of slide link
orange **2003-7300** 100 (4x25)

Insulation stop,
5 pcs/strip,
0.25 - 0.5 mm²
light gray **2002-171** 200 (8x25)

Insulation stop,
5 pcs/strip,
0.75 - 1 mm²
dark gray **2002-172** 200 (8x25)

Test plug,
with 500 mm cable,
2 mm Ø
red **210-136** 50

Test plug,
with 500 mm cable,
2.3 mm Ø
yellow **210-137** 50

For list of approvals and user guide, see pages 634 to 637.

Accessories for Multilevel Installation Terminal Blocks

❶ Conductor sizes: 0.25 mm² – 4 mm² "s + f-st"; Push-in conductor sizes: 0.75 mm² – 4 mm² "s" and 0.75 mm² – 2.5 mm² "insulated ferrules, 12 mm"

❷ 250 V/
400 V = rated voltage
4 kV/
6 kV = rated surge voltage
3 = pollution degree
(also see Section 14)

❸ 250 V/4 kV potential-ground

❹ 400 V/6 kV potential-potential

❺ Strip length, see packaging or instructions.

❻ See application notes for:
Colored push-in type jumper bars, page 139
Star point jumper, page 140
Delta jumper, page 140
Staggered jumper, page 141
Adjacent jumper for continuous commoning, page 139
Push-in type wire jumper, page 140
TOPJOB®S connector, page 134
TOPJOB®S L-type test plug module, page 136

Accessories Multilevel Installation Terminal Block

Push-in type jumper bars and staggered jumpers, see 2002 Series

Push-in type jumper bar, insulated,			
❻	I_N 25 A,		
	light gray		
	2-way	**2002-402**	200 (8x25)
	3-way	**2002-403**	200 (8x25)
	4-way	**2002-404**	200 (8x25)
	5-way	**2002-405**	100 (4x25)
	6-way	**2002-406**	100 (4x25)
	7-way	**2002-407**	100 (4x25)
	8-way	**2002-408**	100 (4x25)
	9-way	**2002-409**	100 (4x25)
	10-way	**2002-410**	100 (4x25)
Push-in type jumper bar, insulated,			
	I_N 25 A,		
	light gray		
	from 1 to 3	**2002-433**	200 (8x25)
	from 1 to 4	**2002-434**	200 (8x25)
	from 1 to 5	**2002-435**	100 (4x25)
	from 1 to 6	**2002-436**	100 (4x25)
	from 1 to 7	**2002-437**	100 (4x25)
	from 1 to 8	**2002-438**	100 (4x25)
	from 1 to 9	**2002-439**	100 (4x25)
	from 1 to 10	**2002-440**	100 (4x25)
Push-in type wire jumper,			
❻	insulated,		
	I_N 16 A,		
	wire size 1.5 mm²		
	L = 60 mm	**2009-412**	100 (10x10)
	L = 110 mm	**2009-414**	100 (10x10)
	L = 250 mm	**2009-416**	100 (10x10)
Test plug adapter,			
	for test plug 4 mm Ø		
	gray	**2009-174**	100 (4x25)
Banana plug,			
	for socket 4 mm Ø,		
	color mixed		
		215-111	50
Testing tap,			
	for max. 2.5 mm²		
	gray	**2009-182**	100 (4x25)
Operating tool,			
	3.5 mm and 5.5 mm blade,		
	for TOPJOB®S installation terminal blocks		
		2009-310	50

Staggered jumper,			
❻	insulated,		
	I_N 25 A,		
	light gray		
	2-way	**2002-472**	100 (4x25)
	3-way	**2002-473**	100 (4x25)
	4-way	**2002-474**	100 (4x25)
	5-way	**2002-475**	50 (2x25)
	6-way	**2002-476**	50 (2x25)
	7-way	**2002-477**	50 (2x25)
	8-way	**2002-478**	50 (2x25)
	9-way	**2002-479**	50 (2x25)
	10-way	**2002-480**	50 (2x25)
	11-way	**2002-481**	50 (2x25)
	12-way	**2002-482**	50 (2x25)
Customized staggered jumper,			
	insulated,		
	I_N 25 A,		
	light gray		
	1-3	**2002-473/011-000**	
			100 (4x25)
	1-3-5	**2002-475/011-000**	
	1-3-5-7	**2002-477/011-000**	
	1-3-5-7-9	**2002-479/011-000**	
	1-3-5-7-9-11	**2002-481/011-000**	
			50 (2x25)
Adjacent jumper for continuous commoning,			
❻	insulated, I_N 25 A,		
	light gray		
	2-way	**2002-400**	100 (4x25)
WMB Multi marking system,			
	10 strips with 10 markers per card,		
	stretchable 5 - 5.2 mm		
	plain	**793-5501**	5
WMB Inline, plain,			
	stretchable 5 - 5.2 mm,		
	1,500 WMB markers, 5 mm, on roll		
	white	**2009-115**	1
Marking strip, plain,			
	11 mm wide,		
	50 m roll		
	white	**2009-110**	1
Operating tool,			
	3.5 mm and 2.5 mm blade,		
	for TOPJOB®S installation terminal blocks		
		2009-309	50



Commoning perfomed via new staggered jumper system in one single jumper slot. The 2003 Series multilevel installation terminal blocks are ideal for use in very confined spaces.

Staggered jumper removal
Insert the operating tool between the jumpers and lift up the jumper.
For additional application notes, see page 141.

Application note:

N-disconnect slide links, used in installation terminal blocks, consist of switch contacts that are opened and then closed again as part of the regular circuit testing. To guarantee a reliable connection, a corrosion-resistant contact area is required on the N-busbar.

Historically, uninsulated copper busbars, that have been cleaned/stripped of any possible corrosion prior to install, can be used in dry, pollution-free locations.

According to DIN VDE 0100-520 (VDE 0100 Part 520), installation equipment exposed to contamination or corrosive substances (e.g., water) that promote corrosion or deterioration, must be protected or be made of a corrosion- or wear- resistant material. In these cases, tinned copper busbars guarantee a reliable connection.

WAGO only offers tinned copper busbars.

TOPJOB®S
Multilevel Installation Terminal Blocks 4 (6) mm²
2005 Series

0.5 - 4 (6) mm² ❶ | AWG 20 - 10 250 V/4 kV/3; 36 A (36 A) ❷ ❸ 400 V/6 kV/3; 36 A (36 A) ❷ ❹ Terminal block width 6.2 mm / 0.244 in 11 - 13 mm / 0.47 in ❺	0.5 - 4 (6) mm² ❶ | AWG 20 - 10 400 V/6 kV/3 ❷ I_N 36 A Terminal block width 6.2 mm / 0.244 in 11 - 13 mm / 0.47 in ❺





	Item No.	Pack. Unit
Multilevel installation terminal block,		
with N-disconnect slide link, gray		
◯ NT/L/PE	**2005-7641**	50

	Item No.	Pack. Unit
Multilevel installation terminal block,		
gray		
◯ L/L	**2005-7642**	50
◯ N/L	**2005-7649**	50



	Item No.	Pack. Unit
Multilevel installation terminal block,		
gray		
◯ N/L/PE	**2005-7646**	50
Multilevel installation terminal block,		
gray		
◯ L/L/PE	**2005-7645**	50

2005 Series Accessories

Appropriate marking systems: WMB/Marking strips
(see Section 13)

End and intermediate plate, 1 mm thick



orange **2005-7692** 100 (4x25)

Straight busbar, Cu with tin plating,



10 x 3 mm,
1000 mm long
I_N 140 A **210-133** 1

Cover for N-busbar,



transparent,
1000 mm long
777-303 1

Busbar carrier,



not suitable as end stop,
for DIN 35 rail,
1.5 mm thick
blue **2009-304** 100 (4x25)

Busbar carrier,



can replace end bracket, with detachable
separator plate,
for DIN 35 rail,
7.5 mm thick
blue **2009-305** 25

Accessories

N-supply terminal block, I_N 76 A,



16 mm²,
12 mm wide
blue **2016-7714** 20



green-yellow **2016-7607** 20

Connector,



for N-busbar,
with blue cover,
2.5 - 16 mm²
blue **210-281** 100 (2x50)

Connector,



for N-busbar,
2.5 - 35 mm²
unplated **209-105** 50

Lock-out, snap-on type,



prevents reclosing of slide link
orange **2005-7300** 100 (4x25)

Insulation stop,



5 pcs/strip,
0.25 - 0.5 mm²
light gray **2004-171** 200 (8x25)

Insulation stop,



5 pcs/strip,
0.75 - 1 mm²
dark gray **2004-172** 200 (8x25)

Push-in type jumper bar, insulated,



I_N 32 A,
light gray

2-way	**2004-402**	200 (8x25)
3-way	**2004-403**	200 (8x25)
4-way	**2004-404**	100 (4x25)
5-way	**2004-405**	100 (4x25)
6-way	**2004-406**	100 (4x25)
7-way	**2004-407**	100 (4x25)
8-way	**2004-408**	100 (4x25)
9-way	**2004-409**	100 (4x25)
10-way	**2004-410**	100 (4x25)

For list of approvals and user guide, see pages 634 to 637.