Contact sequence	Front plate no.	Main contacts	Auxiliary contacts		Max. motor rating AC-23 A, 400/415 V, 50/60 Hz	Rated uninterrupted current	Flush mounting **Front IP65**			Surface mounting **IP65** totally insulated			Rear mounting **Front IP65**			
		Pole			400 V		**Part no.** Article no.	**Price** See price list	Std. pack	**Part no.** Article no.	**Price** See price list	Std. pack	**Part no.** Article no.	**Price** See price list	Std. pack	**Information relevant for export to North America**
	FS 908	N/O	N/O	N/C	P kW	I_u A										
Main switch as emergency switching off/emergency stop device																
With red rotary handle and yellow locking collar To IEC/EN 60204-1, VDE 0113 Part 1 Lockable in the 0 (Off) position																
Without auxiliary contacts																
		3 + N	0	0	90	250	**P5-250/EA/SVB/N**[4] 280938		1 Off				**P5-250/V/SVB/N**[4] 280944		1 Off	1) Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
		3 + N	0	0	110	315	**P5-315/EA/SVB/N**[4] 280952						**P5-315/V/SVB/N**[4] 280958			
		6	0	0	6.5	20	**T0-3-8342/EA/SVB**[1] 029382			**T0-3-8342/I1/SVB** 207159		1 Off	**T0-3-8342/V/SVB**[1] 034128			
					13	32	**T3-3-8342/EA/SVB**[1] 071326			**T3-3-8342/I2/SVB**[2] 207208		1 Off	**T3-3-8342/V/SVB**[1] 076072			
					22	63	**T5B-3-8342/EA/SVB**[3] 092308			**T5B-3-8342/I4/SVB**[3] 207242		1 Off	**T5B-3-8342/V/SVB**[3] 092300			
					30	100	**T5-3-8342/EA/SVB** 096383		1 Off	**T5-3-8342/I5/SVB** 207279		1 Off	**T5-3-8342/V/SVB** 096381		1 Off	
		8	0	0	6.5	20	**T0-4-8344/EA/SVB**[1] 008267		1 Off	**T0-4-8344/I1/SVB** 207163		1 Off	**T0-4-8344/V/SVB**[1] 014007		1 Off	
					13	32	**T3-4-8344/EA/SVB**[1] 008964			**T3-4-8344/I2/SVB**[2] 207212		1 Off	**T3-4-8344/V/SVB**[1] 020598			2) Product Standards: UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
					22	63	**T5B-4-8344/EA/SVB**[3] 092062			**T5B-4-8344/I4/SVB**[3] 207248		1 Off	**T5B-4-8344/V/SVB**[3] 092056			
					30	95				**T5-4-8344/I5/SVB** 207283		1 Off				
					30	100	**T5-4-8344/EA/SVB** 095961		1 Off				**T5-4-8344/V/SVB** 095959		1 Off	
With auxiliary contacts																
		3	1	0	6.5	20	**T0-2-15679/EA/SVB**[1] 081588		1 Off	**T0-2-15679/I1/SVB** 207149		1 Off	**T0-2-15679/V/SVB**[1] 086334		1 Off	
		3	1	1	13	25	**P1-25/EA/SVB/HI11**[1] 091080			**P1-25/I2/SVB/HI11**[2] 207297		1 Off	**P1-25/V/SVB/HI11**[1] 095826			3) Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV7 CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 1, 3R, 12, 13
					13	25				**P1-25/I2H/SVB/HI11** 226902		1 Off				
					15	32	**P1-32/EA/SVB/HI11**[1] 072567			**P1-32/I2/SVB/HI11**[1] 207318		1 Off	**P1-32/V/SVB/HI11**[1] 015145			
					15	32				**P1-32/I2H/SVB/HI11** 227870		1 Off				
					37	63	**P3-63/EA/SVB/HI11**[1] 019891			**P3-63/I4/SVB/HI11**[1] 207348		1 Off	**P3-63/V/SVB/HI11**[1] 024637			
					50	100	**P3-100/EA/SVB/HI11**[1] 029383			**P3-100/I5/SVB/HI11**[1] 207378		1 Off	**P3-100/V/SVB/HI11**[1] 034129			
		3	1	0	45	125	**P5-125/EA/SVB/HI10**[4] 280899		1 Off				**P5-125/V/SVB/HI10**[4] 280915		1 Off	
					55	160	**P5-160/EA/SVB/HI10**[4] 280923						**P5-160/V/SVB/HI10**[4] 280929			4) Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV, NLRV7 CSA File No.: 223805 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
					90	250	**P5-250/EA/SVB/HI10**[4] 280937						**P5-250/V/SVB/HI10**[4] 280943			
					110	315	**P5-315/EA/SVB/HI10**[4] 280951						**P5-315/V/SVB/HI10**[4] 280957			