Contact sequence	Front plate no.	Main contacts	Auxiliary contacts		Max. motor rating AC-23 A, 400/415 V, 50/60 Hz	Rated uninterrupted current	Flush mounting **Front IP65**		Std. pack	Surface mounting **IP65** totally insulated		Std. pack	Rear mounting **Front IP65**		Std. pack
		Pole			400 V		**Part no.** Article no.	**Price** See price list		**Part no.** Article no.	**Price** See price list		**Part no.** Article no.	**Price** See price list	
	FS 908	N/O	N/O	N/C	P kW	I_u A									
Main switch without emergency switching off/emergency stop function															
With black rotary handle and locking collar Lockable in the 0 (Off) position															
Without auxiliary contacts															
1 0 1 2 3 4 5 6 N O		3 + N	0	0	45	125	**P5-125/EA/SVB-SW/N**[4] 280913		1 Off				**P5-125/V/SVB-SW/N**[4] 280919		1 Off
					55	160	**P5-160/EA/SVB-SW/N**[4] 280927						**P5-160/V/SVB-SW/N**[4] 280933		
					90	250	**P5-250/EA/SVB-SW/N**[4] 280941						**P5-250/V/SVB-SW/N**[4] 280947		
					110	315	**P5-315/EA/SVB-SW/N**[4] 280955						**P5-315/V/SVB-SW/N**[4] 280961		
1 0 1 2 3 4 5 6 7 8 9 10 11 12		6	0	0	6.5	20	**T0-3-8342/EA/SVB-SW**[1] 031755		1 Off	**T0-3-8342/I1/SVB-SW** 207160		1 Off	**T0-3-8342/V/SVB-SW**[1] 036501		1 Off
					13	32	**T3-3-8342/EA/SVB-SW**[1] 073699			**T3-3-8342/I2/SVB-SW**[2] 207209		1 Off	**T3-3-8342/V/SVB-SW**[1] 078445		
					22	63	**T5B-3-8342/EA/SVB-SW**[3] 092307			**T5B-3-8342/I4/SVB-SW**[3] 207243		1 Off	**T5B-3-8342/V/SVB-SW**[3] 092299		
					30	100	**T5-3-8342/EA/SVB-SW** 096382		1 Off	**T5-3-8342/I5/SVB-SW** 207280		1 Off	**T5-3-8342/V/SVB-SW** 096380		1 Off
1 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16		8	0	0	6.5	20	**T0-4-8344/EA/SVB-SW**[1] 008268		1 Off	**T0-4-8344/I1/SVB-SW** 207164		1 Off	**T0-4-8344/V/SVB-SW**[1] 008272		1 Off
					13	32	**T3-4-8344/EA/SVB-SW**[1] 008965			**T3-4-8344/I2/SVB-SW**[2] 207213		1 Off	**T3-4-8344/V/SVB-SW**[1] 008967		
					22	63	**T5B-4-8344/EA/SVB-SW**[3] 092061			**T5B-4-8344/I4/SVB-SW**[3] 207249		1 Off	**T5B-4-8344/V/SVB-SW**[3] 092055		
					30	95				**T5-4-8344/I5/SVB-SW** 207284		1 Off			
					30	100	**T5-4-8344/EA/SVB-SW** 095960		1 Off				**T5-4-8344/V/SVB-SW** 095958		1 Off
With auxiliary contacts															
1 0 1 2 3 4 5 6 7 8		3	1	0	6.5	20	**T0-2-15679/EA/SVB-SW**[1] 083961		1 Off	**T0-2-15679/I1/SVB-SW** 207150		1 Off	**T0-2-15679/V/SVB-SW**[1] 088707		1 Off
1 0 1 2 3 4 5 6 13 14 21 22		3	1	1	13	25	**P1-25/EA/SVB-SW/HI11**[1] 070194			**P1-25/I2/SVB-SW/HI11**[2] 207295		1 Off	**P1-25/V/SVB-SW/HI11**[1] 098199		
				1	13	25				**P1-25/I2H/SVB-SW/HI11** 227862		1 Off			
				1	13	25				**P1-25/I2H/SVB/HI11** 226902		1 Off			
				1	15	32	**P1-32/EA/SVB-SW/HI11**[1] 012772			**P1-32/I2/SVB-SW/HI11**[1] 207316		1 Off	**P1-32/V/SVB-SW/HI11**[1] 017518		
				1	15	32				**P1-32/I2H/SVB-SW/HI11** 227873		1 Off			
				1	37	63	**P3-63/EA/SVB-SW/HI11**[1] 022264			**P3-63/I4/SVB-SW/HI11**[1] 207345		1 Off	**P3-63/V/SVB-SW/HI11**[1] 027010		
				1	50	100	**P3-100/EA/SVB-SW/HI11**[1] 031756			**P3-100/I5/SVB-SW/HI11**[1] 207375		1 Off	**P3-100/V/SVB-SW/HI11**[1] 036502		
1 0 1 2 3 4 5 6 13 14		3	1	0	45	125	**P5-125/EA/SVB-SW/HI10**[4] 280912		1 Off				**P5-125/V/SVB-SW/HI10**[4] 280918		1 Off
				0	55	160	**P5-160/EA/SVB-SW/HI10**[4] 280926						**P5-160/V/SVB-SW/HI10**[4] 280932		
				0	90	250	**P5-250/EA/SVB-SW/HI10**[4] 280940						**P5-250/V/SVB-SW/HI10**[4] 280946		
				0	110	315	**P5-315/EA/SVB-SW/HI10**[4] 280954						**P5-315/V/SVB-SW/HI10**[4] 280960		
1 0 1 2 3 4 5 6 7 8 9 10 11 12		3	2	1	6.5	20	**T0-3-15683/EA/SVB-SW**[1] 015600		1 Off	**T0-3-15683/I1/SVB-SW** 207158		1 Off	**T0-3-15683/V/SVB-SW**[1] 015664		1 Off
		3	2	1	13	32	**T3-3-15683/EA/SVB-SW**[1] 042851		1 Off	**T3-3-15683/I2/SVB-SW**[2] 207207		1 Off			

1)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

2)

Product Standards	UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12

3)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV7
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 1, 3R, 12, 13

4)

Product Standards	UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking
UL File No.	E36332
UL CCN	NLRV, NLRV7
CSA File No.	223805
CSA Class No.	3211-05
NA Certification	UL Listed, CSA certified
Suitable for	Branch circuits, suitable as motor disconnect
Degree of Protection	IEC: IP65; UL/CSA Type 3R, 12