Flat copper bars

		Rated operational current I_e A	Dimensions mm		**Part no.** Article no.	**Price** See price list	Std. pack
	Tinned	160	12 x 5 x supplied in lengths of 1500		**CU12X5** 034121		10 off
	Tinned	160	12x 5 x supplied in lengths of 2250		**CU12X5-2250** 005093		10 off
	Tinned	240	12 x 10 x supplied in lengths of 1500		**CU12X10** 215269		5 off
	Tinned	310	15 x 5 x supplied in lengths of 1500		**CU15X5** 215270		10 off
	Tinned	360	15 x 10 x supplied in lengths of 1500		**CU15X10** 215271		5 off
	Tinned	250	20 x 5 x supplied in lengths of 1500		**CU20X5** 044092		10 off
	Tinned	250	20 x 5 x supplied in lengths of 2250		**CU20X5-2250** 007466		10 off
	Tinned	250	20 x 5 x supplied in lengths of 2500		**CU20X5-2500** 032703		1 off
	Tinned	400	12 x 10 x supplied in lengths of 1500		**CU20X10** 041719		5 off
	Tinned	400	20 x 10 x supplied in lengths of 2250		**CU20X10-2250** 009839		5 off
	Untreated	630	30 x 10 x supplied in lengths of 1500		**CU30X10** 051211		1 off
	Untreated	850	40 x 10 x supplied in lengths of 1500		**CU40X10** 063076		3 off

Flat copper busbars, predrilled

	Rated operational current I_e A	Thread	Dimensions mm	**Part no.** Article no.	**Price** See price list	Std. pack
	218	M6	15 x 5 x supplied in lengths of 1000	**BPZ-BB/T-15/5/1000** 289861		4 off
	274	M6	20 x 5 x supplied in lengths of 1000	**BPZ-BB/T-20/5/1000** 289862		4 off
	400	M6	32 x 5 x supplied in lengths of 1000	**BPZ-BB/T-32/5/1000** 289863		1 off
	218	M6	15 x 5 x supplied in lengths of 2000	**BPZ-BB/T-15/5/2000** 289864		1 off
	274	M6	20 x 5 x supplied in lengths of 2000	**BPZ-BB/T-20/5/2000** 289865		1 off
	427	M8	20 x 10 x supplied in lengths of 1000	**BPZ-BB/T-20/10/1000** 289866		1 off
	573	M8	30 x 10 x supplied in lengths of 1000	**BPZ-BB/T-30/10/1000** 289867		1 off

DIN-rails

		Part no. Article no.	**Price** See price list	Std. pack
	To IEC/EN 60715 35 x 7.5 mm Short-circuit rating as PE conductor corresponds to 16 mm² copper conductor to IEC/EN 60439-1 Supplied in lengths of 2 m	**TS35X7.5** 053030		20 off
	To IEC/EN 60715 35 x 15 mm Short-circuit rating as PE conductor corresponds to 50 mm² copper conductor to IEC/EN 60439-1 Supplied in lengths of 2 m	**TS35X15** 050657		10 off