









Ordering

Dimensions	Enclosure depth: Dimensions from top: 1. Mounting depth for mounting plate 2. Mounting depth for mounting rail 7.5 mm height 3. Enclosure depth	Mounting depth		Features	**Part no.** Article no.	**Price** See price list	Std. pack
		For mounting plate	For 7.5 mm mounting rail				
mm	mm	mm	mm				
CI-K basic enclosures							
• Protection type IP65 (exception: CI-K2-80-A), material characteristic glass-fibre reinforced polycarbonate • Enclosure base RAL 9005, black/enclosure top only RAL 7035, light grey • Metric cable entry knockouts top, bottom and in the back plate • Push-through cable membrane with CI-K1 and CI-K2 • Hard metric knockouts with CI-K1H and CI-K2H • Hard metric knockouts with CI-K3 to CI-K5 • Control cable entry with CI-K2 • Indicator light L-. can be mounted in base knock out M20/M25							
		–	72	With mounting rail	**CI-K1-95-TS** 206881		1 off
		–	72	With mounting rail	**CI-K1H-95-TS** 105853		1 off
		–	73	With mounting rail	**CI-K2-100-TS** 206882		1 off
		–	73	With mounting rail	**CI-K2H-100-TS** 229304		1 off
		79	–	With mounting plate	**CI-K2-100-M** 206893		1 off
		79	–	With mounting plate	**CI-K2H-100-M** 229306		1 off
		–	118	With mounting rail	**CI-K2-145-TS** 206883		1 off
		–	118	With mounting rail	**CI-K2H-145-TS** 229305		1 off
		124	–	With mounting plate	**CI-K2-145-M** 206894		1 off
		124	–	With mounting plate	**CI-K2H-145-M** 229307		1 off
		124	–	With adapter plate for contactor DILE with overload relay ZE	**CI-K2-145-AD** 207632		1 off
		124	–	With adapter plate for contactor DILE with overload relay ZE	**CI-K2H-145-AD** 229308		1 off
		–	93	With mounting rail	**CI-K3-125-TS** 206884		1 off
		98	–	With mounting plate	**CI-K3-125-M** 206895		1 off
		–	128	With mounting rail	**CI-K3-160-TS** 206885		1 off
		133	–	With mounting plate	**CI-K3-160-M** 206896		1 off

Notes Number and size of cable entries → Page 20/95