	Function: = Momentary, = Maintained	Color	Bezel: Silver **Part no.** Article no.	**Price** See price list	Std. pack	Bezel: black **Part no.** Article no.	**Price** See price list	Std. pack
Illuminated selector switch actuators, thumb-grip, IP66								
ATEX → Engineering Bezel gold-plated → Page 2/48 Maintained/momentary function, can be changed with coding adapter M22-XC-Y → Engineering								
Momentary 	40°	White	**M22-WLK-W** 216812		5 off	**M22S-WLK-W** 216813		5 off
	40°	Red	**M22-WLK-R** 216814			**M22S-WLK-R** 216815		
	40°	Green	**M22-WLK-G** 216816			**M22S-WLK-G** 216817		
	40°	Yellow	**M22-WLK-Y** 216818			**M22S-WLK-Y** 216819		
	40°	Blue	**M22-WLK-B** 216820			**M22S-WLK-B** 216821		
Maintained 	60°	White	**M22-WRLK-W** 216823			**M22S-WRLK-W** 216824		
	60°	Red	**M22-WRLK-R** 216825			**M22S-WRLK-R** 216826		
	60°	Green	**M22-WRLK-G** 216827			**M22S-WRLK-G** 216828		
	60°	Yellow	**M22-WRLK-Y** 216829			**M22S-WRLK-Y** 216830		
	60°	Blue	**M22-WRLK-B** 216831			**M22S-WRLK-B** 216832		
3 positions								
Momentary 	40° ⇕ 40°	White	**M22-WLK3-W** 216833		5 off	**M22S-WLK3-W** 216834		5 off
	40° ⇕ 40°	Red	**M22-WLK3-R** 216835			**M22S-WLK3-R** 216836		
	40° ⇕ 40°	Green	**M22-WLK3-G** 216837			**M22S-WLK3-G** 216838		
	40° ⇕ 40°	Yellow	**M22-WLK3-Y** 216839			**M22S-WLK3-Y** 216840		
	40° ⇕ 40°	Blue	**M22-WLK3-B** 216841			**M22S-WLK3-B** 216842		
Maintained 	60° ⇓ 60°	White	**M22-WRLK3-W** 216843			**M22S-WRLK3-W** 216844		
	60° ⇓ 60°	Red	**M22-WRLK3-R** 216845			**M22S-WRLK3-R** 216846		
	60° ⇓ 60°	Green	**M22-WRLK3-G** 216847			**M22S-WRLK3-G** 216848		
	60° ⇓ 60°	Yellow	**M22-WRLK3-Y** 216849			**M22S-WRLK3-Y** 216850		
	60° ⇓ 60°	Blue	**M22-WRLK3-B** 216851			**M22S-WRLK3-B** 216852		
	Selectable	Selectable → Notes	**M22-WRLK3-*/*** 217438			**M22S-WRLK3-*/*** 217439		
V position								
	60°	White	**M22-WLKV-W** 284393		5 off	**M22S-WLKV-W** 284398		5 off
	60°	Red	**M22-WLKV-R** 284394			**M22S-WLKV-R** 284399		
	60°	Green	**M22-WLKV-G** 284395			**M22S-WLKV-G** 284540		
	60°	Yellow	**M22-WLKV-Y** 284396			**M22S-WLKV-Y** 284543		
	60°	Blue	**M22-WLKV-B** 284397			**M22S-WLKV-B** 284544		

Notes

Example: M22-WRLK3-*/*
/: *= 1 for ⇕ or 2 for ⇓
/: *= Color

Information relevant for export to North America

Product Standards	IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
UL File No.	E29184
UL CCN	NKCR
CSA File No.	012528
CSA Class No.	3211-03
NA Certification	UL Listed, CSA certified
Degree of Protection	UL/CSA Type 3R, 4X, 12, 13