Item no.:	750-600
Product description:	END MODULE





Packing unit 1 piece

Product group	15 (I/O System)
Operating temperature	0 °C ... + 55 °C
Storage temperature	-25 °C ... +85 °C
Relative air humidity	95 %
Vibration resistance	acc. IEC 60068-2-6
Shock resistance	acc. IEC 60068-2-27
Degree of protection	IP 20
EMC immunity to interference	acc. EN 50082-2 (96)
EMC emission of interference	per EN 50081-1 (93)
EMC marine applications - noise proof	gem. Germanischer Lloyd (2003)
EMC marine applications - noise transmission	gem. Germanischer Lloyd (2003)
Conformity marking	CE
Approvals	ATEX
Weight	33.5 g
Color	light gray
Height	64 mm
Height	2.52 in
Width	12 mm
Width	0.472 in
Depth	100 mm
Depth	3.937 in
Mounting	TS 35

Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
750-600	ABS	03-HG374860/2-PDA			
750-600	BSH	Bescheinigung Nr. 467			
750-600	BV	13453/B0 BV			
750-600	DNV	A-10191			
750-600	GL	26 898 - 05 HH			
750-600	IECEx	IECEx PTB 07.0064X			
750-600	KEMA	01 ATEX 1024 X			
750-600	KR	HMB05880-EL004			
750-600	KR	HMB05880-EL005			
750-600	LR	02/20026 (E2)			
750-600	NK	TA06190M			
750-600	PRS	TE/1720/880590/08			
750-600	Rina	ELE153207CS001			
750-600	UL	E175199 Sec.1			
750-600	UL	E198726 Sec.1			
750-600	UL DEMKO A/S	DEMKO 08 ATEX 142851 X			

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected