

Transverse Switching Terminal Blocks and Longitudinal Switching Disconnect Terminal Blocks, 282 Series – Description and Handling –

Commoning




Transverse switching terminal blocks
Left: Adjacent jumper for commoning of switch lever
Right: Commoning with orange jumper

Switch positions




Left: closed
Right: open

Current transformer circuit




via transverse switching terminal blocks
a = Normal operation **b** = Measurement testing
c = Transformer short-circuit


Testing




Testing with touch-proof test sockets 4 mm Ø.
(not offered by WAGO)
e.g., mfd by Multi-Contact Deutschland GmbH




CAGE CLAMP® connection



Conductor termination




Lock-out




Inserting lock-out.

Commoning



Longitudinal switching disconnect terminal blocks

Current transformer circuit



via longitudinal switching disconnect terminal blocks
a = Normal operation **b** = Measurement testing
c = Transformer short-circuit **d** = Relay test


CAGE CLAMP® clamps the following copper conductors:*

solid	stranded	fine-stranded, also with tinned single strands	fine-stranded, tip-bonded	fine-stranded, with ferrule ❶ (gastight crimped)	fine-stranded, with pin terminal (gastight crimped)


* For aluminum conductors, see notes in Section 14.

❶ When using ferrules, the max. conductor cross section accommodated is one size smaller than max. rating of terminal block.


Jumpers with Safety Lid for Longitudinal Switching Disconnect Terminal Blocks Series 282




Jumper with safety lid
– Jumper in pre-latching position



Jumper with safety lid
Longitudinal switching disconnect terminal blocks with inserted jumper, including safety lid




Jumper with safety lid
– Jumper with raised safety lid





Jumper with safety lid
– Removing jumper via safety lid

Transverse Switching Terminal Blocks and Longitudinal Switching Disconnect Terminal Blocks 6 mm², e.g., Current Transformer Circuits, 282 Series

0.2 - 6 mm² | AWG 24 - 10 500 V/6 kV/3 ❶ | 600 V, 30 A I_N 30 A | 300 V, 36 A Terminal block width 8 mm / 0.315 in 12 - 13 mm / 0.49 in ❷	0.2 - 6 mm² | AWG 24 - 10 500 V/6 kV/3 ❶ | 600 V, 30 A I_N 30 A | 300 V, 36 A Terminal block width 8 mm / 0.315 in 12 - 13 mm / 0.49 in ❷	0.2 - 6 mm² | AWG 24 - 10 500 V/6 kV/3 ❶ I_N 30 A Terminal block width 8 mm / 0.315 in 12 - 13 mm / 0.49 in ❷







Item No.	Pack. Unit
2-conductor transverse switching terminal block, with touch-proof test socket, for test plug 4 mm Ø	
◯ gray **282-811** ❸	20

Item No.	Pack. Unit
2-conductor longitudinal switching disconnect terminal block, with touch-proof test sockets, for test plug 4 mm Ø	
◯ gray **282-821** ❸	20

Item No.	Pack. Unit
2-conductor through terminal block, with touch-proof test sockets, for test plug 4 mm Ø	
◯ gray **282-841**	20

Item-Specific Accessories

End and separator plate,

1.5 mm thick		
orange	**282-366**	50 (5x10)
gray	**282-361**	50 (5x10)

Adjacent jumper for switch lever, insulated, orange,

I_N 30 A		
2-way	**282-442**	50 (5x10)
3-way	**282-443**	50 (5x10)
4-way	**282-444**	50 (5x10)
5-way	**282-445**	50 (5x10)
6-way	**282-446**	50 (5x10)

Item-Specific Accessories

End and separator plate,

1.5 mm thick		
orange	**282-365**	50 (5x10)
gray	**282-360**	50 (5x10)

Item-Specific Accessories

End and separator plate,

1.5 mm thick		
orange	**282-365**	50 (5x10)
gray	**282-360**	50 (5x10)

Accessories

Appropriate marking systems: WMB/Miniature WSB (see Section 13)

Lock-out,

for disconnect link		
yellow	**282-370**	100 (4x25)

Coupling device,

mechanically locks multiple links,		
yellow		
2-way	**282-372**	50 (5x10)
3-way	**282-373**	50 (5x10)
4-way	**282-374**	50 (5x10)

Jumper, insulated,

I_N 30 A,		
orange		
2-way	**282-432**	50 (5x10)
3-way	**282-433**	50 (5x10)
4-way	**282-434**	50 (5x10)
5-way	**282-435**	50 (5x10)
6-way	**282-436**	50 (5x10)
7-way	**282-437**	50 (5x10)
8-way	**282-438**	50 (5x10)
9-way	**282-439**	50 (5x10)
10-way	**282-440**	50 (5x10)

Protective warning marker,

with high-voltage symbol, black,		
for 5 terminal blocks		
yellow	**282-415**	100 (4x25)

Jumper, special design,

I_N 30 A,		
orange		
1-3-5	**282-435/011-000**	
1-3-5-7	**282-437/011-000**	
		50 (5x10)

Jumper with safety lid, insulated,

I_N 30 A,		
orange		
2-way	**282-432/100-000**	
3-way	**282-433/100-000**	
4-way	**282-434/100-000**	
		50 (5x10)

Collective carrier for jumpers,

for jumpers for transverse switching terminal block (282-811) and longitudinal switching disconnect terminal block (282-821)		
gray	**282-369**	25

WMB Multi marking system,

10 strips with 10 markers per card,		
for terminal widths 5 - 17.5 mm		
plain	**793-501**	5


WMB Multi marking system, plain,

10 strips with 10 markers per card,		
for terminal widths 5 - 17.5 mm		
yellow	**793-501/000-002**	
red	**793-501/000-005**	
blue	**793-501/000-006**	
gray	**793-501/000-007**	
orange	**793-501/000-012**	
light green	**793-501/000-017**	
green	**793-501/000-023**	
violet	**793-501/000-024**	
		5

For list of approvals and user guide, see pages 634 to 637.

0.2 - 6 mm² | **AWG 24 - 10**
500 V/6 kV/3 ❶
I_N 30 A

Terminal block width 8 mm / 0.315 in
12 - 13 mm / 0.49 in ❷



	Item No.	Pack. Unit
2-conductor through terminal block,		
without test sockets		
gray	**282-841/049-000**	20

Item-Specific Accessories

End and separator plate,			
	1.5 mm thick		
	orange	**282-365**	50 (5x10)
	gray	**282-360**	50 (5x10)
WMB Multi marking system,			
	10 strips with 10 markers per card, for terminal widths 5 - 17.5 mm, yellow		
	k/l (50x)	**794-5553/000-002**	5
WMB Multi marking system,			
	10 strips with 10 markers per card, for terminal widths 5 - 17.5 mm, blue		
	U/V (50x)	**794-5554/000-006**	5
Screwless end stop,			
	for DIN 35 rail, 6 mm wide		
	gray	**249-116**	100 (4x25)
Screwless end stop,			
	for DIN 35 rail, 10 mm wide		
	gray	**249-117**	50 (2x25)


❶ 500 V = rated voltage
6 kV = rated surge voltage
3 = pollution degree
(also see Section 14)


❷ Strip length, see packaging or instructions.


❸ Max. height when rotating the disconnect link (incl. locking cover): 45 mm/1.77 in
For operating stickers, please refer to our online catalog:
for 282-811: Item No. 210-424
for 282-821: Item No. 210-423

Disconnect and Ground Conductor Disconnect Terminal Blocks 6 mm²/30 A and Through Terminal Blocks of Same Profile 282 Series

0.2 - 6 mm²	AWG 24 - 10	0.2 - 6 mm²	AWG 24 - 10	0.2 - 6 mm²	AWG 24 - 10
400 V/6 kV/3 ❶	600 V, 30 A	800 V/8 kV/3 ❶	600 V, 30 A		
I_N 30 A	300 V, 36 A	I_N 41 A	600 V, 40 A		
Terminal block width 8 mm / 0.315 in		Terminal block width 8 mm / 0.315 in		Terminal block width 16 mm / 0.63 in	
12 - 13 mm / 0.49 in ❷		12 - 13 mm / 0.49 in ❷		12 - 13 mm / 0.49 in ❷	







	Item No.	Pack. Unit
2-conductor disconnect terminal block,		
with test point,		
orange disconnect link		
gray	**282-697**	25
blue	**282-695**	25
Other terminal blocks with the same profile:		
Through	**282-699** Page 220	

	Item No.	Pack. Unit
3-conductor through terminal block,		
with test point,		
same profile as disconnect terminal blocks		
gray	**282-699**	25
blue	**282-694**	25
Other terminal blocks with the same profile:		
Disconnect	**282-697** Page 220	
Ground cond. disc.	**282-640** Page 220	
Fuse	**282-696** Page 222	

	Item No.	Pack. Unit
Ground conductor disconnect terminal block,		
with test point,		
orange disconnect link, gray		
24 V	**282-640**	12
48 V	**282-641**	12
120 V	**282-638**	12
230 V	**282-639**	12
Other terminal blocks with the same profile:		
Through	**282-699** Page 220	

Item-Specific Accessories

Adjacent jumper, insulated,			
	I_N 41 A		
	gray	**282-402**	100 (4x25)
Alternate jumper, insulated,			
	I_N 41 A		
	gray	**282-409**	100 (4x25)
Test plug adapter, 8.3 mm wide,			
	for terminal blocks 1.5 - 10 mm²,		
	for test plug 4 mm Ø		
	gray	**209-170**	50 (2x25)

Item-Specific Accessories

Adjacent jumper, insulated,			
	I_N 41 A		
	gray	**282-402**	100 (4x25)
Alternate jumper, insulated,			
	I_N 41 A		
	gray	**282-409**	100 (4x25)
Test plug adapter, 8.3 mm wide,			
	for terminal blocks 1.5 - 10 mm²,		
	for test plug 4 mm Ø		
	gray	**209-170**	50 (2x25)

Accessories

Appropriate marking system: WMB
(see Section 13)

End plate, 2 mm thick			
	orange	**282-333**	100 (4x25)
	gray	**282-334**	100 (4x25)
Protective warning marker,			
	with high-voltage symbol, black,		
	for 5 terminal blocks		
	yellow	**282-405**	100 (4x25)
Screwless end stop,			
	for DIN 35 rail,		
	6 mm wide		
	gray	**249-116**	100 (4x25)
Screwless end stop,			
	for DIN 35 rail,		
	10 mm wide		
	gray	**249-117**	50 (2x25)

For list of approvals and user guide, see pages 634 to 637.