




		For use with	Part no. Article no.	Price See price list	Std. pack	Notes	Information relevant for export to North America
Service distribution board mounting accessories							
Including push-fit shaft							
	For retrofitting in service distribution board mounting T0-…/IVS design. Use the basic switch's front plate.	T0-…/XZ	**IVS-T0** 091114		1 off		UL/CSA certification not required
Coupling drive							
Including push-fit shaft							
	For the retrofitting of switch T0(T3)-.../XZ as rear mounting, spare part for T0(T3)/(P1)-.../Z	–	**DE-T0** 093487		1 off		UL/CSA certification not required
	For the conversion of T5(B)-.../E flush mounting switch to rear mounting, spare part for T5(B)/(P3)-...Z	–	**DE-P3** 093972		3 off		
Interlock sections							
With PE and neutral conductor connection Mounting on the back of flush mounting switch, with interlock function in rear mounting switches.							
		T0-…/E, …EZ, …Z T3-…/E, …EZ, …Z P1-…/E, …EZ, …Z	**UV-T0** 019925		1 off	Mounting on the back of flush mounting switch	UL/CSA certification not required
		T5(B)-…/E, …Z P3-…/E, …Z	**UV-P3** 048289		1 off	With interlock function for rear mounting switches	
Interlock extensions							
A max. of 4 units can be plugged on the interlock section every 25 mm (an equal number of shaft extensions is required for this)							
	Use only with T0/T3-… and P3-…/Z designs	UV-T0	**ZVV-T0** 022298		10 off	–	UL/CSA certification not required
	Use only with T5(B)-…/Z and P3-…/Z designs	UV-P3	**ZVV-P3** 024671		10 off	–	
Shaft extensions							
A max. of 4 units can be put on the switch shaft every 25 mm							
		T0-…/Z, T0-…/V T3-…/Z, T3-…/V P1-…/Z, P1-…/V	**ZAV-T0** 027044		10 off	–	UL/CSA certification not required
		T5(B)-…/Z P3-…/Z P3-…/V	**ZAV-P3** 029417		10 off	–	
Shaft							
	Aluminum, length: 480 mm	P5-…/V… P5-…/Z	**ZAV-P5** 280979		1 off		UL/CSA certification not required
Interlock extensions und shaft extensions, complete							
	Extension to 25 mm When ordering with basic unit		**+ZAV(X1)+ZVV(X1)-T0/P3** 254546		1 off		UL/CSA certification not required
Control cable terminal							
		P5-250/315	**ST-P5-250/315** 280978		1 off	Terminal capacity: • Solid or stranded: 4 mm² • Flexible with ferrules to DIN 46228: 4 mm²	UL/CSA certification not required