Contact sequence	Front plate no.	Main contacts	Auxiliary contacts		Max. motor rating AC-23 A, 400/415 V, 50/60 Hz	Rated uninterrupted current	Flush mounting **Front IP65**		Surface mounting **IP65** totally insulated		Rear mounting **Front IP65**		Std. pack	**Information relevant for export to North America**
		Pole			400 V		**Part no.** Article no.	**Price** See price list	**Part no.** Article no.	**Price** See price list	**Part no.** Article no.	**Price** See price list		
	FS 908	N/O	N/O	N/C	P kW	I_u A								
Main switch without emergency switching off/emergency stop function														
With black rotary handle and locking collar Lockable in the 0 (Off) position														
Without auxiliary contacts														
1 0 2 0	1	0	0	6.5	20	**T0-1-8200/EA/SVB-SW**[1] 055483		**T0-1-8200/I1/SVB-SW** 207146		1 Off	**T0-1-8200/V/SVB-SW**[1] 060229		1 Off	1)
				13	32	**T3-1-8200/EA/SVB-SW**[1] 068949		**T3-1-8200/I2/SVB-SW**[2] 207201		1 Off	**T3-1-8200/V/SVB-SW**[1] 004882			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
				22	63	**T5B-1-8200/EA/SVB-SW**[3] 094278		**T5B-1-8200/I4/SVB-SW**[3] 207241		1 Off				
1 0 2 0 3 0 4 0	2	0	0	6.5	20	**T0-1-102/EA/SVB-SW**[1] 093451		**T0-1-102/I1/SVB-SW** 207144		1 Off	**T0-1-102/V/SVB-SW**[1] 022330			
				13	32	**T3-1-102/EA/SVB-SW**[1] 016747		**T3-1-102/I2/SVB-SW**[2] 207199		1 Off	**T3-1-102/V/SVB-SW**[1] 021493			
				22	63	**T5B-1-102/EA/SVB-SW**[3] 094468		**T5B-1-102/I4/SVB-SW**[3] 207239		1 Off	**T5B-1-102/V/SVB-SW**[3] 094462			
				30	100	**T5-1-102/EA/SVB-SW** 098807							1 Off	2)
1 0 3 0 4 0 5 0 6 0	3	0	0	6.5	20	**T0-2-1/EA/SVB-SW**[1] 041246		**T0-2-1/I1/SVB-SW** 207148		1 Off	**T0-2-1/V/SVB-SW**[1] 045992		1 Off	Product Standards: UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
				13	25	**P1-25/EA/SVB-SW**[1] 048365		**P1-25/I2/SVB-SW**[2] 207294		1 Off	**P1-25/V/SVB-SW**[2] 050738			
				13	25			**P1-25/I2H/SVB-SW** 227861		1 Off				
				15	32	**P1-32/EA/SVB-SW**[1] 053111		**P1-32/I2/SVB-SW**[2] 207315		1 Off	**P1-32/V/SVB-SW**[1] 055484			
				15	32			**P1-32/I2H/SVB-SW** 227872		1 Off				
				37	63	**P3-63/EA/SVB-SW**[1] 057857		**P3-63/I4/SVB-SW**[1] 207344		1 Off	**P3-63/V/SVB-SW**[1] 060230			
				50	100	**P3-100/EA/SVB-SW**[1] 062603		**P3-100/I5/SVB-SW**[1] 207374		1 Off	**P3-100/V/SVB-SW**[1] 064976			
				45	125	**P5-125/EA/SVB-SW**[4] 280911					**P5-125/V/SVB-SW**[4] 280917			3)
				55	160	**P5-160/EA/SVB-SW**[4] 280925					**P5-160/V/SVB-SW**[4] 280931			Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV7 CSA File No.: 12528 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 1, 3R, 12, 13
				90	250	**P5-250/EA/SVB-SW**[4] 280939					**P5-250/V/SVB-SW**[4] 280945			
				110	315	**P5-315/EA/SVB-SW**[4] 280953					**P5-315/V/SVB-SW**[4] 280959			
1 0 3 0 4 0 5 0 6 0 N 0	3 + N	0	0	6.5	20	**T0-2-8900/EA/SVB-SW**[1] 207401		**T0-2-8900/I1/SVB-SW** 207152		1 Off	**T0-2-8900/V/SVB-SW**[1] 207406		1 Off	
				13	25	**P1-25/EA/SVB-SW/N**[1] 083960		**P1-25/I2/SVB-SW/N**[2] 207296		1 Off	**P1-25/V/SVB-SW/N**[1] 088706			4)
				13	25			**P1-25/I2H/SVB-SW/N** 227863		1 Off				Product Standards: UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No.: E36332 UL CCN: NLRV, NLRV7 CSA File No.: 223805 CSA Class No.: 3211-05 NA Certification: UL Listed, CSA certified Suitable for: Branch circuits, suitable as motor disconnect Degree of Protection: IEC: IP65; UL/CSA Type 3R, 12
				15	32	**P1-32/EA/SVB-SW/N**[1] 093452		**P1-32/I2/SVB-SW/N**[2] 207317		1 Off	**P1-32/V/SVB-SW/N**[1] 098198			
				15	32			**P1-32/I2H/SVB-SW/N** 227874		1 Off				
				15	32			**P1-32/I2H/N** 227869		1 Off				
				37	63	**P3-63/EA/SVB-SW/N**[1] 012771		**P3-63/I4/SVB-SW/N**[1] 207346		1 Off	**P3-63/V/SVB-SW/N**[1] 017517			
				50	100	**P3-100/EA/SVB-SW/N**[1] 022263		**P3-100/I5/SVB-SW/N**[1] 207376		1 Off	**P3-100/V/SVB-SW/N**[1] 027009			