		For use with	**Part no.** Article no. for separate order	**Price** See price list	Std. pack	**Notes**	**Information relevant for export to North America**
Rotary handle on circuit-breaker							
Complete with rotary drive							
Standard, black/grey							
   	Lockable in 0 position on switch with up to 3 padlocks.	NZM1(-4), PN1(-4), N(S)1(-4)	**NZM1-XDV** 260125		1 off	NZM1, 2, 3: Can also be combined with insulating surround. MODAN handle position detection by wire release can be retrofitted.	Product Standards: UL489; CSA-C22.2 No. 5-09; IEC60947, CE marking UL File No.: E140305 UL CCN: DIHS CSA File No.: 022086 CSA Class No.: 1437-01 NA Certification: UL Listed, CSA certified
		NZM2(-4), PN2(-4), N(S)2(-4)	**NZM2-XDV** 260127				
		NZM3(-4), PN3(-4), N(S)3(-4)	**NZM3-XDV** 260129				
		NZM4(-4), N(S)4(-4)	**NZM4-XDV** 266608				
 	Lockable in 0 position on handle with up to 3 padlocks.	NZM1(-4), PN1(-4), N(S)1(-4)	**NZM1-XDVG** 285247		1 off	Can also be combined with insulating surround.	
		NZM2(-4), PN2(-4), N(S)2(-4)	**NZM2-XDVG** 285248				
Red-yellow for emergency switching off							
   	Lockable in 0 position on switch with up to 3 padlocks.	NZM1(-4), PN1(-4), N(S)1(-4)	**NZM1-XDVR** 260135		1 off	NZM1, 2, 3: Can also be combined with insulating surround. MODAN handle position detection by wire release can be retrofitted.	Product Standards: UL489; CSA-C22.2 No. 5-09; IEC60947, CE marking UL File No.: E140305 UL CCN: DIHS CSA File No.: 022086 CSA Class No.: 1437-01 NA Certification: UL Listed, CSA certified
		NZM2(-4), PN2(-4), N(S)2(-4)	**NZM2-XDVR** 260137				
		NZM3(-4), PN3(-4), N(S)3(-4)	**NZM3-XDVR** 260140				
		NZM4(-4), N(S)4(-4)	**NZM4-XDVR** 266610				
 	Lockable in 0 position on handle with up to 3 padlocks.	NZM1(-4), PN1(-4), N(S)1(-4)	**NZM1-XDVGR** 285249		1 off	Can also be combined with insulating surround.	
		NZM2(-4), PN2(-4), N(S)2(-4)	**NZM2-XDVGR** 285280				

Notes Circuit-breaker can also be installed in a lying position 90° left/right, with the handle still in the same position.