KE64.3

Nazwa:	**Zacisk Clampo Pro**
	1 torowy, żółty/zielony, Al/Cu 35-240 mm²
Typ:	KE64.3
GTIN:	6418677191930
Opis:	Zaciski uniwersalne Ensto Clampo stosowane są do łączenia przewodów Al/Cu o przekrojach 2.5 – 240 mm². Szeroki zakres zastosowań od tradycyjnych rozdzielnic, automatykę kontrolno-pomiarową, po instalacje budownictwa mieszkaniowego.
Opakowanie:	
Jednostka:	szt.



Specyfikacje techniczne

Stopień zanieczyszczenia	3
Moment dokręcenia	12 Nm (35-70mm²), 45 Nm (95-240mm²)
Masa	0.249 kg
Przekrój żyły	35-240
Temperatura pracy	≤ 80 °C
Klasa cieplna	T1
Montaż	Śruba
Liczba biegunów	1
Łeb śruby	Sześciokąt
Screw head size	8 mm
Obudowa	Poliamid
Kolor	Żółty/zielony
Rozmiar żyły	500-3/0
Moment dokręcenia	360 Lb-In
Standardy	EN 60947-7-2, IEC 61238-1, UL 1059
Kategoria UL	XCFR2

Ensto Pol Sp. z o.o.
ul. Starogardzka 17 A
83-010 Straszyn, Poland
tel. +48 58 692 40 00
fax +48 58 692 40 20
www.ensto.pl

This product card has been printed from Ensto´s web-pages. Please, observe our legal notice on the front page of www.ensto.com.
© Ensto 2015

KE64.3

Nr specyfikacji UL	E192532, E192532

Ensto Pol Sp. z o.o.
ul. Starogardzka 17 A
83-010 Straszyn, Poland
tel. +48 58 692 40 00
fax +48 58 692 40 20
www.ensto.pl

This product card has been printed from Ensto´s web-pages. Please, observe our legal notice on the front page of www.ensto.com.
© Ensto 2015