OABP203013G



Nazwa:	**Obudowa Cubo O**
	Wymiary 200 x 300 x 132 mm, boki gładkie, pokrywa szara, ABS
Typ:	OABP203013G
GTIN:	6418677184567
Opis:	Obudowy Ensto Cubo O dostępne są z bokami gładkimi lub przetłoczeniami metrycznymi. Pokrywa i śruby pokrywy wyposażone są w otwory umożliwiające zaplombowanie obudowy. Pokrywa może być również zamontowana z tyłu obudowy.
Opakowanie:	1/1
Jednostka:	szt.

CE RoHS FI

Specyfikacje techniczne

Zawartość	Podstawa obudowy, pokrywa, śruby pokrywy, śruby montażowe
Stopień ochrony	IP66/IP67
Odporność na udar	IK 07/IK 06
Wysokość	300 mm
Szerokość	200 mm
Głębokość	132 mm
Masa	1.176 kg
Objętość	792.00 cm³
Głębokość wewnętrzna	115.0 mm
Wysokość zewnętrzna pokrywy	30 mm
Rozmiar	200 x 300 x 132
Temperatura pracy	-40 … 60 °C
Zakres temperatur (krótki okres)	-40 … 80 °C
Base	ABS
Cover	ABS
Śruby pokrywy	Poliamid
Uszczelka	Poliuretan
Kolor	Szary

Ensto Pol Sp. z o.o.
ul. Starogardzka 17 A
83-010 Straszyn, Poland
tel. +48 58 692 40 00
fax +48 58 692 40 20
www.ensto.pl

This product card has been printed from Ensto´s web-pages. Please, observe our legal notice on the front page of www.ensto.com.
© Ensto 2015

OABP203013G

Standardy	EN 62208, GOST R

Ensto Pol Sp. z o.o.
ul. Starogardzka 17 A
83-010 Straszyn, Poland
tel. +48 58 692 40 00
fax +48 58 692 40 20
www.ensto.pl

This product card has been printed from Ensto´s web-pages. Please, observe our legal notice on the front page of www.ensto.com.
© Ensto 2015