48 PT / PT DIN - Junction, connection and domotic boxes - IP40



For brick walls

GW48004



48 PT - JUNCTION AND CONNECTION BOXES FOR SIDE-BY-SIDE ASSEMBLY - WHITE LID RAL 9016

Code	Outer dim. LxHxD (mm)	Compartment pre-arrangement	Pack Carton
GW 48 001	92x92x45	1	162
GW 48 002	118x96x50	1	114
GW 48 003	118x96x70	1	84
GW 48 004	152x98x70	1	64
GW 48 005	160x130x70	1	49

CHARACTERISTICS: surface embossing of the lids to facilitate painting.
External knurling of the base to improve mortar adherence.
Pre-arrangement for combined coupling (both horizontal and vertical) via the joining element GW48051.
Lid protected with heat-shrinking film that also contains the bag of fixing screws.
Mortar guard element assembled by pressing on the base opening.
ACCESSORIES SUPPLIED: ø3x25 mm screw kit for lid fixing. mortar guard element in cardboard supplied as standard in the packs and packed with paper banding.
NOTES: for the inputs, remove the knockouts after cutting the relative tangs with scissors.

GW48006



48 PT DIN - JUNCTION AND CONNECTION BOXES FOR SIDE-BY-SIDE ASSEMBLY WITH DIN RAIL INTEGRATED ON THE BACK-MOUNTING BOX - COLOUR: WHITE LID RAL 9016

Code	Outer dim. LxHxD (mm)	Compartment pre-arrangement	No. EN 50022 mod. per comp.	Domotic equipment coupling	Dispersible max power (W)	No. supports GW44720	Pack Carton
GW 48 006	196x152x75	2	4.5	DIN rail	11	2	34
GW 48 007	294x152x75	3	5	DIN rail	13	3	22
GW 48 008	392x152x75	4	5	DIN rail	17	4	17
GW 48 009	480x160x75	3	8	DIN rail	25	5	17
GW 48 010	516x202x90	3	9	DIN rail	29	5	9
GW 48 011	516x294x90	6	4	DIN rail	30	5	5

CHARACTERISTICS: surface embossing of the lids to facilitate painting. External knurling of the base to improve mortar adherence. Pre-arrangement for combined coupling (both horizontal and vertical) via the joining element GW48051. Lid protected with heat-shrinking film that also contains the bag of fixing screws. Mortar guard element assembled by pressing on the base opening.
ACCESSORIES SUPPLIED: GW48011 box supplied with 5 internal dividers. ø3x25 mm screw kit for lid fixing. Mortar guard element in cardboard supplied as standard in the packs and packed with paper banding.
APPLICATION: GW48006-GW48007-GW48008-GW48009-GW48010-GW48011 thanks to the DIN rail on the back-mounting box can also be used for KNX devices from the DIN rail, domotic devices for domestic range and video entryphone devices.
NOTES: for the inputs, remove the knockouts after cutting the relative tangs with scissors
GW48006-GW48007-GW48008-GW48009-GW48010-GW48011 boxes will be equipped with a DIN rail built into the back-mounting box from March 2013.

News ④=Available while stocks last ①=April 2013 ②=June 2013 ③=September 2013