Complementary items

GW68431



YELLOW-PAINTED METAL CONDUIT SUPPORT WITH SUPPORT FOR CABLES OF UP TO 20 M

Code	Outer dim. LxHxD (mm)	For distribution board type	Pack Carton
GW 68 431	350x715x435	Q-DIN 10	1
GW 68 433	350x770x520	Q-DIN 14/20	1

NOTES: the type of cable considered is H 07 RN - F 5 x 4 mm^2; the length varies according to the type of cable.
GW68433: Q-DIN protection system against the front drops.

GW68432



METAL CARRIER PAINTED IN YELLOW EQUIPPED WITH TWO WHEELS AND ROTATING DRUM TO WIND UP TO 50 M OF CABLE

Code	Outer dim. LxHxD (mm)	For distribution board type	Pack Carton
GW 68 432	495x1000x605	Q-DIN 14/20	1

NOTES: the type of cable considered is H 07 RN - F 5 x 4 mm^2; the length varies according to the type of cable. 1+1 flanges for socket-outlets IEC 309 16A and 32A.

GW46552



POLE SUPPORT KIT FOR 68 Q-DIN BOARDS

Code	For Q-DIN	Max sustainable load (kg)	Pack Carton
GW 46 552	14	12	1
GW 46 553	20	125	1

CHARACTERISTICS: fixed on the back of the boards. The maximum sustainable load values refer to Q-DIN boards.
APPLICATIONS: for application of boards on poles from 60 to 80mm.
ACCESSORIES SUPPLIED: 2 pieces. For the correct use of the kit, see the instructions sheet.

GW46446



SET OF 4 STEEL BRACKETS FOR FIXING SURFACE-MOUNTING BOARDS

Code	Material	For Q-DIN	Accessories supplied	Pack Carton
GW 44 621	Insulation	5	Self-tapping fixing screws	40/480
GW 46 446	Galvanised steel	10/14/20	Self-tapping fixing screws	20
GW 46 451	Stainless steel	10/14/20	Self-tapping fixing screws	20

NOTES: GW46446 and GW46451 - maximum supportable load 8kg for Q-DIN10, 12kg for Q-DIN14, and 15kg for Q-DIN20.

GW74061



ROUND MUSHROOM-HEAD EMERGENCY PUSH-BUTTONS, DIAM. 22MM

Code	Functions	For Q-DIN	Description	Pack Carton
GW 74 061	With holding	10/14/20	Mushroom head Ø 40	5/60

ACCESSORIES SUPPLIED: 3-seat contact-holding flange.

GW74201



CONTACTS - ITH= 10A - 240V AC

Code	Type	Category of use 240V ac15	Category of use 240V dc13	Colour	Pack Carton
GW 74 201	1 NO	3 A	0.27 A	Green	10/60
GW 74 202	1 NC	3 A	0.27 A	Red	10/60

CHARACTERISTICS: GW74202, suitable for opening the contact also in the event of it slightly sticking, in conformity with the EN 60947-5-1 standard.
Clip assembly on the contact-holder flanges.

GW40422



SECURITY LOCK

Code	Material	Pack Carton
GW 40 422	Pressure die-cast metal	1/10

ACCESSORIES SUPPLIED: 2 keys.
NOTES: All the keys and relative locks with the same product code are identical.

GW68436N



Q-DIN TRANSPORTATION HANDLE

Code	Description	For distribution board type	Pack Carton
GW 68 436 N	Handle	Q-DIN 10/14/20 and additional modules	1/10

GW68292



BLANK LIDS FOR IEC 309 CAP AND INTERLOCKED SWITCHED SOCKET-OUTLETS

Code	Description	Dimensions LxH (mm)	Pack Carton
GW 68 292	Lid for IEC 309 16A	85x75	1/10
GW 68 293	Lid for IEC 309 32A	95x80	1/10
GW 68 294	Lid for IEC 309 63A	110x100	1/10
GW 66 703 N	Lid for vertical interlocked socket-outlet 16-32A	220x103	1/10
GW 66 705 N	Lid for vertical interlocked socket-outlet 63A	270x145	1/10

News ④=Available while stocks last ①=April 2013 ②=June 2013 ③=September 2013