

40 CD - Protected decorative enclosures - IP40











Smoked transparent door - Smooth walls

GW40043



ENCLOSURES PRE-ARRANGED FOR TERMINAL BLOCK - WHITE RAL 9016

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Installable terminal blocks	Dispersible power (W)	Pack Carton
GW 40 043	8	200x180x100	1xGW40401	15	14
GW 40 045	12	280x225x100	1xGW40402	22	9
GW 40 047	24 (12X2)	280x350x100	2xGW40401	25	6
GW 40 049	36 (18x2)	400x400x130	2xGW40402	45	2
GW 40 051	54 (18x3)	400x550x130	2xGW40402	63	2
GW 40 053	72 (18x4)	400x850x150	4xGW40402	75	1

ACCESSORIES SUPPLIED: module masks, circuit labels.
GW40049, GW40051, GW40053, equipped with removable frame for carrying out wiring operations outside the enclosure.
NOTES: dispersible power calculated according to IEC 60670-24. For the perforations, use the GW52401 milling cutter.
To restore the double insulation, use the relative accessories (module masks, screwcaps, or brackets for surface-mounting).
CHARACTERISTICS: Thermo-pressure with ball equal to 70°C.

GW40048



ENCLOSURES FITTED WITH TERMINAL BLOCK - WHITE RAL 9016

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 044	12	280x225x100	22	9
GW 40 046	24 (12X2)	280x350x100	25	6
GW 40 048	36 (18x2)	400x400x130	45	2

ACCESSORIES SUPPLIED: terminal block, module masks, circuit labels.
GW40044: Terminal block N (mm^2) (3x25) + (10x10) and terminal block T (mm^2) (3x25) + (10x10);
GW40046: Terminal block N (mm^2) 2x[(1x25) + (7x10)] and terminal block T (mm^2) 2x[(1x25) + (7x10)];
GW40048: Terminal block N (mm^2) 2x[(1x25) + (7x10)] and terminal block T (mm^2) 2x[(1x25) + (7x10)];
fitted with removable frame, to carry out the wiring operations outside the enclosure.
NOTES: dispersible power calculated according to IEC 60670-24. For the perforations, use the GW52401 milling cutter.
To restore the double insulation, use the relative accessories (module masks, screwcaps or wall mounting brackets).
CHARACTERISTICS: Thermo-pressure with ball equal to 70°C.