COMPLETE DEVICES

GW26222



WALL-MOUNTING INDUSTRIAL SOCKET-OUTLETS TO IEC 309 STANDARD - COLOUR GREY RAL 7035 - IP44

Code	Rated current (A)	No. of poles	Rated voltage	Reference h	Outer dim. LxHxD (mm)	Pack Carton
GW 26 222	16	2P+E	230V ac	6	64x80x97	5/40
GW 26 223	16	3P+E	400V ac	6	64x80x97	5/40

Rated voltage with alternated current.

CHARACTERISTICS: fitted for fixing the earth terminal GW26407.

ACCESSORIES SUPPLIED: cable gland for conduits of max 20mm external diameter.

GW27415



INDICATOR LAMPS- MAX 15W - GREY RAL 7035 - IP55

Code	Diffuser colour	Rated voltage	Lampholder type	Outer dim. LxHxD (mm)	Pack Carton
GW 27 415	Red	230V ac	E14	66x82x95	5/40
GW 27 416	Green	230V ac	E14	66x82x95	5/40
GW 27 417	Yellow	230V ac	E14	66x82x95	5/40
GW 27 418	Transparent	230V ac	E14	66x82x95	5/40
GW 27 419	Light blue	230V ac	E14	66x82x95	5/40

Rated voltage with alternated current. Supplied without lamp.

CHARACTERISTICS: fitted for fixing the earth terminal GW26407.

ACCESSORIES SUPPLIED: cable gland for conduits of max 20mm external diameter.

GW27424



ELECTRONIC FLASHLIGHTS- MAX 25W - GREY RAL 7035 - IP55

Code	Diffuser colour	Rated voltage	Flash frequency	Lampholder type	Outer dim. LxHxD (mm)	Pack Carton
GW 27 421	Red	24V ac	1 Hz	E14	66x82x95	1/12
GW 27 422	Red	230V ac	1 Hz	E14	66x82x95	1/12
GW 27 423	Yellow	24V ac	1 Hz	E14	66x82x95	1/12
GW 27 424	Yellow	230V ac	1 Hz	E14	66x82x95	1/12

Supplied without lamp.

CHARACTERISTICS: fitted for fixing the earth terminal GW26407.

ACCESSORIES SUPPLIED: cable gland for conduits of max 20mm external diameter.

GW26417



BUZZERS FOR SIGNALLING - GREY RAL 7035 - IP40

Code	Rated voltage	Sound intensity	Frequency impulses of sound	Outer dim. LxHxD (mm)	Pack Carton
GW 26 417	24V ac	70 dB (at 1 m)	1 Hz	64x80x59	1/12
GW 26 427	230V ac	70 dB (at 1 m)	1 Hz	64x80x59	1/12

CHARACTERISTICS: fitted for fixing the earth terminal GW26407, GW26417 consumption 60mA.

ACCESSORIES SUPPLIED: cable gland for conduits of max 20mm external diameter.

GW27431A



INFRARED ADJUSTABLE MOVEMENT DETECTOR WITH TWILIGHT SENSOR 230V - 50/60HZ - IP54

Code	Range of action	Duration adjustment	Treshold adjustment	Outer dim. LxHxD (mm)	Pack Carton
GW 27 431 A	12 m	8 sec. - 35 min.	2 - 2000 lux	80x110x80	1

CHARACTERISTICS: Horizontal cover range 130°, adjustable sensor: 90°.

Incandescent lamps (230V ac) and halogen (230Vac): max. 600W, fluorescent loads: 3AX.

GW26419



TWILIGHT SENSOR WITH RELAY OUTPUT - GREY RAL 7035 - 230V - 50HZ - IP55

Code	Treshold adjustment	Output contacts	Outer dim. LxHxD (mm)	Pack Carton
GW 26 419	1-100 lux	1NO 10A(AC1)/5A(AC15) 250V ac	64x80x59	1/12

Complete insulation can be obtained by using the screwcaps GW44622.

CHARACTERISTICS: fitted for fixing the earth terminal GW26407.

ACCESSORIES SUPPLIED: cable gland for conduits of max 20mm external diameter.

①=April 2013 ②=June 2013 ③=September 2013