42 RV - Watertight enclosures for emergency manoeuvres - IP55



Equipment with illuminable push-button

GW42201



WATERTIGHT ENCLOSURE FOR EMERGENCY SYSTEMS - EQUIPPED WITH ILLUMINATED PUSH-BUTTON FOR LOCALISATION, AND TWO CONTACTS (1NA+1NC) - ITH 10A TO 240V PREARRANGEMENT FOR USE OF GREEN LED TO SIGNAL GOOD CONDITION OF EMERGENCY

Code	Outer dim. LxHxD (mm)	Colour	Pack Carton
GW 42 201	120x120x50	Red RAL 3000	1/10

CHARACTERISTICS: possibility of mounting on flush-mounting box GW24403. 2-seat contact-holding flange.
ACCESSORIES SUPPLIED: substitute button key to enable configuration of manual or automatic action upon the breaking of the glass, self-adhesive pictograms "Break the glass" and "Press the button", screwcaps for double insulation, screws and accessories for the sealing of the frontal.
"Sicur Push" breakable glass.
NOTES: substitute contacts NO: GW74201, NC: GW74202 lamps for locating push-button: GW30951 12V~/-, GW30952 24V~/-, GW30943 230V~; green LEDs for indicating emergency circuit integrity: GW30958 from 12 to 24V~/-, GW30959 from 110 to 230V~/-, GW30960 from 48V~/-;
To restore the double insulation use the relative screwcaps supplied.

Fitted with hole Ø 22 mm

GW42204



WATERTIGHT ENCLOSURE FOR EMERGENCY SYSTEMS FITTED WITH HOLE Ø 22MM

Code	Outer dim. LxHxD (mm)	Colour	Pack Carton
GW 42 204	108x180x100	Red RAL 3000	1/10

ACCESSORIES SUPPLIED: Door fitted with lock with 2 keys.
"Sicur Push" breakable glass.
To restore the doubleinsulation, use the relative accessories supplied (module masks and brackets for surface-mounting (GW44621).
NOTES: compatible with momentary push-buttons, emergency mushroom-head push-buttons, selectors, and indicators Ø 22mm of the 74 PS range.
To increase the number of contacts that can be installed, use the 5-seat flange - GW74203.

With DIN rail

GW42202



WATERTIGHT ENCLOSURES FOR EMERGENCY USE AND SPECIAL APPLICATIONS WITH RAIL DIN

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
Colour: Red RAL 3000				
GW 42 206	4	108x180x100	12	1/10
GW 42 202	8	180x180x100	18	1/10
Colour: Grey RAL 7035				
GW 42 207	4	108x180x100	12	1/10
GW 42 208	8	180x180x100	18	1/10

ACCESSORIES SUPPLIED: door equipped with security lock with 2 keys, self-adhesive pictogram "Break the glass", user label and screwcaps for double insulation.
"Sicur Push" breakable glass.
NOTES: dispersible power calculated according to IEC 60670-24.
To restore the double insulation use the relative accessories supplied (module mask and screwcaps) or brackets for surface mounting GW44621.