

Switch-disconnector, 3 p, 1250A, frame size 4

Part no. LN4-1250-I
Article no. 112014

Similar to illustration

Technical data ETIM 5.0

Low-voltage industrial components (EG000017) / Switch disconnector (EC000216)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnector (ecl@ss8-27-37-14-03 [AKF060009])

Version as switch disconnector compact		Yes
Version as main switch		Yes
Version as maintenance-/service switch		Yes
Version as safety switch		No
Version as emergency stop installation		Yes
Max. rated operation voltage Ue AC	V	400
Rated permanent current Iu	A	1250
Rated operation power AC-3, 400 V	kW	710
Rated operation power at AC-23, 400 V	kW	710
Conditioned rated short-circuit current Iq	kA	100
Number of poles		3
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		0
Motor drive optional		Yes
Motor drive integrated		No
Voltage release optional		Yes
Device construction		Built-in device fixed built-in technique
Suitable for ground mounting		Yes
Suitable for front mounting		No
Suitable for front mounting center		No
Suitable for distribution board installation		Yes
Suitable for intermediate mounting		Yes
Type of control element		Rocker lever
Interlockable		Yes
Connection type main current circuit		Bolt connection
Degree of protection (IP), front side		IP20

© 12/2014 by Eaton Industries GmbH