Product data sheet
Characteristics

A9MEM3365
iEM3365 energy meter - 125 A - BACnet - 1 digital I - 1 digital O - multi-tariff



Main

Range of product	Acti 9 iEM3000
Device short name	IEM3365
Product or component type	Energy meter

Complementary

Poles description	1P + N 3P 3P + N
Type of measurement	Active and reactive power Current Voltage Active and reactive energy
Device application	Sub billing Multi-tariff Partial meter
Accuracy class	Active energy: class B according to EN 50470-3 Active energy: class 1 according to IEC 61557-12 Active energy: class 1 according to IEC 62053-21
Input type	Direct input
[In] rated current	125 A
Rated voltage	173...480 V 100...277 V
Network frequency	50 Hz 60 Hz
Technology type	Electronic
Display type	LCD display
Sampling rate	32 samples/cycle
Maximum value measured	99999999.9 kWh
Communication port protocol	BACnet : 9.6, 19.2, 38.4, 57.6, 76.8 kbauds, insulation: 4000 V
Local signalling	Overload : alarm Accuracy checking : flashing LED (yellow) Power ON : indicator light (green)
Number of inputs	1 digital
Number of outputs	1 digital (static)
Mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Screw terminals 50 mm²
Overvoltage category	III

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Standards	IEC 61036 IEC 61557-12 IEC 62053-21 IEC 62053-23 IEC 61010
Product certifications	MID conforming to EN 50470-3 MID conforming to EN 50470-1

Environment

IP degree of protection	Body : IP20 conforming to IEC 60529 Front panel : IP40 conforming to IEC 60529
Pollution degree	2
Colour	White
9 mm pitches	14
Width	126 mm
Height	103.2 mm
Depth	69.3 mm

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1415 - Schneider Electric declaration of conformity
REACh	Reference contains SVHC above the threshold - go to CaP for more details
Product environmental profile	Available
Product end of life instructions	Available Download End Of Life Manual