SIEMENS

Product data sheet 5SL6325-6



Similar to image

CIRCUIT BREAKER 400V 6KA, 3POLE, B, 25A

Technical data:		
mounting position		any
Height	mm	90
Width	mm	54
Depth	mm	76
Mounting depth	mm	70
Current / for AC / rated value	A	25
Tripping characteristic class		B
Supply voltage		
• for AC / rated value	V	400
• with multi-phase operation / with AC / rated value	V	400
Supply voltage frequency / rated value	Hz	50
Operating voltage		
• minimum	V	24
• with multi-phase operation / with AC / maximum	V	440
• for DC / rated value / maximum	V	60
Number of poles		3
Number of poles /note		3P
Switching capacity current		

subject to modifications
© Copyright Siemens AG 2013

• in accordance with IEC 60947-2 / rated value	kA	6
• acc. to EN 60898 / rated value	kA	6
Active power loss / at rated value current / with AC / in warm operating state / per pole	W	2.5
Number of pitch units for width		3
Product feature / sealable		Yes
Protection class IP		IP20, with connected conductors
Degree of pollution		2
Influence of the surrounding temperature		Periodically +55°C, max. 95% humidity
Ambient temperature	°C	-25 … +45
Ambient temperature / during storage	°C	-40 … +75
Mechanical operating cycles as operating time / typical		20,000
Product equipment / touch-protection		Yes
type of voltage		AC/DC
Insulation voltage		
• with multi-phase operation / with AC / rated value	V	440
Conductor cross-section that can be connected		
• solid	mm²	0.75 … 35
• multibrin	mm²	0.75 … 35
• finely stranded		
• with wire end processing	mm²	0.75 … 25
Tightening torque		
• with screw-type terminals	N·m	2.5 … 3
Product feature		
• [not supplied - silicon-free]		Yes
• halogen-free		Yes
Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30		6
Item designation / according to DIN EN 61346-2		F
Device tag / according to DIN EN 81346-2		F

Certificates/approvals:

General Product Approval					Declaration of Conformity
CEBEC	GOST	IMQ	other	VDE	EG-Konf.

other

other

Further information:

© Copyright Siemens AG 2013

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
http://support.automation.siemens.com/WW/view/en/5SL6325-6/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SL6325-6

CAx-Online-Generator
http://www.siemens.com/cax

Tender specifications
Datanorm GAEB81 GAEB83 RTF TXT



last change: Feb 18, 2013

© Copyright Siemens AG 2013