SIEMENS

Data sheet 6ES7241-1AH32-0XB0

SIMATIC S7-1200, COMMUNICATION MODULE CM 1241, RS232, 9 PIN SUB D (MALE), SUPPORTS MESSAGE BASED FREEPORT



Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, max.	200 mA; From backplane bus 5 V DC
Power loss	
Power loss, typ.	1.1 W
Interfaces	
Number of interfaces	1
Interface physics, RS 232C (V.24)	Yes
Point-to-point	
• Cable length, max.	10 m
Ambient conditions	
Free fall	
• Fall height, max.	0.3 m; five times, in dispatch package

Changes preserved
© Copyright Siemens AG

Ambient temperature during operation	
• permissible temperature range	-20 °C to +60 °C horizontal mounting, -20 °C to 50 °C vertical mounting, 95% humidity, non-condensing
• permissible temperature change	5°C to 55°C, 3°C / minute
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Air pressure acc. to IEC 60068-2-13	
• Operation, min.	795 hPa
• Operation, max.	1 080 hPa
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
Relative humidity	
• permissible range (without condensation) at 25 °C	95 %

Dimensions	
Width	30 mm
Height	100 mm
Depth	75 mm

Weights	
Weight, approx.	150 g

last modified: 30.09.2015

Changes preserved
© Copyright Siemens AG