DPX™-IS 250 isolating switches
63 to 250 A



0 266 37



0 266 47



XL³ mounting accessories **p. 222, 230, 240**

Dimensions **see e-catalogue**
Electrical characteristics **p. 170**

Isolating switches for on-load circuit breaking by visible isolation and positive action of the contacts
Padlock integrated in the handle
Connection with cage terminals
Supplied with terminal shields
Conform to IEC 60947-3
Category of use AC 23 A
Accept the same electrical auxiliaries as the DPX (p. 144)
Can be mounted on rail ⎓ or on plate in XL³ enclosures

DPX-IS with release

Can be associated with a residual current relay with separate coils (p. 145), supplied without shunt trip

Pack	Cat.Nos 3P	Cat.Nos 4P	
			Front handle
1	0 266 30	0 266 34	63 A
1	0 266 31	0 266 35	100 A
1	0 266 32	0 266 36	160 A
1	0 266 33	0 266 37	250 A
			Right-hand side handle
1	0 266 40	0 266 44	63 A
1	0 266 41	0 266 45	100 A
1	0 266 42	0 266 46	160 A
1	0 266 43	0 266 47	250 A
			Left-hand side handle
1	0 266 50	0 266 54	63 A
1	0 266 51	0 266 55	100 A
1	0 266 52	0 266 56	160 A
1	0 266 53	0 266 57	250 A

DPX-IS without release

Pack	Cat.Nos 3P	Cat.Nos 4P	
			Front handle
1	0 266 02	0 266 06	160 A
1	0 266 03	0 266 07	250 A
			Right-hand side handle
1	0 266 12	0 266 16	160 A
1	0 266 13	0 266 17	250 A
			Left-hand side handle
1	0 266 22	0 266 26	160 A
1	0 266 23	0 266 27	250 A

Mounting on rail ⎓

Pack	Cat.Nos	
		Rail ⎓ fixing plate
1	0 262 39	For DPX-IS 250

Rotary handles

Pack	Cat.Nos	
		Direct for emergency use
		For mounting instead of standard handle
1	0 266 89	Front and right-hand side handle
1	0 266 90	Left-hand side handle
		Vari-depth handle IP 55
		Comprising: connecting rod, bracket, self-adhesive drilling template, fixing accessories (seal to maintain the IP protection up to IP 55, door lock mechanism)
1	0 266 86	For front and side handle device
1	0 266 87	For front and side handle device for emergency use
		To be ordered with Cat.Nos 0 266 89 or 0 266 90

Accessories

Pack	Cat.Nos	
		Cage terminals
1	0 262 88[1]	Set of 4 For cable 185 mm² (rigid) or 150 mm² (flexible) for DPX 250 ER and DPX-IS 250
		Spreaders
1	0 273 22	Set of upstream and downstream spreaders
		Rear terminals
		Used to convert the fixed version with front terminals to the fixed version with rear terminals
	3P / 4P	
1	0 265 10 / 0 265 11	Set of upstream and downstream rear terminals
		Terminal shields
1	0 262 87	Set of 2
		Padlock
		For locking mechanism in open position (factory assembled)
1	0 266 92	Ronis
		Interlock
1	0 266 94	Provides closing of 2 devices at the same time (factory assembled)

For detailed dimensions, **see e-catalogue**

1: Can not be mounted on side by side mounted earth leakage modules 160 A