Product data sheet
Characteristics

MTN5510-1219
ARGUS Presence Master with IR, relay 2-gang, polar white



Main

Range of product	ARGUS presence detector
Product or component type	Presence detector
Function available	Master function
Number of channels	2
Time delay	10 s...30 min 5...120 min
Horizontal detection angle	0...360 °
Detection zone	Radius 7 m
Colour tint	Polar white
Colour code	RAL 9010
Material	PC (polycarbonate) brilliant
Type of packing	Carton
IP degree of protection	IP20

Complementary

Type of setting	Light sensitivity adjustable Time adjustment
Control type	Remote control
Device mounting	Ceiling
Mounting height	2.5 m
[Ue] rated operational voltage	220/230 V
Output current	10 A 4 A
Network frequency	50/60 Hz
Light intensity adjustment	10...1000 lux
Input compatibility	Pushbuttons and electronic insert
Input function	2 x external triggering over PL
Load type	Energy saving lamp : : 100 VA Low voltage halogen lamp with electronic transformer : : 1050 VA - 230 V AC Low voltage halogen lamp with wire-wound transformer : : 500 VA - 230 V AC Incandescent lamp : 2200 W - 230 V AC Capacitive : : 10 A, 140 µF - 230 V AC Motor : : 1000 VA - 230 V AC Halogen lamp : 2000 W - 230 V AC

Environment

Ambient air temperature for operation	0...25 °C
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Not Green Premium product
Product environmental profile	Available
Product end of life instructions	Available

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.