	Description	part no. Article no.
XI/OC		
• Compact I/O system for connection to XC100/200 Modular PLCs • XC100/200 expandable with up to 15 XI/OC modules • Optionally, screw terminals or spring-cage terminals for digital/analog modules • UL/CSA approvals		
Digital modules 	8 inputs, 24 V DC	**XIOC-8DI** 257891
	16 inputs, 24 V DC	**XIOC-16DI** 257892
	32 inputs, 24 V DC	**XIOC-32DI** 267411
	8 outputs, 24 V DC, 0.3 A	**XIOC-8DO** 257894
	12 relay outputs	**XIOC-12DO-R** 257897
	16 outputs, 24 V DC, 0.3 A	**XIOC-16DO** 257896
	16 outputs, 24 V DC, 0.8 A, short-circuit proof	**XIOC-16DO-S** 257895
	16 connections, 4 inputs, 12 freely parameterizable as inputs/outputs, 24 V DC outputs 0.5 A	**XIOC--16DX** 262322
	32 outputs, 24 V DC, 0.2 A	**XIOC-32DO** 267413
Analog modules 	Inputs 8 Inputs 4 - 20 mA	**XIOC-8AI-I2** 262549
	Inputs 8 voltage input 8 - 10 V	**XIOC-8AI-U1** 257899
	Inputs 8 voltage inputs, ±10 V	**XIOC-8AI-U2** 257900
	Inputs 4 inputs for temperature monitoring, Pt100/1000	**XIOC-4T-PT** 257901
	Inputs 4 inputs for thermocouples Type K, J, L, B, N, E, R, S, T	**XIOC-4AI-T** 289933
	Outputs 2 outputs ± 10 V	**XIOC-2AO-U2** 257904
	Outputs 2 Outputs 0 - 10 V, 2 Outputs 4 - 20 mA	**XIOC-2AO-U1-2AO-I2** 257902
	Outputs 4 Outputs 0 - 10 V	**XIOC-4AO-U1** 257903
	Combination modules, 2 inputs and 1 output, 0 - 10 V 1 ms conversion time	**XIOC-2AI-1AO-U1** 262409
	Combination modules, 2 inputs and 1 output, 0 - 10 V, 0 - 20 mA 1 ms conversion time, individual changeover	**XIOC-2AI-1AO-U1-L1** 281545
	Combination modules, 4 inputs and 2 outputs, 0 - 10 V 1 ms conversion time	**XIOC-4AI-2AO-U1** 262405
	Combination modules, 4 inputs and 2 outputs, 0 - 10 V, 0 - 20 mA 1 ms conversion time, individual changeover	**XIOC-4AI-2AO-U1-I1** 281544
Counter modules 	1 input up to 100 kHz, 24 V DC, 5 V DC, 2 digital transistor outputs, opto-isolated, 24 V DC 30 pole plug required for counter module	**XIOC-1CNT-100KHZ** 257906
	2 inputs up to 100 kHz, (24 V DC or 5 V diff), 4 digital transistor outputs, opto-coupled, 24 V DC 30 pole plug required for counter module	**XIOC-2CNT-100KHZ** 257907
	2 incremental encoders up to 400 kHz, 5 V DC, 2 analog outputs, ±10 V	**XIOC-2CNT-2AO-INC** 262417
Communication modules 	PROFIBUS-DP master module	**XIOC-NET-DP-M** 257908
	PROFIBUS DP slave module	**XIOC-NET-DP-S** 286419
	Suconet K master module	**XIOC-NET-SK-M** 289982
	Serial interface RS232C, RS485, RS422 Operating modes: transparent mode, MODBUS master/slave, SUCOM-A, Suconet-K slave	**XIOC-SER** 267191
	Serial interface RS232C, RS485, RS422 Operating modes: transparent mode, MODBUS master/slave, SUCOM-A, DNP3 protocol	**XIOC-TC1** 135265