CADDY® PYRAMID ST Fixed Strut Supports – PSF6C (360463)







- Provides superior support for pipe, conduit, duct, cable tray and equipment
- Foam bottom offers low abrasion interface for better roof membrane protection
- Compatible with roof surfaces including single ply, bituminous, metal and spray foam
- Provides superior load distribution, even with varying rooftop surfaces
- Ready to use out of the box, saving installation time and labor
- Multiple sizes and load ratings offer the ability to tailor the solution to the application
- Easy to transport to the roof
- Hot-dip galvanized and UV stabilized for long lasting performance
- Supports green building requirements; thermoplastic bases are made from recycled material and can contribute to earning LEED credits





Part Number	PSF6C
Article Number	360463
Material	Polyethylene Polypropylene Steel
Finish	Hot-dip galvanized
Temperature	-45 to 65 °C -50 to 150 °F
Static Load Safety Factor	3:1
Length 1 (L1)	6" 152 mm
Length 2 (L2)	8" 203 mm
Height (H)	4.8" 122 mm
Width (W)	6" 152 mm
Surface Area	41 in² 26,452 mm²
Unit Weight	1 lb 0.5 kg
Static Load (F)	300 lb 1,334 N
Standard Packaging Quantity	20 pc

Part Number	PSF6C
UPC	78285684299
UNSPSC	30151609
ETIM	EC011776

Static load at 73.1 kPa (10.6 psi) roof loading. Contact project or roofing engineer for maximum allowable load on individual project roof system.

WARNING
ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2014 ERICO International Corporation. All rights reserved.
CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.